Product data sheet Characteristics

9001K71

joystick controller \emptyset 30 - horizontal - 3 position spring return - w/o contact

| Main | |
|-------------------------------|-----------------------|
| Range of product | Harmony 9001K |
| Product or component type | Joystick controller |
| Component name | 9001K |
| Bezel material | Chromium plated metal |
| Mounting diameter | 30 mm |
| Shape of signaling unit head | Octagonal |
| Operator position information | 3 positions |
| Type of operator | Spring return |
| Contacts type and composition | Without contact block |
| Operator profile | Operating shaft |
| Shaft length | 80 mm |

Complementary

| Operating position | Any position |
|--------------------|--------------|
| Product weight | 0.372 kg |

Environment

| Environment | |
|--|--|
| Standards | CSA C22-2 No 14 EN/IEC 60947-5-1 IEC 60947-1 IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 |
| Protective treatment | TC |
| Ambient air temperature for storage | -4070 °C |
| Ambient air temperature for operation | -2570 °C |
| Vibration resistance | 7 gn (f = 2500 Hz) conforming to IEC 60068-2-6 |
| Shock resistance | 50 gn conforming to IEC 60068-2-27 |
| Class of protection against electric shock | Class II conforming to IEC 60536 |
| IP degree of protection | IP66 conforming to IEC 60529 IP66 conforming to NF C 20-010 |
| NEMA degree of protection | NEMA 1 NEMA 12 NEMA 13 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 6 |
| RoHS EUR status | Will be compliant |
| RoHS EUR conformity date | 2Q2009 |