SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART A information is below)

1. IDENTIFICATION OF TH	SUBSTANCE/PREPARATION AND OF THE COM	IPANY
1.1 Product name	: SYLGARD(R) 527 A&B SILICONE DIELECTRIC below)	C GEL (PART A information is
1.2 Identified uses	: Electrical and electronic applications	
Uses advised against	: None known.	
1.3 Company	: Dow Corning Europe S.A. rue Jules Bordet - Parc Industriel - Zone C B-7180 Seneffe Belgium	
E-mail address (Safety Data Sheet)	: sdseu@dowcorning.com	
Customer Service	: English Tel: +49 6 Deutsch Tel: +49 6 Français Tel: +32 6 Italiano Tel: +32 6 Español Tel: +32 6	11237500 4511149 4511170
1.4 Emergency Phone Number	 Fax: +32 6 Dow Corning (Barry U.K. 24h) Dow Corning (Wiesbaden 24h) Dow Corning (Seneffe 24h) Tel: +44 1 Tel: +44 6 Tel: +42 6 	446732350 1122158

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to EU Directives 67/548/EEC or 1999/45/EC:

Not hazardous.

2.2 Label elements

Labelling according to EEC Directive

No special packaging or labelling requirements.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART A information is below)

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone

According to EU Directives 67/548/EEC or 1999/45/EC:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification
No hazardous ingred	lients.				

According to Regulation (EC) No. 1272/2008:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification

No hazardous ingredients.

CLP classifications are based on all current available data including from known international organizations. These classifications are subject to revision as more information becomes available.

4. FIRST AID MEASURES

4.1 Description of First Aid Measures:

On contact with eyes	:	No first aid should be needed.
On skin contact	:	No first aid should be needed.
If inhaled	:	No first aid should be needed.
On ingestion	:	No first aid should be needed.

5. FIRE-FIGHTING MEASURES

5.1	Suitable extinguishing media	:	On large fires use dry chemical, foam or water spray (fog). On small fires use carbon dioxide (CO2), dry chemical or water spray. Water can be used to cool fire exposed containers.
	Unsuitable extinguishing media	:	None known.
5.2	Hazards during fire fighting	:	None known.
	Hazardous Combustion Products	:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.
5.3	Special protective equipment/procedures	:	A self-contained respirator and protective clothing should be worn. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART A information is below)

keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

6.1	Personal precautions, protective equipment and emergency procedures	:	Wear proper protective equipment.
6.2	Environmental precautions	:	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.
6.3	Methods and materials for containment and cleaning up	:	Determine the need to evacuate or isolate the area according to your local emergency plan. Very large spills should be contained by bunding, etc procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product produces an extremely slippery surface.

7. HANDLING AND STORAG	E	
7.1 Advice on safe handling	:	Avoid eye contact. General ventilation is recommended. Do not empty into drains.
7.2 Advice on storage	:	Do not store with oxidizing agents. Storage temperature: minimum -15 °C, maximum 35 °C
7.3 Specific uses	:	Refer to technical data sheet available on request.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Name	(CAS-No.	Exposure Limits
None of the components have	assig	gned exposure lin	its.
8.2 Exposure controls			
Engineering Controls	:	Ventilation : R	efer to Section 7.1
Personal protection equipme	<u>ent</u>		
Respiratory protection	:	Respiratory pro	ptection is not normally required.
Hand protection	:	Gloves are not	normally required.
Eye/face protection	:	Safety glasses	should be worn.

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART A information is below)

Skin protection	:	Protective equipment is not normally necessary.	
Hygiene measures	:	Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.	
Additional information	:	These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these types of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.	
<u>Environmental exposure</u> <u>controls</u>	:	Refer to section 6 and 12.	

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	:	Liquid
Colour	:	Colorless
Odour	:	None
Boiling point/range	:	> 65 °C
Flash point	:	121 °C (Pensky-Martens Closed Cup)
Explosive properties	:	No
Specific Gravity	:	0.97
Viscosity	:	415 cSt at 25°C.
Oxidizing properties	:	No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

10. S	TABILITY AND REACTIV	/IT	Y
10.1	Reactivity	:	None known.
10.2	Stability	:	Stable under normal usage conditions.
10.3	Possibility of hazardous reactions	:	None known.
10.4	Conditions to avoid	:	None established.
10.5	Materials to avoid	:	Can react with strong oxidising agents.

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART A information is below)

10.6 Hazardous decomposition products : Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Acute toxicity:		
On contact with eyes	:	May cause temporary discomfort.
On skin contact	:	No adverse effects are normally expected.
If inhaled	:	No adverse effects are normally expected.
On ingestion	:	No adverse effects are normally expected.
Chronic toxicity:		
On skin contact	:	No adverse effects are normally expected.
If inhaled	:	No adverse effects are normally expected.
On ingestion	:	No adverse effects are normally expected.
<u>Toxicokinetics, metabolism</u> and distribution	:	No specific information is available.
<u>Other Health Hazard</u> <u>Information</u>	:	Product may emit formaldehyde vapour at temperatures above 180°C in the presence of air. Formaldehyde vapour is a suspected carcinogen, toxic byinhalation and irritating to eyes and the respiratory system. Exposure limits should be strictly respected.

¹ Based on product test data. ² Based on test data from sim

² Based on test data from similar products.

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity effects

No adverse effects on aquatic organisms.

12.2 Persistence and degradability

Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded.

12.3 Bioaccumulation

No bioaccumulation potential.



According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART A information is below)

12.4 Release to waters / Mobility in soil

Fate and effects in waste water treatment plants:

:

Removed > 90% by binding onto sewage sludge. No adverse effects on bacteria. The siloxanes in this product do not contribute to the BOD.

13. DISPOSAL CONSIDERATIONS

Product and packaging disposal

Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

14. TRANSPORT INFORMATION

Road / Rail (ADR/RID)

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture			
<u>Status</u>			
EINECS	: All ingredients listed or exempt.		
TSCA	: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.		

According to article 31 and Annex II of the EU REACH Regulation

Version: 2.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART A information is below)

16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

Source of information: Internal data and publically available information

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART B information is below)

1. IDENTIFICATION OF TH	UBSTANCE/PREPARATION AND OF THE COMPA	NY
1.1 Product name	SYLGARD(R) 527 A&B SILICONE DIELECTRIC G	EL (PART B information is
1.2 Identified uses	Electrical and electronic applications	
Uses advised against	None known.	
1.3 Company	Dow Corning Europe S.A. rue Jules Bordet - Parc Industriel - Zone C B-7180 Seneffe Belgium	
E-mail address (Safety Data Sheet)	sdseu@dowcorning.com	
Customer Service	English Tel: +49 61123 Deutsch Tel: +49 61123 Français Tel: +32 64511 Italiano Tel: +32 64511 Español Tel: +32 64511	37500 1149 1170
1.4 Emergency Phone Number	Fax: +32 6488 Dow Corning (Barry U.K. 24h) Dow Corning (Wiesbaden 24h) Dow Corning (Seneffe 24h)	732350 2158

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

According to EU Directives 67/548/EEC or 1999/45/EC:

:

Not hazardous.

2.2 Label elements

Labelling according to EEC Directive

S-phrases

S9 Keep container in a well-ventilated place. S16 Keep away from sources of ignition - no smoking.

2.3 Other hazards

Some hydrogen gas may be released. Hydrogen is flammable and can form explosive mixtures with air.



According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART B information is below)

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical characterization: Silicone

According to EU Directives 67/548/EEC or 1999/45/EC:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification
No hazardous ingred	lients.				

According to Regulation (EC) No. 1272/2008:

Name	CAS-No.	EINECS/ ELINCS No.	REACH Registration Number	Conc. (% w/w)	Classification
------	---------	--------------------------	---------------------------------	------------------	----------------

No hazardous ingredients.

CLP classifications are based on all current available data including from known international organizations. These classifications are subject to revision as more information becomes available.

4. FIRST AID MEASURES

4.1 Description of First Aid Measures:

On contact with eyes	:	No first aid should be needed.
On skin contact	:	No first aid should be needed.
If inhaled	:	No first aid should be needed.
On ingestion	:	No first aid should be needed.

5. FIRE-FIGHTING MEASURES

5.1	Suitable extinguishing media	:	On large fires use AFFF alcohol compatible foam or water spray (fog). On small fires use AFFF alcohol compatible foam, CO2 or water spray (fog). Water can be used to cool fire exposed containers. Most fire extinguishing media will cause hydrogen release. Thus, in poorly ventilated or confined spaces, the accumulation of hydrogen may result in flash fire or explosion if ignited. Applying foam may release flammable hydrogen gas that can be trapped under the foam.
	Unsuitable extinguishing media	:	Dry powder. Do not allow extinguishing medium to contact container contents.
5.2	Hazards during fire fighting	:	None known.
	Hazardous Combustion Products	:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely

SAFETY DATA SHEET

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART B information is below)

		burned carbon compounds. Formaldehyde. Hydrogen. A self-contained respirator and protective clothing should be worn. Determine the need to
		evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

6. ACCIDENTAL RELEASE MEASURES

6.1	Personal precautions, protective equipment and emergency procedures	:	Wear proper protective equipment.
6.2	Environmental precautions	:	Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.
6.3	Methods and materials for containment and cleaning up	:	Determine the need to evacuate or isolate the area according to your local emergency plan. Very large spills should be contained by bunding, etc procedures. Mop, wipe or soak up with absorbent material and place in a vented container. The spilled product produces an extremely slippery surface.

7. HANDLING AND STORAGE 7.1 Advice on safe handling : General ventilation is required. Avoid eye contact. Do not empty into drains. 7.2 Advice on storage : Keep container closed and store away from water or moisture. This product may evolve hydrogen on storage. Do not store in or use glass containers. Storage temperature: minimum -15 °C, maximum 35 °C 7.3 Specific uses : Refer to technical data sheet available on request.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters					
Name	CAS-No.	Exposure Limits			
None of the components have as	signed exposure lim	its.			
8.2 Exposure controls					
Engineering Controls	: Ventilation : Re	efer to Section 7.1			

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART B information is below)

Personal protection equipn	nent	
Respiratory protection	:	Respiratory protection is not normally required.
Hand protection	:	Gloves are not normally required.
Eye/face protection	:	Safety glasses should be worn.
Skin protection	:	Protective equipment is not normally necessary.
Hygiene measures	:	Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.
Additional information	:	These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these types of materials in consumer aerosol applications that has been developed by the silicone industry (www.SEHSC.com) or contact the Dow Corning customer service group.
<u>Environmental exposure</u> <u>controls</u>	:	Refer to section 6 and 12.

9. PHYSICAL AND CHEMICAL PROPERTIES			
Form	:	Liquid	
Colour	:	Colorless	
Odour	:	None	
Boiling point/range	:	> 100 °C	
Flash point	:	100 °C (Closed Cup)	
Explosive properties	:	No Some hydrogen gas may be released. Hydrogen is flammable and can form explosive mixtures with air.	
Specific Gravity	:	0.972	
Viscosity	:	415 cSt at 25°C.	
Oxidizing properties	:	No	
The above information is not intend	led for us	e in preparing product specifications. Contact Dow Corning before writing specifications.	

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART B information is below)

10. S	10. STABILITY AND REACTIVITY				
10.1	Reactivity	:	Hydrogen is liberated on contact with water, alcohols, acidic or basic materials, many metals or metallic compounds and can form explosive mixtures in air.		
10.2	Stability	:	Stable under normal usage conditions.		
10.3	Possibility of hazardous reactions	:	Some hydrogen gas may be released. Hydrogen is flammable and can form explosive mixtures with air.		
10.4	Conditions to avoid	:	None established.		
10.5	Materials to avoid	:	Can react with strong oxidising agents.		
10.6	Hazardous decomposition products	:	Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde. Hydrogen.		

11. TOXICOLOGICAL INFORMATION	

Acute toxicity:		
On contact with eyes	:	May cause temporary discomfort.
On skin contact	:	No adverse effects are normally expected.
If inhaled	:	No adverse effects are normally expected.
On ingestion	:	No adverse effects are normally expected.
<u>Chronic toxicity:</u>		
On skin contact	:	No adverse effects are normally expected.
If inhaled	:	No adverse effects are normally expected.
On ingestion	:	No adverse effects are normally expected.
<u>Toxicokinetics, metabolism</u> and distribution	:	No specific information is available.
<u>Other Health Hazard</u> <u>Information</u>	:	Product may emit formaldehyde vapour at temperatures above 180°C in the presence of air. Formaldehyde vapour is a suspected carcinogen, toxic byinhalation and irritating to eyes and the respiratory system. Exposure limits should be strictly respected.

¹ Based on product test data.

² Based on test data from similar products.



According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART B information is below)

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity effects

No adverse effects on aquatic organisms.

12.2 Persistence and degradability

Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded.

12.3 Bioaccumulation

No bioaccumulation potential.

12.4 Release to waters / Mobility in soil

Fate and effects in waste water treatment plants:

Removed > 90% by binding onto sewage sludge. No adverse effects on bacteria. The siloxanes in this product do not contribute to the BOD.

13. DISPOSAL CONSIDERATIONS

Product and packaging
disposal:Dispose of in accordance with local regulations. According to the European Waste
Catalogue, Waste Codes are not product specific, but application specific. Waste codes
should be assigned by the user, preferably in discussion with the waste disposal
authorities.

14. TRANSPORT INFORMATION

Road / Rail (ADR/RID)

Not subject to ADR/RID.

Sea transport (IMDG)

Not subject to IMDG code.

Air transport (IATA)

Not subject to IATA regulations.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

<u>Status</u>

According to article 31 and Annex II of the EU REACH Regulation

Version: 3.0 Revision Date: 19.07.2011 Superseded date: 26.04.2011

SYLGARD(R) 527 A&B SILICONE DIELECTRIC GEL (PART B information is below)

EINECS

All ingredients listed or exempt.

TSCA

All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

16. OTHER INFORMATION

This product safety data sheet was prepared in compliance with article 31 and Annex II of the EU REACH Regulation as well as its relevant amendements, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with article 31 and Annex II of the EU REACH Regulation.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

Source of information: Internal data and publically available information