

SAFETY DATA SHEET CCC Contact Cleaner C

According to Regulation (EC) No 1907/2006

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

CCC Contact Cleaner C MCC-CCC, MCC-CCC101 Cleaning agent MICROCARE EUROPE, BVBA Havendoklaan 19 1804 Cargovil - Vilvoorde Belgium +32 251 95 05

MANUFACTURER

MICROCARE CORPORATION 595 John Downey Drive New Britain, CT 06019 United States of America CAGE: OATV9 +1 860-827-0626 +1 860-827-8105 techsupport@microcare.com

2 HAZARDS IDENTIFICATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CLASSIFICATION (1999/45) R52/53.

ENVIRONMENT

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

PHYSICAL AND CHEMICAL HAZARDS

Vapours are heavier than air and may travel along the floor and in the bottom of containers. Considering the limited amount applied during use and the size of the container, the risk of adverse effects is considered small. Gas or vapour displaces oxygen available for breathing (asphyxiant).

HUMAN HEALTH

Prolonged skin contact may cause redness, irritation and dry skin. Mild dermatitis, allergic skin rash.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification (67/548)
1,1,1,2,3,4,4,5,5,5-decafluoropentane	420-640-8	138495-42-8	30-60%	R52/53.
ACETONE	200-662-2	67-64-1	1-5%	F;R11 Xi;R36 R66 R67

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Place unconscious person on the side in the recovery position and ensure breathing can take place. Perform artificial respiration if breathing has stopped. Keep out of the reach of children.

NOTES TO THE PHYSICIAN

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

INHALATION

Move into fresh air and keep at rest. If respiratory problems, artificial respiration/oxygen.

INGESTION

Do not induce vomiting. Immediately rinse mouth and drink plenty of water (200-300 ml). Consult a physician for specific advice.

SKIN CONTACT

Remove contaminated clothes and rinse skin thoroughly with water.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Make sure to remove any contact lenses from the eyes before rinsing. Consult a physician for specific advice.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIAL FIRE FIGHTING PROCEDURES

Move container from fire area if it can be done without risk.

UNUSUAL FIRE & EXPLOSION HAZARDS

Aerosol containers can explode when heated, due to excessive pressure build-up.

SPECIFIC HAZARDS

Avoid contact with naked flames and hot surfaces as corrosive and toxic decomposition products can be formed.

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Warn everybody of potential hazards and evacuate if necessary. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Considering the limited amount applied during use and the size of the container, the risk of adverse effects is considered small.

ENVIRONMENTAL PRECAUTIONS

Contain spillages with sand, earth or any suitable adsorbent material. Avoid release to the environment.

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Provide good ventilation. Avoid inhalation of vapours/spray and contact with skin and eyes. Avoid contact with naked flames and hot surfaces as corrosive and toxic decomposition products can be formed. Keep out of the reach of children.

STORAGE PRECAUTIONS

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C. Keep upright.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA	- 8 hrs	STEL	- 15 min	Notes
ACETONE	WEL	500 ppm	1210 mg/m3	1500 ppm	3620 mg/m3	

WEL = Workplace Exposure Limit.

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

RESPIRATORY EQUIPMENT

Vapours are heavier than air and may travel along the floor and in the bottom of containers. At work in confined or poorly ventilated spaces, respiratory protection with air supply must be used. Self-contained breathing apparatus with full facepiece.

HAND PROTECTION

For prolonged or repeated skin contact use suitable protective gloves.

EYE PROTECTION

Wear approved, tight fitting safety glasses where splashing is probable.

OTHER PROTECTION

Wear suitable protective clothing as protection against splashing or contamination.

HYGIENE MEASURES

No specific hygiene procedures noted, but good personal hygiene practices are always advisable, especially when working with chemicals. When using do not eat, drink or smoke.

SKIN PROTECTION

Wear apron or protective clothing in case of splashes.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Clear liquid		
COLOUR	Colourless		
ODOUR	Slight odour Ether		
VOLATILITY DESCRIPTION	Volatile.		
SOLUBILITY	Slightly soluble in water.		
Flammability	This product is not flammable.		
BOILING POINT (°C)	44 C / 111 F	VAPOUR DENSITY (air=1)	4
VAPOUR PRESSURE	47 kPa 20	VOLATILE BY VOL. (%)	100
FLAMMABILITY LIMIT - LOWER(%)	5.5	FLAMMABILITY LIMIT - UPPER(%)	9.0

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid contact with naked flames and hot surfaces as corrosive and toxic decomposition products can be formed.

HAZARDOUS POLYMERISATION

Will not polymerise.

MATERIALS TO AVOID

Alkali metals. Alkali earth metals. Powdered metal.

HAZARDOUS DECOMPOSITION PRODUCTS

When heated, toxic and corrosive vapours/gases may be formed. Halogenated hydrocarbons. Hydrogen fluoride (HF). Carbon dioxide (CO2). Carbon monoxide (CO).

11 TOXICOLOGICAL INFORMATION

GENERAL INFORMATION

No specific health warnings noted. Keep out of the reach of children.

INHALATION

Vapours may irritate the respiratory system and cause coughing, asthmatic breathing and breathlessness.

INGESTION

May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.

SKIN CONTACT

Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

EYE CONTACT

May cause temporary eye irritation.

OTHER HEALTH EFFECTS

This substance has no evidence of carcinogenic properties.

MEDICAL SYMPTOMS

High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting.

Name

ACETONE

Name	HFC-134a Tetrafluoroethane
Toxic Dose 1 - LD 50	>2085 mg/kg (oral rat)
OTHER HEALTH EFFECTS	
This substance has no evidence of c	arcinogenic properties.
Name	1,1,1,2,3,4,4,5,5,5-decafluoropentane
Toxic Dose 1 - LD 50	>5,000 mg/kg (oral rat)
Toxic Conc LC 50	11,100 ppm/4h (inh-rat)
Name	PENTAFLUOROBUTANE
Toxic Dose 1 - LD 50	>2000 mg/kg (oral rat)
Toxic Conc LC 50	25000 ppm/4h (inh-rat)
OTHER HEALTH EFFECTS	
IARC Not Listed. OSHA Not Regulat	ed.

12 ECOLOGICAL INFORMATION

	Name	ACETONE			
		HFC-134a Tetrafluoroethane			
	LC 50, 96 Hrs, FISH mg/l	450			
	EC 50, 48 Hrs, DAPHNIA, mg/l	980			
	Name	1,1,1,2,3,4,4,5,5,5-decafluoropentane			
	Ecotoxicity				
	It is unlikely that the substance will di	issolve in water in amounts big enough to have a toxic effect on fish and daphnies.			
	LC 50, 96 Hrs, FISH mg/l	27.2			
	IC 50, 72 Hrs, ALGAE, mg/l	120			
	Bioaccumulation potential				
	Bioaccumulation is unlikely to be sign	nificant because of the low water solubility of this product.			
	Degradability				
	The product is not expected to be bio	odegradable.			
	Name	PENTAFLUOROBUTANE			
	LC 50, 96 Hrs, FISH mg/l	>200			
	EC 50, 48 Hrs, DAPHNIA, mg/l	>200			
	IC 50, 72 Hrs, ALGAE, mg/l	113			
	Mobility				
	The product has poor water-solubility	Ι.			
	Bioaccumulation potential				
	Bioaccumulation is unlikely to be sign	nificant because of the low water solubility of this product.			
	Degradability				
	The product is not readily biodegrada	able.			
13	DISPOSAL CONSIDERATIONS				

GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



PROPER SHIPPING NAME	AEROSOLS		
PROPER SHIPPING NAME	Consumer Commodity ORM-D		
UN NO. ROAD	UN1950	UK ROAD PACK GR.	N/A
ADR CLASS NO.	2.2	ADR LABEL NO.	3
HAZCHEM CODE	N/A	CEFIC TEC(R) NO.	20G53
RID CLASS NO.	2.2	UN NO. SEA	1950
IMDG CLASS	2.2	IMDG PACK GR.	N/A
UN NO. AIR	1950	AIR CLASS	2.2
AIR SUB CLASS	N/A	AIR PACK GR.	N/A

15 REGULATORY INFORMATION

RISK PHRASES		
	R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
SAFETY PHRASES		
	S60	This material and its container must be disposed of as hazardous waste.
	A1	Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
	A2	Do not spray on a naked flame or any incandescent material.

EU DIRECTIVES

System of specific information relating to Dangerous Preparations. 2001/58/EC.

APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37.

NATIONAL REGULATIONS

The Aerosol Dispensers (EEC Requirements)(Amendment) Regulations 1996 (S.I 1996 No. 2421).

16 OTHER INFORMATION	
REVISION COMMENTS	

NOTE: Lines within the margin indicate significant changes from the previous revision.

REVISION DATE	03/01/2011	
REV. NO./REPL. SDS GENERATED	3	
SAFETY DATA SHEET STA	TUS	
Approved.		
DATE	June 1, 2009	
RISK PHRASES IN FULL		
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	
R11	Highly flammable.	
R36	Irritating to eyes.	
R66	Repeated exposure may cause skin dryness or cracking.	
R67	Vapours may cause drowsiness and dizziness.	

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.