





Terminal Blocks



Dimensions : Millimetres (Inches)

UL File No : E330595

Specifications

Current Rating	: 16 A 300 V ac
Minimum Insulation Withstand Voltage	: 2,000 V ac
Insulation Resistance	: > 2,000 MΩ 500 V dc
Operating Temperature	: -40°C to +105°C
Wire Strip Length	: 4 mm to 5 mm
Wire Range	: 12 to 26 AWG
Screw Torque	: 5 lb - inches

Item Number	Material		Plating / Finish	Remark
1	Insulation Body	Polyamide 66 (UL94V-0)	-	Green
2	Cage Clamp	Brass	Ni-plated	-
3	Terminal	Brass	Tin-plated	-
4	Screw	Steel	Ni-plated	-



Specification Table

Description	Pitch : 5.08 mm (0.2 inches)			Part Number
	Poles	A (mm)	A (inches)	
Terminal Block	3	15.24	6	MC24372
Terminal Block	8	40.64	1.6	MC24373
Terminal Block	12	60.96	2.4	MC24370

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.