

Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 9

sds no.: 179508 V004.2

Revision: 15.08.2011

printing date: 16.03.2012

Loctite 7455

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier:

Loctite 7455

Relevant identified uses of the substance or mixture and uses advised against:

Intended use:

Primer

Details of the supplier of the safety data sheet:

Henkel Limited

2 Bishop Square Business Park AL109EY Herfordshire Hatfield

Great Britain

Phone: +44 1606 593933 +44 1606 863762 Fax-no.:

ua-productsafety.uk@uk.henkel.com

Emergency Telephone Number:

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

Classification of the substance or mixture:

Classification (DPD):

F+ - Extremely flammable

R12 Extremely flammable.

Xi - Irritant

R38 Irritating to skin.

Dangerous for the environment

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

MSDS-No.: 179508 Loctite 7455 Page 2 of 9

V004.2

Label elements (DPD):

N - Dangerous for the environment



Xi - Irritant

F+ - Extremely flammable



Risk phrases:

R12 Extremely flammable.

R38 Irritating to skin.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

Safety phrases:

S23 Do not breathe spray.

S28 After contact with skin, wash immediately with plenty of water and soap.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Additional labeling:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding $50\,^{\circ}$ C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children

For consumer use only: S2 Keep out of the reach of children

S46 If swallowed, seek medical advice immediately and show this container or label.

Contains:

n-Heptane

Other hazards:

The aerosol container is under pressure. Do not expose to high temperatures.

SECTION 3: Composition/information on ingredients

General chemical description:

Primer

MSDS-No.: 179508 Loctite 7455 Page 3 of 9

V004.2

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
n-Heptane	205-563-8	>= 50-<= 100 %	Flammable liquids 2
142-82-5			H225
			Aspiration hazard 1
			H304
			Skin irritation 2
			H315
			Specific target organ toxicity - single
			exposure 3
			H336
			Acute hazards to the aquatic environment 1
			H400
			Chronic hazards to the aquatic environment 1
			H410
Propane	200-827-9	>= 10-< 20 %	Flammable gases 1
74-98-6			H220
			Gases under pressure
Benzenamine, N,N,4-trimethyl-	202-805-4	>= 0-< 1 %	Acute toxicity 3; Inhalation
99-97-8			H331
			Acute toxicity 3; Dermal
			H311
			Acute toxicity 3; Oral
			H301
			Specific target organ toxicity - repeated
			exposure 2
			H373
			Chronic hazards to the aquatic environment 3
			H412

Only dangerous ingredients for which a CLP classification is already available are displayed in this table. For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
n-Heptane	205-563-8	>= 50 - <= 100 %	Xi - Irritant; R38
142-82-5			R67
			F - Highly flammable; R11
			Xn - Harmful; R65
			N - Dangerous for the environment; R50/53
Propane	200-827-9	>= 10 - < 20 %	F+ - Extremely flammable; R12
74-98-6			•
Benzenamine, N,N,4-trimethyl-	202-805-4	>= 0 -< 1 %	T - Toxic; R23/24/25
99-97-8			R33
			R52/53

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

Description of first aid measures:

Inhalation:

Move to fresh air. Seek medical advice.

Skin contact:

Rinse with running water and soap.

Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

MSDS-No.: 179508 Loctite 7455 Page 4 of 9

V004.2

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

Seek medical advice.

Most important symptoms and effects, both acute and delayed:

Vapors may cause drowsiness and dizziness.

SKIN: Redness, inflammation.

Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

SECTION 5: Firefighting measures

Combustion behaviour:

Solvent containing flammable product. In case of fire toxic gases are released.

Extinguishing media:

Suitable extinguishing media:

Foam, extinguishing powder, carbon dioxide.

Special hazards arising from the substance or mixture:

Oxides of carbon, oxides of nitrogen, irritating organic vapors.

Advice for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid skin and eye contact.

Remove sources of ignition.

Ensure adequate ventilation.

Environmental precautions:

Do not let product enter drains.

Methods and material for containment and cleaning up:

Wipe up using absorbent material.

Store in a partly filled, closed container until disposal.

Reference to other sections:

See advice in chapter 8

SECTION 7: Handling and storage

Precautions for safe handling:

Avoid skin and eye contact.

Keep away from sources of ignition - no smoking.

Vapours should be extracted to avoid inhalation.

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry place.

Do not store near sources of heat or ignition, or reactive materials.

MSDS-No.: 179508 Loctite 7455 Page 5 of 9

V004.2

Specific end use(s):

Primer

SECTION 8: Exposure controls/personal protection

Control parameters:

Valid for

Great Britain

Ingredient	ppm	mg/m ³	Туре	Category	Remarks
N-HEPTANE	500		Time Weighted Average		EH40 WEL
142-82-5			(TWA):		
N-HEPTANE	500	2.085	Time Weighted Average	Indicative	ECTLV
142-82-5			(TWA):		

Exposure controls:

Respiratory protection:

Do not inhale vapors and fumes.

Use only in well-ventilated areas.

Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended.

In circumstances where there is a potential for prolonged or repeated skin contact, the use of disposable gloves (polyethylene, natural rubber or equivalent ester-resistant material) is recommended.

Eye protection:

Wear protective glasses.

Skin protection:

Suitable protective clothing

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties:

Appearance liquid colourless
Odor Aliphatic

pH not applicable

 Initial boiling point
 96 - 98 °C (204.8 - 208.4 °F)

 Flash point
 Not applicable to aerosols.

 Decomposition temperature
 No data available / Not applicable

Vapour pressure 46,7 mbar
Density 0,68 g/cm3

Bulk density

No data available / Not applicable
Viscosity

No data available / Not applicable
Viscosity (kinematic)

No data available / Not applicable
Explosive properties

No data available / Not applicable

Solubility (qualitative) Not miscible

(Solvent: Water)

Solidification temperature No data available / Not applicable Melting point No data available / Not applicable Flammability No data available / Not applicable Auto-ignition temperature No data available / Not applicable No data available / Not applicable Explosive limits Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate No data available / Not applicable Vapor density No data available / Not applicable Oxidising properties No data available / Not applicable

MSDS-No.: 179508 Loctite 7455 Page 6 of 9

V004.2

Other information:

No data available / Not applicable

SECTION 10: Stability and reactivity

Reactivity:

Strong oxidizing agents.

Chemical stability:

Stable under recommended storage conditions.

Possibility of hazardous reactions:

See section reactivity

Conditions to avoid:

Stable under normal conditions of storage and use.

SECTION 11: Toxicological information

General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause bronchopneumonia or pulmonary oedema.

Inhalative toxicity:

May cause headache and dizziness.

Skin irritation:

The product is irritant to skin and mucous membranes.

Eye irritation:

Prolonged or repeated contact may cause eye irritation.

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
n-Heptane 142-82-5	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		

SECTION 12: Ecological information

General ecological information:

Very toxic to aquatic organisms.

May cause long-term adverse effects in the aquatic environment.

Do not empty into drains / surface water / ground water.

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

MSDS-No.: 179508 Loctite 7455 Page 7 of 9

V004.2

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
n-Heptane 142-82-5	LC50	220 - 270 mg/l	Fish		Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
n-Heptane 142-82-5	EC50	1,5 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogKow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
n-Heptane	4,66					
142-82-5						
Benzenamine, N,N,4-	2,81				25 °C	
trimethyl-						
99-97-8						

SECTION 13: Disposal considerations

Waste treatment methods:

Product disposal:

Dispose of according to regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

14 06 03 Other solvents and solvent mixtures

SECTION 14: Transport information

Road transport ADR:

Class: 2

Packaging group:

Classification code: 5F

Hazard ident. number:

UN no.: 1950 Label: 2.1

Technical name: AEROSOLS Tunnelcode: (D)

Additional substance property: Environmentally Hazardous

Railroad transport RID:

Class: 2

Packaging group:

Classification code: 5F
Hazard ident. number: 23
UN no.: 1950
Label: 2.1

Technical name: AEROSOLS

Tunnelcode:

Additional substance property: Environmentally Hazardous

MSDS-No.: 179508 Loctite 7455 Page 8 of 9

V004.2

Inland water transport ADN:

Class: 2

Packaging group:

Classification code: 5F

Hazard ident. number:

UN no.: 1950 Label: 2.1

Technical name: AEROSOLS

Additional substance property: Environmentally Hazardous

Marine transport IMDG:

Class: 2.1

Packaging group:

UN no.: 1950
Label: 2.1
EmS: F-D ,S-U
Seawater pollutant: Marine pollutant
Proper shipping name: AEROSOLS (n-Heptane)

Air transport IATA:

Class: 2.1

Packaging group:

Packaging instructions (passenger) 203
Packaging instructions (cargo) 203
UN no.: 1950
Label: 2.1

Proper shipping name: Aerosols, flammable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture:

VOC content 100 %

(VOCV 814.018 VOC regulation

CH)

VOC content 100 %

(1999/13/EC)

MSDS-No.: 179508 Loctite 7455 Page 9 of 9

V004.2

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R11 Highly flammable.

R12 Extremely flammable.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R33 Danger of cumulative effects.

R38 Irritating to skin.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.