

SAFETY DATA SHEET

BLOC LUBE RED 15ML

1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

PRODUCT NAME BLOC LUBE RED 15ML
PRODUCT NO. EBLR15ML
APPLICATION Manufacture of electrical equipment
SUPPLIER H K WENTWORTH PTY LIMITED
P.O. BOX 339
BROOKVALE, NSW 2100
AUSTRALIA
TEL: 02 9938 1566
FAX: 02 9938 1467
GENERAL MANAGER
EMERGENCY TELEPHONE Tel: 029938 1566 between 8.30am and 5.00pm EST

2 HAZARDS IDENTIFICATION

HAZARD ID

Highly flammable.

Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Irritating to eyes.

HAZARD ID 2

The above phrases are the risks associated with the product

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE (According to criteria of NOHSC). DANGEROUS GOODS (According to ADG Code).

SAFETY PHRASES

S16 Keep away from sources of ignition - No smoking.
S25 Avoid contact with eyes.
S37 Wear suitable gloves.
S51 Use only in well-ventilated areas.

DG CLASS

Class 3: Flammable liquids.

PACKING GROUP II

UN NO. 1263

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTYL ACETATE -norm	204-658-1	123-86-4	30-60%	R10 R66 R67
ETHYL ACETATE	205-500-4	141-78-6	10-30%	F;R11 Xi;R36 R66 R67
PROPAN-2-OL	200-661-7	67-63-0	10-30%	F;R11 Xi;R36 R67

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels Ingredients are registered on AICS

4 FIRST-AID MEASURES

NOTES TO THE PHYSICIAN

Treat symptomatically

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

BLOC LUBE RED 15ML

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Get medical attention.

SKIN CONTACT

Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use: Alcohol resistant foam. Powder. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

No specific fire fighting procedure given.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Absorb in vermiculite, dry sand or earth and place into containers. Wear necessary protective equipment.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

STORAGE PRECAUTIONS

Flammable/combustible - Keep away from oxidisers, heat and flames. Store in tightly closed original container in a cool, dry well-ventilated place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	LT - ppm	LT - mg/m3	ST - ppm	ST - mg/m3
BUTYL ACETATE -norm	ES-TWA	150 ppm	713 mg/m3	200 ppm	950 mg/m3
ETHYL ACETATE	ES-TWA	200 ppm	720 mg/m3	400 ppm	1440 mg/m3
PROPAN-2-OL	ES-TWA	400 ppm	983 mg/m3	500 ppm	1230 mg/m3

INGREDIENT COMMENTS

Australian exposure limits are: LT= ES-TWA and ST= ES STEL

ENGINEERING MEASURES

Provide sufficient ventilation during operations which cause vapour formation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit

HAND PROTECTION

Use protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear approved safety goggles.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid		
COLOUR	Red		
ODOUR	Characteristic		
VISCOSITY	600-800 cps @ 20 °C	FLASH POINT (°C)	3.3 CC (Closed cup).

BLOC LUBE RED 15ML

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid heat, flames and other sources of ignition.

11 TOXICOLOGICAL INFORMATION

INHALATION

May cause irritation to the respiratory system.

INGESTION

May cause stomach pain or vomiting.

SKIN CONTACT

Product has a defatting effect on skin. Prolonged or repeated exposure may cause severe irritation.

EYE CONTACT

Irritating to eyes.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Not regarded as dangerous for the environment.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS 3

PROPER SHIPPING NAME PAINT OR PAINT RELATED MATERIAL

ADG CLASS

Class 3: Flammable liquid

UN NO.	1263	UK ROAD PACK GR.	II
ADR CLASS NO.	3	DG CLASS	Class 3: Flammable liquids.
PACKING GROUP	II	HAZARD No. (ADR)	33
ADR LABEL NO.	3	HAZCHEM CODE	3YE
CEFIC TEC(R) NO.	30GF1-I+II, 30GF1-sp	RID CLASS NO.	3
RID PACK GROUP	II	UN NO. SEA	1263
IMDG CLASS	3	IMDG PAGE NO.	3
IMDG PACK GR.	II	EMS	F-E, S-E
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1263	AIR CLASS	3
AIR PACK GR.	II		

15 REGULATORY INFORMATION

LABELLING

BLOC LUBE RED 15ML



Irritant



Highly Flammable

RISK PHRASES

R11	Highly flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

SAFETY PHRASES

S16	Keep away from sources of ignition - No smoking.
S25	Avoid contact with eyes.
S37	Wear suitable gloves.
S51	Use only in well-ventilated areas.

GUIDANCE NOTES

Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003 (1995)]

NATIONAL REGULATIONS

National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC:1005(1994)]

National Code of Practice for the Control of Workplace Hazardous Substances [NOHSC:2007(1994)]

National Code of Practice for the Preparation of Material Safety Datasheets [NOHSC:2011(2003)]

Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004) and List of Designated Hazardous Substances

POISONS SCHEDULE NUMBER NONE

16 OTHER INFORMATION

REVISION DATE NOVEMBER 2007

REV. NO./REPL. SDS GENERATED 0

SDS NO. 10801

RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R36	Irritating to eyes.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.