

SAFETY DATA SHEET

FLAME RETARDANT EPOXY RESIN 2001A

1 IDENTIFICATION OF THE MATERIAL AND SUPPLIER

PRODUCT NAME FLAME RETARDANT EPOXY RESIN 2001A
PRODUCT NO. EER2001A
APPLICATION Resin
SUPPLIER H K WENTWORTH PTY LIMITED
P.O. BOX 339
BROOKVALE, NSW 2100
AUSTRALIA
TEL: 02 9938 1566
FAX: 02 9938 1467
GENERAL MANAGER
EMERGENCY TELEPHONE Tel: 029938 1566 between 8.30am and 5.00pm EST

2 HAZARDS IDENTIFICATION

HAZARD ID

Irritating to eyes and skin.

May cause sensitisation by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

HAZARD ID 2

The above phrases are the risks associated with the product

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE (According to criteria of NOHSC). NON-DANGEROUS GOODS (According to ADG Code).

SAFETY PHRASES

S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S24/25	Avoid contact with skin and eyes.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P5	Contains epoxy constituents. See information supplied by the manufacturer.

DG CLASS

Not classified for transportation.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
EPOXY RESIN (Number average MW <= 700)	500-033-5	25068-38-6	10-30%	R43 Xi;R36/38 N;R51/53
Neodecanoic acid glycidyl ester	247-979-2	26761-45-5	1-5%	N;R51/53. R43.

COMPOSITION COMMENTS

Ingredients not listed are classified as non-hazardous or at a concentration below reportable levels Ingredients are registered on AICS

4 FIRST-AID MEASURES

NOTES TO THE PHYSICIAN

Treat symptomatically

INHALATION

Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.

INGESTION

DO NOT INDUCE VOMITING! Rinse mouth thoroughly. Promptly get affected person to drink large volumes of water to dilute the swallowed chemical. Get medical attention immediately!

FLAME RETARDANT EPOXY RESIN 2001A

SKIN CONTACT

Rinse the skin immediately with lots of water. Get medical attention if any discomfort continues.

EYE CONTACT

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Fire can be extinguished using: Foam. Alcohol resistant foam. Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES

Use water to keep fire exposed containers cool and disperse vapours.

6 ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS

Absorb in vermiculite, dry sand or earth and place into containers. Wear necessary protective equipment. Wash thoroughly after dealing with a spillage.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame.

STORAGE PRECAUTIONS

Store in tightly closed original container in a cool, dry well-ventilated place. Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

INGREDIENT COMMENTS

Australian exposure limits are: LT= ES-TWA and ST= ES STEL

PROTECTIVE EQUIPMENT



ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit

HAND PROTECTION

Use suitable protective gloves if risk of skin contact. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Use approved safety goggles or face shield.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Viscous Liquid

COLOUR

White / off-white

SOLUBILITY

Insoluble in water

RELATIVE DENSITY

1.83 @ 20 C

VISCOSITY

cps @ 20 C

FLASH POINT (°C)

>120 CC (Closed cup).

FLAME RETARDANT EPOXY RESIN 2001A

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions.

CONDITIONS TO AVOID

Avoid contact with acids and oxidising substances.

HAZARDOUS DECOMPOSITION PRODUCTS

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂). Nitrous gases (NO_x).

11 TOXICOLOGICAL INFORMATION

INHALATION

No specific health warnings noted.

INGESTION

May cause stomach pain or vomiting.

SKIN CONTACT

Irritating to skin. May cause allergic contact eczema. May cause sensitisation by skin contact.

EYE CONTACT

Irritating to eyes.

HEALTH WARNINGS

EYES, NOSE AND MOUTH. Repeated exposure may cause chronic eye irritation. SKIN. Mild dermatitis, allergic skin rash. Defatting, drying and cracking of skin.

ROUTE OF ENTRY

Ingestion. Skin and/or eye contact.

12 ECOLOGICAL INFORMATION

ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION

GENERAL

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID).

ROAD TRANSPORT NOTES

Not Classified

RAIL TRANSPORT NOTES

Not Classified.

SEA TRANSPORT NOTES

Not Classified.

AIR TRANSPORT NOTES

Not Classified.

ADG CLASS

Not classified for transportation

DG CLASS

Not classified for transportation. MARINE POLLUTANT No.

15 REGULATORY INFORMATION

LABELLING



Irritant

CONTAINS

EPOXY RESIN (Number average MW <= 700)
Neodecanoic acid glycidyl ester

FLAME RETARDANT EPOXY RESIN 2001A

RISK PHRASES

R43	May cause sensitisation by skin contact.
R36/38	Irritating to eyes and skin.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES

S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37	Wear suitable gloves.
S24/25	Avoid contact with skin and eyes.
S61	Avoid release to the environment. Refer to special instructions/safety data sheets.
P5	Contains epoxy constituents. See information supplied by the manufacturer.

GUIDANCE NOTES

Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003 (1995)]

NATIONAL REGULATIONS

National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC:1005(1994)]

National Code of Practice for the Control of Workplace Hazardous Substances [NOHSC:2007(1994)]

National Code of Practice for the Preparation of Material Safety Datasheets [NOHSC:2011(2003)]

Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004) and List of Designated Hazardous Substances

POISONS SCHEDULE NUMBER NONE

16 OTHER INFORMATION

REVISION DATE NOVEMBER 2007

REV. NO./REPL. SDS GENERATED 0

SDS NO. 10861

RISK PHRASES IN FULL

R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.