



## Solder / Desolder Rework Station

Complete single-piece unit combines the benefits of a temperature controlled vacuum desoldering station, with a high quality temperature controlled soldering iron.

### Kit Includes:

- 1 mm nozzle plus one spare
- Cleaning pins
- Replacement filters and filter tube

## Product Description

- Closed loop temperature control
- Digital display
- Handles stay cool during prolonged use
- Rugged metal enclosure
- A variety of replacement tips available

### Vacuum Desoldering Iron:

- Efficient internal pump provides vacuum action
- Lightweight ergonomic gun handle
- Trigger pump activator
- Heat resistant detachable cord and vacuum tube
- 24 V ac, 48 W heating element
- Temperature range: 410°F to 900°F

### Temperature Controlled Soldering Iron:

- 24 V ac, 48 W heating element
- Temperature range: 320°F to 900°F
- Heat resistant detachable cord
- Includes iron clad 3/64 inches conical tip
- Variety of replacement tips are available
- Overall dimensions : (H) 5.5 inches × (W) 8.25 inches × (D) 7.5 inches
- Power requirements : 120 V ac, 60 Hz, 100 W

## Part Number Table

Description	Part Number
Rework Station	72-6345

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell plc 2012.