T01102 001229 entrelec

## Thermocouple terminal blocks MTC 6 Spacing 6 mm .2381 Compression clamp 6 mm block for thermocouple End stop th. 9,1 mm BADL 0199 408.02 0103 002.26 End stop th. 9,1 mm **BAM** principle of connection Other end stops: See Accessories section PR30 prepunched 0173 220.05 Rail 35 x 7,5 x 1 Rail 0168 500.12 **1** 35 x 15 x 2,3 PR4 Rail 35 x 15 x 1,5 ℃ PR5 prepunched 0101 598.26 Rail □ 32 x 15 PR1Z2 0163 050.04 Other rails: See Accessories section CE ⟨£x⟩ Type Part number Block standard 0115 206.22 Grey body MTC 6 **Characteristics** NFC DIN UL **CSA** Wire size 2 conductors for mm<sup>2</sup> / AWG thermocouple (DIA. 0,5 - 1,5 mm) Rated voltage 500 V Gr.C Rated current Rated wire size 31 mm max. / 1.22 Wire stripping length mm / inches 0,4-0,6 Nm / 3.5-5.3 lb.in Recommended torque Nm / Ib.in **Accessories** Part number Type th. 2,8 0118 368.16 End section FEM6 СВМ5 th. 0,5 0178 745.14 Shield connector th. 0.8 0178 746.15 R See section on markers 1 Sides of block 2 Top of block marking method

## Thermocouple terminal blocks

Entrelec's MTC 6 thermocouple terminal block provides an interface for connecting thermocouple wire with virtually no loss of signal integrity. The interface design ensures positive wire continuity and allows selection and inventory of one terminal block for all thermocouple material.

The thermocouple principle is based on the reaction of different metals to temperature. When thermocouple wires are terminated or connected, the "metal balance" must be maintained. The introduction of a foreign material (such as copper) results in loss of signal strength and integrity.




Figure 1. MTC 6 with shield connector

When running extended or intermittent lengths of thermocouple wire, to a measurement instrument, two solutions are available :

- When signals are carried over a long distance, a thermocouple transmitter is required. The thermocouple signal, in millivolts (mV), is converted to a milliampere (mA) signal (i.e. 4-20 mA) for ease of transmission.
- 2. When thermocouple wire is of insufficient length, termination and interconnection, using terminal blocks, will extend its length.

## Universal terminal block

Other thermocouple terminal blocks are available with hardware (screws, clamps and connecting bar) which match the thermocouple material being used. This requires inventory of many different terminal block types.



Entrelec's MTC 6 terminal block adapts to all thermocouple material. This "neutral" method of connection limits the introduction of foreign materials to an insignificant level. The thermocouple wire insulation is stripped (31 mm maximum) and the bare wires are superimposed on one another. The thermocouple wires are in contact over their complete 31 mm length and tightened at two points by round tip screws (see figure 2). The screws, made of plated brass, have only a mechanical function, that of holding the wires together with a point contact. Thus, the pressure points are not relevant in the connection environment.

One thermocouple lead connects through one terminal block (see figure 2). The MTC 6 requires only 6 mm of space, allowing 50 terminals per foot of rail.

## Thermocouple shield wire connector bar

The MTC 6 can be field or factory equipped with a shield connector bar (see figure 1). This bar, made of treated brass, mounts in the lower part of the terminal block. It ensures the continuity of the thermocouple wire shield through the terminal block or to ground with no additional spacing.