



CONFIGURATION		PART NUMBER		CONTACT TYPE
STRAIGHT EXTENSION, 17 POSITION, TYPE: 17P (CCW)		MA1JAP1700		SOCKET/PINS
DIMENSIONS				
$ \begin{array}{c} 27,9 \\ \hline 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\$				
TECHNICAL DATA				
TEMPERATURE RANGE:	-20C to	+130C		
PROTECTION:	IP 67 (PLUGGED CONDITION)			
DEGREE OF PROTECTION:	3			
OVER VOLTAGE CATEGORY:	III			
HOUSING BODY:	ZINC DIE-CAST			
COUPLING NUT:	BRASS, NICKEL-PLATED			
INSULATION INSERTS:	PA66, UL 94 / VO			
CONTACTS:	BRASS, GOLD-PLATED			
SEALS:	DUPONT VITON			
MAX CURRENT:	9A			
CONTACT SIZE:	17 x 1.0mm			
MAXIMUM VOLTAGE:	125V AC/DC			
CONTACT RESISTANCE:	<5			
TEST VOLTAGE: (BETWEEN CONTACTS)	2500V			
MAXIMUM MATING CYCLES:	>50			
NOTES				
Sales and Technical Support 1-800-394-7732		www.sineco.com	Rev: NO	C Date: 2/9/2012

© 2012 Amphenol Sine Systems Corporation. Every effort has been made to ensure that the information contained in this document is accurate at the time of publication. Specifications or information stated in this publication are subject to change without notice.