

Digital Clamp Meter



Specifications

Basic Functions	Range	Basic Accuracy
DC Current (A)	40A / 600A	± (2.5% +5)
AC Voltage (V)	4V / 40V / 400V / 600V	± (1% +5)
DC Voltage (V)	400mV / 4V / 40V / 400V / 600V	± (0.8% +1)
Resistance (Ω)	400Ω / 4KΩ / 40KΩ / 400KΩ / 4MΩ / 40MΩ	± (1% +2)
Capacitance (F)	4nF / 40nF / 400nF / 4μF / 40μF / 100μF	± (4% +3)
Frequency (Hz)	10Hz ~ 10MHz 10MHz	± (0.5% +3) Reference only
Temperature (°C)	-40 °C ~ 1,000°C	± (2.5% +3)

Features

Display Count	–	3,999
Auto Range	–	√
Jaw Capacity	–	28mm
Diode	–	√
Auto Power Off	–	√
Continuity Buzzer	–	√
Low Battery Indication	–	√
Data Hold	–	√
MAX Mode	–	√
Setup	–	√
Input Impedance for DCV	Around 10MΩ	√



Digital Clamp Meter



General Characteristic	
Power	9V Battery (6F22)
LCD Size	35.60mm × 18mm
Product Color	Orange and Grey
Product Net Weight	260g
Product Size	208mm × 76mm × 30mm
Standard Accessories	Battery, Test Lead, Carrying Bag, Point Contact Temperature Probe
Standard Individual Packing	Gift Box, English Manual
Standard Carton Measurement	540mm × 495mm × 335mm (0.09 CBM Per Standard Carton)
Standard Carton Gross Weight	25 kgs.

Part Number Table

Description	Part Number
Multimeter, Digital, Clamp	72-9480

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell plc 2012.

