



Webro (Long Eaton) Ltd, Vision House
Meadow Brooks Business Park
Meadow Lane, Long Eaton
Nottingham, NG10 2GD. UK

Tel: (+44)(0)115 9724483 Fax :(+44)(0)115 9461230
Web www.webro.com Email: info@webro.com


Cable & Connectors

WF165 Cables

Application

Coaxial cables are suitable for many applications, including low power video, video signal, and broadband signals. They are also used in high frequency transmission, especially for transmitters and receivers, computers, radio and TV transmissions.

Construction



1	Inner conductor	Plain Copper
2	Dielectric	Foamed Polyethylene Insulation
3.1	Screen	Copper Tape
3.2	Screen	Copper Braid
4	Sheath	PVC Sheath. (PE, UG & LSZH options also available)

MECHANICAL CHARACTERISTICS

1. Inner conductor:	
Diameter:	1.63 mm Plain Annealed Copper
2. Insulation:	
Diameter:	7.25mm (Natural)
3.1 Screen:	Plain copper foil tape
3.2 Screen:	Plain Copper Wire Braid Coverage >50%
4. Sheath:	
Diameter:	10.10mm Nominal
5. Cable:	
Storage/operating temperature:	-15°C to +70°C
Minimum installation temperature:	-5 °C

Electrical characteristics

DC resistance Inner conductor:	≤ 10.5 Ω/km @ 20°C
DC resistance Outer conductor:	≤ 12 Ω/km @ 20°C
Characteristic Impedance:	75 ± 3Ωm
Capacitance:	58pF/m (nominal)
Velocity Ratio:	0.81
Attenuation (d/B 100m @ 20°C)	
10Mhz	<1.2
50Mhz	<3.0
100Mhz	<4.0
200Mhz	<6.0
460Mhz	<9.0
860Mhz	<12.5
1000Mhz	<13.5
1750Mhz	<19.0

Return Loss

5 – 470MHz	≥23
470 – 862MHz	≥20
862 – 2150MHz	≥18



Certificate No. 4416

For further information call sales
Tel +44(0)115 9724483
Fax +44(0)115 9461230
Email info@webro.com

