



EAD
WWW.EAD-LTD.COM
QUINTUS
312175

Quintus

Penta-Band Internal PCB Antenna

Features

- ◆ Groundplane Independent
- ◆ Covers 850/900/1800/1900/2100 MHz bands
- ◆ Various cable/connector options
- ◆ Ideal for fixed and mobile terminals

Specifications

Radiating element	1/2 Wave Element
Frequency range	850/900/1800/1900/2100 MHz
Gain	2 dBi
Polarisation	Linear
Return loss	-7.0 dB
Power rating	10W
Cable / Connector	Various including MMCX, U.FL, SMA
Dimensions	83x 22mm

Popular Ordering Options


FQTN35144-MR-16	Quintus with 160mm RG-178 and MMCX Connector
FQTN35144-UF-10	Quintus with 100mm cable and U.FL Connector

Specifications subject to change without notice.

5 Little Balmer
Buckingham Industrial Park
Buckingham
MK18 1TF
UK



Tel: +44 (0)1280 824055
Fax: +44 (0)1280 817179
Email: sales@ead-ltd.com
Web: www.ead-ltd.com

EAD
embedded antenna design ltd
Delivering Antenna Innovation



Quintus | Penta-Band Internal PCB Antenna

Return Loss



Specifications subject to change without notice.

5 Little Balmer
Buckingham Industrial Park
Buckingham
MK18 1TF
UK

Tel: +44 (0)1280 824055
Fax: +44 (0)1280 817179
Email: sales@ead-ltd.com
Web: www.ead-ltd.com