

# CHEMTRONICS<sup>®</sup>

## Technical Data Sheet

**TDS # 2400**

### Tun-O-Wash<sup>®</sup> Cleaner

#### PRODUCT DESCRIPTION

Tun-O-Wash<sup>®</sup> Cleaner is a fast drying, one step precision cleaning and degreasing agent safe for most plastics. Engineered with very low surface tension, this high pressure aerosol formulation flushes areas clean and evaporates instantly leaving no residue.


- Removes encrusted dirt, grease and other contaminants
- Penetrates hard to reach areas
- Evaporates quickly
- Leaves no residues
- Low odor formulation
- Noncorrosive
- Contains no CFCs or HCFCs
- Contains no 1,1,1 Trichloroethane

#### TYPICAL APPLICATIONS

Tun-O-Wash<sup>®</sup> Cleaner cleans and degreases:

- Contacts
- Label Residue
- Light Fluxes
- Potentiometers
- Printed Circuit Boards
- Selector Switches
- Tape Drives
- Tuners
- Volume and Tone Controls

#### TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

<b>Boiling Point</b>	141°F Initial
<b>Vapor Density (air=1)</b>	>1
<b>Solubility in Water</b>	20%
<b>Specific Gravity (water = 1@77°F)</b>	0.70
<b>Evaporation Rate (butyl acetate=1)</b>	>1
<b>Appearance</b>	Clear, Colorless Liquid
<b>Odor</b>	Mild
<b>Surface Tension (dynes/cm @21.6°C)</b>	17.3
<b>Flash Point (TCC)</b>	-20.0°F
<b>Flammable</b>	(-29°C)
<b>Kauri-Butanol (KB) Number</b>	50
<b>Shelflife</b>	5 years
<b>RoHS/WEEE Status</b>	

#### COMPATIBILITY

Tun-O-Wash<sup>®</sup> Cleaner is generally compatible with most materials used in the electronics industry. As with any cleaning agent, compatibility must be determined on a non-critical area prior to use.

<u>Material</u>	<u>Compatibility</u>
ABS	Good
Buna-N	Good
EPDM	Poor
Graphite	Excellent
HDPE	Excellent
Kynar™	Fair
LDPE	Fair
Lexan™	Fair
Neoprene	Fair
Noryl®	Good
Nylon 66™	Excellent
Cross-Linked PE	Excellent
Polypropylene	Good
Polystyrene	Non-Compatible
PVC	Good
Silicone Rubber	Non-Compatible
Teflon™	Excellent
Viton™	Excellent

<b>Performance</b>	
<b>Product Required for Water Soluble Oil Removal (mg solvent / 1 mg oil)</b>	
Tun-O-Wash Cleaner	<b>33</b>
Conventional CFC Cleaner	<b>94</b>
<b>Water Soluble Oil Removal Rate (mg / in<sup>2</sup> sec.)</b>	
Tun-O-Wash Cleaner	<b>11</b>
Conventional CFC Cleaner	<b>5</b>

## USAGE INSTRUCTIONS

For industrial use only.  
 Read MSDS carefully prior to use.  
 Spray 4-6 inches from surface to clean. Wash parts from top to bottom, allowing the liquid to flush away dirt and dissolved grease. For precise application use attached extension tube. Product is Extremely Flammable - Do not use near sources of ignition and energized equipment.

## AVAILABILITY

ES2400 12.5 oz. Aerosol

## TECHNICAL & APPLICATION ASSISTANCE

Chemtronics® provides a technical hotline to answer your technical and application related questions. The toll free number is:  
**1-800-TECH-401.**

## ENVIRONMENTAL IMPACT DATA

<b>ENVIRONMENTAL IMPACT DATA</b>			
CFC	0.0%	VOC	95.7%
HCFC	0.0%	HFC	0.0%
CL Solv.	0.0%	ODP	0.0

CFC, HCFC, CL. SOLV., VOC, and HFC numbers shown are the content by weight. Ozone depletion potential (ODP) is determined in accordance with the Montreal Protocol and U.S. Clean Air Act of 1990. The ODP of this product is 0.0. It is the sum of the ODP of the substances that may contribute to the depletion of stratospheric ozone, based upon the weight of each substance in the product's formulation.

**NOTE:** This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS® does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

## MANUFACTURED BY:

ITW CHEMTRONICS  
 8125 COBB CENTER DRIVE  
 KENNESAW, GA 30152  
 1-770-424-4888

REV. G (06/06)

## DISTRIBUTED BY: