

High Power 12W LED




Features:

- Excellent transiting heat from LED chip operating under 350mA
- High luminous output
- No UV

Applications:

- Reading lights
- Portable flashlights
- Uplighters & downlighters
- Garden lighting
- LCD backlights / light guides
- General lighting

Package Dimensions:




All dimensions are in mm
Tolerance: $\pm 0.5\text{mm}$

Absolute Maximum Ratings at $T_a=25^\circ\text{C}$

Parameter	Symbol	Unit
Power Dissipation	12,250	mW
LED Junction Temperature	120	$^\circ\text{C}$
Reverse Voltage	5	V
D.C. Forward Current	350	mA
Pulsed Forward Current ($t_p < 100\mu\text{s}$, Duty cycle = 0.005)*1	700	mA
Operating Temperature Range	-40 to +75	$^\circ\text{C}$
Storage Temperature Range	-40 to +100	$^\circ\text{C}$
Soldering Temperature	Reflow Soldering : 260°C for 10sec Hand Soldering: 350°C for 3sec.	



Duty Cycle:



- Proper current derating must be observed to maintain junction temperature below the maximum.
- All products no sensitive to ESD damage (6,000 Volts by HBM condition)
- Be careful with a powered up current limited power supply, because of current spikes during power up and/or connection. Best practice is to connect the LED then turn up the voltage gradually. People building their own power supplies should design for minimum current spikes during power up and connection.
- For best results the customer needs to provide proper control of the thermal path, protect against electrical overstress conditions and ensure they are properly attached to the heat sink.
- It is strongly recommended that the temperature of lead does not exceed 55°C.
- It is strongly recommended to apply an electrically isolated heat conducting film between the slug and contact surfaces

Electrical & Optical Characteristics:

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Luminous Flux	Φ_V	IF=350mA	800	950		lm
	η	IF=350mA		80		Lm/W
CIE Chromaticity Coordinates: X Axis	X	IF=350mA		0.4578		
CIE Chromaticity Coordinates: Y Axis	Y	IF=350mA		0.4101		
Forward Voltage	VF	IF=350mA	30		35	V
Correlated Colour Temperature	CCT	IF=350mA		2,750		K
Thermal Resistance Junction to Case	R θ J-C	IF=350mA		9		°C/W
Reverse Current	IR	VF=5V			50	μ A
Viewing Angle at 50% IV	2 θ ½	IF=350mA		120		Deg.

- Notes: 1. The data is tested by IS tester.
2. Customer's special requirements are also welcome.

Typical Electrical & Optical Characteristics Curves:

(25°C Ambient temperature unless otherwise noted)






Fig.1 WHITE LED Spectrum VS. WAVELENGTH


High Power 12W LED




Ambient Temperature VS. Forward Current



Radiation Diagram



Forward Current VS. Applied Voltage




Forward Current VS. Luminous Flux

Chromaticity Coordinates Specifications for Bin Grading:

Bin	Rank				
8A	X	0.4345	0.443	0.4582	0.4483
	Y	0.388	0.4055	0.4099	0.3919
8B	X	0.443	0.453	0.4687	0.4582
	Y	0.4055	0.4248	0.4289	0.4099
8C	X	0.4582	0.4687	0.4813	0.47
	Y	0.4099	0.4289	0.4319	0.4126
8D	X	0.4483	0.4582	0.47	0.4593
	Y	0.3919	0.4099	0.4126	0.3944



Chromaticity Coordinates & Bin Grading Diagram:



Part Number Table

LED Chip		Lens Colour	Part Number
Material	Colour Coordinates		
InGaN/Metal	Warm white	Water clear	703-1025

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.