Solutions

<sup>®</sup> building a smarter, unified business foundation Connect. Manage. Automate.

Services



About Us

Support

Worldwide

Entire Site

-Search-

Search Results

## Evaluate

Industries

- Product Bulletins - PDF-PAN-TY Polyp ..
- Design a Solution
- Catalog Cut Sheet
  - PDF-PLT1M-M100 P
- Part Drawings
- PDF-Pan-Ty Polyp - Specification Sheets
- PDF-Pan-Ty Polyp ..
- How to Buy
  - Bill of Material
  - Favorite Products List



Partners

Products

⊠ Text Search: 'PLT3S-M100'

Software

Your search criteria matched only one product, shown below

## **PLT3S-M100**



· For chemical resistance where high loop tensile strength is not required especially in the presence of hydrochloric acid, salts and bases

- · Greater resistance to damage caused by ultraviolet light indoor or outdoor use
- Material requires lowering the tool setting (see package label)
- · One-piece construction for consistent performance and reliability
- · Lowest threading force of any one-piece cable tie in the industry

 Curved tip is easy to pick up from flat surfaces and allows faster initial threading to speer installation

| Part Number                                | PLT3S-M100   |  |
|--|--|--|
| <ul> <li>RoHS Compliancy Status</li> </ul> | Compliant  |  |
| Part Description                           | Cable Tie, 11.5", Standard cross section                                   |  |
| Product Type                               | Cable Ties   |  |
| Material                                   | Weather Resistant Polypropylene  |  |
| Color                                      | Black  |  |
| CSA Certified                              | No   |  |
| UL Listed (File #E56854)                   | No   |  |
| UL Recognized (File #E56854)               | No   |  |
| Length (In.)                               | 11.5   |  |
| Length (mm)                                | 292  |  |
| Width (In.)                                | 0.190  |  |
| <ul> <li>Width (mm)</li> </ul>             | 4.8  |  |
| CE Compliant                               | Yes  |  |
| Cross Section                              | Standard   |  |
| Head Height (In.)                          | 0.220  |  |
| Head Height (mm)                           | 5.6  |  |
| Head Width (In.)                           | 0.337  |  |
| Head Width (mm)                            | 8.6  |  |
| Locking Style                              | Locking  |  |
| Material Flammability Rating               | HB   |  |
| Max. Bundle Diameter (In.)                 | 3.00   |  |
| Max. Bundle Diameter (mm)                  | 76   |  |
| Max. Continuous Use Temperature            | 239°F (115°C)  |  |
| Min. Bundle Diameter (In.)                 | 0.06   |  |
| Min. Bundle Diameter (mm)                  | 1.5  |  |
| Min. Loop Tensile Strength (Lbs.)          | 30   |  |
| Min. Loop Tensile Strength (N)             | 133  |  |
| Plenum-Rated                               | No   |  |
| Pricing Description                        | Cable Tie, 11.5"L (292mm) Standard, Weather Resistant Polypropylene, Black |  |
| Thickness (In.)                            | 0.052  |  |
| Thickness (mm)                             | 1.3  |  |
| • Tool                                     | GTS, GTSL, GS2B, GTH, GS4H, PTS, PTS, PPTS, STS2, STH2                     |  |
| Tool Setting                               | 5 (GTS, GS2B, PTS, PPTS)<br>2 (GTH, GS4H)                                  |  |
| Min. Order UOM                             | PC   |  |
| Min. Order Qty.                            | 1000   |  |

|   | ······ -·· -····      |   |
|---|-----------------------|---|
| • | BOM Qty. (# of Pkgs.) | 0 |
|   |                       |   |

Add to Favorite Product List

Please register to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.

Home | Industries | Solutions | Services | Products | Partners | Support | Contact Us | Site Map | Careers Copyright © 1995-2012, PANDUIT CORP. All rights reserved. | Legal Information | Privacy Policy