

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number :

744778928

LF




Bezeichnung : **SPEICHERDROSSEL WE-PD**

description : **POWER-CHOKE WE-PD**

DATUM / DATE : 2006-01-10

A Mechanische Abmessungen / dimensions :



	Typ S	
A	$7,3 \pm 0,3$	mm
B	$3,2 \pm 0,3$	mm
C	$1,5 \pm 0,2$	mm
D	$1,5 \pm 0,3$	mm
E	$4,0 \pm 0,3$	mm


● = Start of winding

Marking = Inductance code

B Elektrische Eigenschaften / electrical properties :

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Induktivität / inductance	1 kHz / 0,25V	L	820,0	μH	± 20%
DC-Widerstand / DC-resistance	@ 20°C	R _{DC typ}	4,990	Ω	typ.
DC-Widerstand / DC-resistance	@ 20°C	R _{DC max}	6,540	Ω	max.
Nennstrom / rated current	ΔT=40 K	I _{DC}	0,21	A	max.
Sättigungsstrom / saturation current	ΔL/L <10%	I _{sat}	0,20	A	typ.
Eigenres.-Frequenz / self-res.-frequency		SRF	2,50	MHz	typ.

C Lötpad / soldering spec.:



D Prüfgeräte / test equipment :

HP 4274 A für/for L und/and Q

HP 34401 A für/for I_{DC} und/and R_{DC}

E Testbedingungen / test conditions :

Luftfeuchtigkeit / humidity: 33%
Umgebungstemperatur / temperature: +20°C

F Werkstoffe & Zulassungen / material & approvals :

Basismaterial / base material: Ferrit/ferrite
Endoberfläche / finishing electrode: 100% Sn
Anbindung an Elektrode / soldering wire to plating: Sn/Ag/Cu - 96.5/3.0/0.5%
Draht / wire: 2SFBW; 155°

G Eigenschaften / general specifications :

Betriebstemp. / operating temperature: -40°C - + 125°C
Umgebungstemp. / ambient temperature: -40°C - + 85°C
It is recommended that the temperature of the part does not exceed 125°C under worst case operating conditions.

Freigabe erteilt / general release:	Kunde / customer			
		SST	Version 5	06-01-10
Datum / date	Unterschrift / signature	MST	Version 4	04-10-11
	Würth Elektronik	SST	Version 3	04-07-28
		SST	Version 2	04-04-21
		SST	Version 1	04-04-08
Geprüft / checked	Kontrolliert / approved	Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
http://www.we-online.de

Spezifikation für Freigabe / specification for release

Kunde / customer :
 Artikelnummer / part number : 744778928


LF



Bezeichnung : SPEICHERDROSSEL WE-PD
 description : POWER-CHOKE WE-PD

DATUM / DATE : 2006-01-10

H Induktivitätskurve / Inductance curve :



Freigabe erteilt / general release:	Kunde / customer				
Datum / date	Unterschrift / signature		SSt	Version 5	06-01-10
			MST	Version 4	04-10-11
	Würth Elektronik		SST	Version 3	04-07-28
			SST	Version 2	04-04-21
Geprüft / checked	Kontrolliert / approved		SST	Version 1	04-04-08
			Name	Änderung / modification	Datum / date

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.de>

Spezifikation für Freigabe / specification for release

Kunde / customer : _____
 Artikelnummer / part number : **744778928**
 Bezeichnung : **SPEICHERDROSSEL WE-PD**
 description : **POWER-CHOKE WE-PD**


LF





DATUM / DATE : 2006-01-10

I Rollenspezifikation / tape and reel specification :

Gurtspezifikation / Tape specification:




A	$10,0 \pm 0,1$	mm
B	$16,0 \pm 0,2$	mm
C	$1,50 \pm 0,1$ $0,0$	mm
D	$4,00 \pm 0,1$	mm
E	$2,00 \pm 0,1$	mm
F	$1,75 \pm 0,1$	mm
G	$10,0 \pm 0,1$	mm
H	$5,0 \pm 0,1$	mm



Rollenspezifikation / Reel specification:

a	$330,0 \pm 2,0$	mm
b	$21,0 \pm 0,8$	mm
c	$13,0 \pm 0,5$	mm
d	$100,0 \pm 1,0$	mm



The force for tearing off cover tape is 10 to 130 grams in arrow direction

Freigabe erteilt / general release:

Kunde / customer

Datum / date

Unterschrift / signature

Würth Elektronik

Geprüft / checked

Kontrolliert / approved

SST	Version 5	06-01-10
MST	Version 4	04-10-11
SST	Version 3	04-07-28
SST	Version 2	04-04-21
SST	Version 1	04-04-08
Name	Änderung / modification	Datum / date

This electronic component has been designed and developed for usage in general electronic equipment. Before incorporating this component into any equipment where higher safety and reliability is especially required or if there is the possibility of direct damage or injury to human body, for example in the range of aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc, Würth Elektronik eiSos GmbH must be informed before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.de>