



Specifications

Best Functions	Range	Best Accuracy
DC voltage	200mV/2V/20V/200V/1000V	±(0.5% +1)
AC voltage	2V/20V/200V/1000V	±(0.8% +3)
DC current	2mA/200mA/20A	±(0.8% +1)
AC current	2111A/200111A/20A	±(1% +3)
Resistance	200Ω/2kΩ/20kΩ/2MΩ/20MΩ	±(0.8% +1)
Capacitance	2nF/2n00F/100µF	±(4% +3)
Temperature (°F)	-40°F to 1,800°F	±(1% +3)
Frequency	2kHz/20kHz	±(1.5% +5)

Special Functions

Diode	
Continuity buzzer]
Transistor]
Data hold]
Full icon display	Yes
Sleep mode]
Low battery display]
Input impedance for DC voltage measurement (Around $10M\Omega$)]
Maximum display (1,999)	

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk www.mcmelectronics.com





General Characteristics

Power	9V battery (6F22)	
LCD size	60 × 54mm	
Product colour	Grey, holster - red	
Product net weight	351g (including holster)	
Product size	179 × 88 x 39mm	
Standard accessories	Test lead, battery, English manual, point contact temperature probe, multi-purpose socket, holster	
Optional accessories	Clip-on test lead light (UT-TL), built-in test lead light (UT-L1), built-in test lead light plus (UT-L2)	
Standard individual packing	Gift box	
Standard quantity per carton	30 pieces	
Standard carton measurement	480 × 420 × 290mm (0.059CBM per standard carton)	
Standard carton gross weight	19kg	

Part Number Table

Description	Part Number
Multimeter, Digital	72-7930

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Tenma is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk www.mcmelectronics.com

