

Conductive Carbon Infused Black Nylon Braided Sleeving



Description:

CN is braided from 11 mil carbonized nylon monofilament yarn. CN is designed to protect sensitive wiring from abrasion while shielding it from high frequency noise. Many successful applications have utilized CN for maintaining clean video signals, interference filtering in pro sound environments, and RF filtering on power cables and outputs. CN is also useful in static sensitive environments.

CN utilizes a patented carbonization process which infuses our braided sleeving with a microscopic carbon compound that is virtually indistinguishable from the base material. The result is a strong, long lasting jacket that is ready for the most sensitive applications.

Features:

- Economical and easy to install
- Expands up to 150%
- Resists gasoline and engine chemicals
- EMI, RFI protection
- Superior static disipation
- Cut and abrasion resistant
- Cut cleanly with hot knife

Specifications:

Material : Carbonized Nylon
 Grade : CNN
 Monofilament Diameter : .011"

Nominal Size	Part Number	Expansion Range		Bulk Spool	Wall Thickness	Available Colours	Lbs/100'
		Min	Max				
1"	CNN1.00BK	5/8"	1 5/8"	250'	0.028"	Black	1.37

Part Number Table

Description	Part Number
Conductive Carbon Infused Black Nylon Braided Sleeving	CNN1.00BK

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

