Firewire Cable Host to Device, 6 pin/M - 4pin/M multicomp









Cable : [30AWG (7/0.103)/1P + AL / MY + SPIRAL(50/0.10)] × 2C +

FILLER + MY + 90%BD(24/5/0.12/)]TIN


Insulation Wire One: FO-PE, OD = Ø0.88 ± 0.05MM


Colour: Red & Green, Blue & Orange Jacket: 80° C PVC, OD = \emptyset 4.8 ± 0.15MM

Colour: Platinum Gray


PVC : Platinum Gray

Connector : 1394 4P Male Nickel-Plating Insulator Colour: Black : 1394 6P Male Nickel-Plating Insulator Colour: Black Connector





Section A-A



Part Number Table

Description	Length	Part Number
Firewire Cable, Host to Device, 6 pin/M - 4pin/M	72 ± 1 [1829 ± 25.4]	SPC20016
	120 ± 2 [3048 ± 50.8]	SPC20014
	180 ± 2 [4572 ± 50.8]	SPC20015

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.



