


Socket


3.5mm Jack, PCB, Stereo

pro-SIGNAL



Specifications:

Maximum Contact Resistance	: 30mΩ
Minimum Insulation Resistance	: 100MΩ at 500V DC
Dielectric Withstand Voltage	: 500V AC for one Minute



Dimensions : Millimetres

Specification Table

Number	Designation	Material	Finished
1	Earth Terminal	0.25T Phosphor Bronze	Silver Plated
2	Ring Spring	0.2T TiCuR1-M-EH	
3	Tip Spring	0.25T TiCuR1-M-EH	
4	Barrel	Brass	Nickel Plated
5	Housing	PBT	Black Colour

Part Number Table

Description	Part Number
3.5mm Jack - PCB Stereo	PSG01538

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
 www.farnell.com
 www.newark.com
 www.cpc.co.uk

pro-SIGNAL