




## Specifications:

Metal material	: Spring Brass
Minimum insertion and extraction force	: 1kg
Minimum dielectric strength	: 500V AC for 60 seconds
Minimum insulation resistance	: 100MΩ at 500V DC
Maximum temperature rise	: 50°C
Maximum voltage drop	: 20mV
Body material	: Thermoplastic material
Metal material	: Phosphor Copper
Suitable rated current	: 30A 250V
Metal finish	: Bright tin plated
Low cost	
Low contact resistance	
Beryllium copper recommended for current higher than 30A	



Dimensions : Millimetres

## Part Number Table

Description	Part Number
Fuseholder, PCB Mount, ATO	MCCQ-121

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.