Digital Multimeter





Features:

- With Temperature
- Continuity buzzer
- Data hold
- Full icon display
- · Sleep mode
- Low battery display
- Included standard test leads, plus separate short leads for accurate capacitance checking
- Includes standard 9 V battery and owners manual
- Meets 1,000 V CATII standards

Description

Full function multimeter offers a variety of ranges for every service application, including Fahrenheit and Celsius temperature measurement. Rugged overmolded housing stands up to the daily rigors of field service use, and large backlit LCD display is easily read from several feet away. Measures AC / DC voltage, AC / DC current, resistance, capacitance frequency and temperature. 3 1/2 digit, 1,999 count display features 7/8 inches digits for easy at-a-glance reading.

Function	Range	Accuracy
DC Voltage	200 mV, 2 V, 20 V, 200 V, 1,000 V	± (0.5% + 1)
AC Voltage	2 V, 20 V, 200 V, 750 V	± (0.8% + 3)
DC Current	20 mA, 200 mA, 20 A	± (0.8% + 1)
AC Current	20 mA, 200 mA, 20 A	± (1% + 3)
Resistance	200 Ω, 2 kΩ, 20 kΩ, 200 kΩ, 2 MΩ, 20 MΩ, 200 MΩ	± (0.8% + 1)
Capacitance	20 nF, 200 nF, 2 μF, 100 μF	± (4% + 3)
Temperature (°C)	-40°C to 1,000°C	± (1% + 3)
Temperature (°F)	-40°F to 1,832°F	± (1% + 4)
Frequency	2 KHz to 20 KHz	± (1.5% + 5)
Input Impedance	10 ΜΩ	-
Dimensions	6 1/2 inches (H) × 3 1/4 inches (W) × 1 1/4 inches (D)	-

Part Number Table

Description	Part Number	
Multimeter, Digital	72-7725	

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA" is the registered trademark of the Group. © Premier Farnell plc 2012.



