
Header - Straight





Specifications:

| Maximum Contact Resistance | : 20 mΩ at 1 A dc |
|-------------------------------|--------------------------------|
| Minimum Insulation Resistance | : 1,000 M Ω at 500 V dc |
| Current Rating | : 2 A |
| Voltage | : 500 V ac for 1 minute |
| Operating Temperature | : -55°C to 105°C |
| Contact | : Brass |
| Housing | : PBT and 30% glass fibre |

Specification Table

| Number of Positions | Α | В | С | Part Number |
|---------------------|------------|--------------|-------------|-------------|
| 20 | 33 (1.299) | 30.6 (1.205) | 22.86 (0.9) | MC9A12-2034 |
| | | | | |

Dimensions : Millimetres (Inches)


www.element14.com www.farnell.com www.newark.com



Header - Straight



Part Number Explanation:



Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Famell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage raising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.



www.element14.com www.farnell.com www.newark.com