
## Studs





## **Specifications:**

Material / Finish : Steel / zinc and clear AISI 300 series stainless steel / self colour

Thread Size	М3	M4
D ±0.4	4.6	5.9
H maximum	2.1	2.4
Minimum rec sheet thickness	1	1
Hole +0.08 -0	3	4
Minimum distance to edge of sheet	5.6	7.2

## Part Number Table

Description	Part Number
Stud, Captive, M3 × 8, PK50	PFH-M3-8
Stud, Captive, M3 × 10, PK50	PFH-M3-10
Stud, Captive, M3 × 12, PK50	PFH-M3-12
Stud, Captive, M3 × 14, PK50	PFH-M3-14
Stud, Captive, M3 × 16, PK50	PFH-M3-16
Stud, Captive, M3 × 18, PK50	PFH-M3-18
Stud, Captive, M3 × 20, PK50	PFH-M3-20
Stud, Captive, M4 × 8, PK50	PFH-M4-8
Stud, Captive, M4 × 10, PK50	PFH-M4-10
Stud, Captive, M4 × 12, PK50	PFH-M4-12
Stud, Captive, M4 × 16, PK50	PFH-M4-16
Stud, Captive, M4 × 18, PK50	PFH-M4-18
Stud, Captive, M4 × 20, PK50	PFH-M4-20

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Famell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk www.mcmelectronics.com

