



Specifications:

Description	: 20 AWG (10 / 0.254 mm) tinned copper, heat resisting PVC insulated; UL Style 1015 (105°C in air, 600 V); CSA type TEW (105°C in air, 600 V)
Conductors	: 20 AWG (10 / 0.254 mm) tinned annealed copper bunch, complying with UL 758, and CSA standard C22.2 No.127 Minimum cross - sectional area : 0.503 mm ² Maximum lay of bunch : 31.8 mm
Insulation	: PVC compound meeting the requirements of class 43 PVC to UL 1581 and class 28 to CSA standard C22.2 No. 127 : Minimum thickness at any one point : 0.69 mm : Minimum average thickness : 0.76 mm : Nominal overall diameter : 2.6 mm Printed : CSA Type TEW 105°C 600 V FT-1 LL55192 E28423 20 AWG* AWM Style 1015 105°C 600 V VW-1 (where* is the recognised component mark)
Lay Up	: Not applicable
Screen	: Not applicable
Sheath	: Not applicable
Service Data	: For use as the internal wiring of apparatus : Maximum voltage rating : 600 V ac, 750 V dc : Maximum temperature rating : 105°C : Maximum current rating : at 20°C : 16.5 A : : at 30°C : 15 A : : at 40°C : 13.5 A : Approximate mass / unit length : 11 kg / km

Part Number Table

Description	Part Number
Wire, Blue, 10 / 30 AWG, 100 m	MCTEW 203110 BLU
Wire, Brown, 10 / 30 AWG, 100 m	MCTEW 203110 BRN
Wire, Red, 10 / 30 AWG, 100 m	MCTEW 203110 RED
Wire, Green / Yellow, 10 / 30 AWG, 100 m	MCTEW 203110 G/Y
Wire, Black, 10 / 30 AWG, 305 m	MCTEW 203110 BLK-305M

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.