
Adaptor

SMA Jack - MCX Plug





Dimensions : Millimetres (Inches)

Specifications:

Bodies: Brass per JIS-C3604
: Beryllium copper per ASTM B196 UNS C17300Centre Contact: Beryllium copper per ASTM B196 UNS C17300
: Beryllium copper per ASTM D1457 and ASTM D1710Connector interface per MIL-STD-348AConnector interface per CECC 22220Part to be clean and free of burrs

Specification Table

Number	Description	Material	Finish	Part Number
1	Chassis	Beryllium Copper	Gold 3 µ Inches Minimum	
2	Insulation	Teflon	None	
3	Centre Contact	Beryllium Copper	Gold 50 µ Inches Minimum	27-26 TGG
4	Body	Brass	Gold 3 µ Inches Minimum	
5	Insulation	Teflon	None	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Famell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.



www.element14.com www.farnell.com www.newark.com