



Crimp Terminal

Female, Red



Dimensions : Millimetres

Specifications:

Maximum Electric Current	: AWG	22	20	18	16
	: Amperes	3	4	7	10
Maximum Electrical Rating	: 105°C 300V maximum				
Insulation Material	: Nylon				
Insulation Colour	: Red				
Terminal Material	: Brass				
Wire Range	: 26 to 16AWG (0.5 to 1.5mm ²)				
Terminals Surface Treatment	: Tin plated				
Thickness	: 0.45mm				
Nema Tab	: 0.032" × 0.25" (0.8 × 6.35mm)				
Cable Diameter Min.	: 0.57mm				
Cable Diameter Max.	: 1.65mm				
Connector Type	: Disconnect				
Contact Material	: Copper				
Current Rating	: 12A				
Gender	: Receptacle				
Operating Temperature Min.	: -20°C to +85°C				
Voltage Rating	: 415V AC				

Part Number Table

Description	Part Number
Crimp Terminal - Female, Nylon Insulation, Red	FDFNY1-250

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.