

# Adaptor Mini DP To DVI

pro-SIGNAL



## Specifications:

### Cable Wiring

32AWG (7/0.08mm TCu) × 1P + D (7/0.08mm TCu) + AM × 5C + 32AWG (7/0.08mm TCu) × 5C + AD (7/0.08mm TCu) + B (16 × 7/0.12mm TCu) (Coverage 85%)

Jacket material : PVC OD: 4.8 ±0.1m  
Cable length : 0.15m  
Cable colour : White

### Connector A

Mini Display Port 20P male solder type

Insulation : White  
Contact : Brass, gold plated  
Shell : Fe, nickel plated


### Connector B

DVI (24 + 1)P female solder type (with PCB)

Insulation : Black  
Contact : Phosphor bronze, gold plated  
Shell : Fe, gold plated  
Over mould : Assembly, white

### Parameter Settings

Conductive resistance : 1Ω  
Minimum insulative resistance : 10MΩ  
Hi-Pot : DC 300V/10ms, 1.5mA/I, 50Hz, 0.03s



Dimensions : Millimetres

## Part Number Table

Description	Part Number
Adaptor, Mini DP To DVI, 150mm	HK-GDP02

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-SIGNAL is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com  
www.farnell.com  
www.newark.com  
www.cpc.co.uk

pro-SIGNAL