

Demo board description

The Keil MCB1857 Evaluation Board enables you to create and test working programs based on the LPC1800 family of ARM Cortex™-M3 based devices. The MCB1857 Evaluation Board and Starter Kit includes the MDK-ARM Lite Edition Tools. These tools help you get started writing programs and testing the microcontroller and its capabilities. Sample applications that run on the MCB1857 evaluation board, and a Quickstart guide are included.

Features

- Full-speed USB 2.0 Host/Device interface (USB host + micro USB Device connectors)
- CAN interfaces
- 180MHz ARM Cortex-M3 processor-based MCU in LBG256
- 136KB On-Chip SRAM
- 1MB dual bank On-Chip Flash
- On-Board Memory: 16MB NOR Flash, 4MB Quad-SPI Flash, 16 MB SDRAM, & 16KB EEPROM (I2C)
- Color QVGA TFT LCD with touchscreen
- 10/100 Ethernet Port
- High-speed USB 2.0 Host/Device/OTG interface (USB host + Micro USB Device/OTG connectors)
- Serial/UART Port
- MicroSD Card Interface
- 4 user push-buttons + reset
- Digital Temperature Sensor (I2C)
- Analog Voltage Control for ACD Input
- Audio CODEC with Line-In/Out and Microphone/headphone connector + Speaker
- Debug Interface Connectors:
 - 20-pin JTAG (0.1 inch)
 - 10-pin Cortex debug (0.05 inch)
 - 20-pin Cortex debug + ETM Trace (0.05 inch)

Descriptive summary

Keil MCB1857 Evaluation Board

The Keil MCB1857 Evaluation Board enables you to create and test working programs based on the LPC1800 family of ARM Cortex™-M3 based devices.