## **Day/Night Zoom Bullet Camera**





- High resolution 500TV lines in colour
- Vandal resistant housing
- 10 x Optical Zoom
- •
- Selectable 2 x, 4 x, 8 x Digital Zoom or OFF TRUE Day/Night, Mechanical Cut-Filter 33-piece Infra-Red LED Assembly with CDS Sensor
- On Screen Display (OSD) Menu
   DNR (Digital Noise Reduction) 4 levels of
- noise reduction Saves up to 70% HHD Storage with DNR, using MPEG Codec
- Selectable electronic shutter control, FLK/ ESC/Manual
- Selectable white balance, ATW/AWC/Manual

- Selectable back light compensation, H/M/L/Off
- Selectable gain control, H/M/L/Off
- Sens-up maintains luminance levels in low light x128
- Privacy masking 4 programmable zones
- Mirror function horizontal image inversion
- Camera Title
- IP67 rated
  Dual Voltage, DC12V/AC24V
  Fully Cable Managed Bracket
- Sunshield

Sony 1/4" Super HAD CCD 500 TVL Colour 570 TVL Monochrome Image Sensor Horizontal Resolution Effective Pixels Video Output

Electronic Shutter

570 TVL Monochrome  $752 \text{ (h)} \times 582 \text{ (v)}$   $CVBS 1.0V \text{ p-p} \sim 75\Omega$   $CVBS 1.0V \text{ p-p} \sim 75\Omega$  CSC (x/28, 1/50 to 10/20,000 sec.) Manual (x/28, 1/50 to 100,000 sec.) Minual (x/28, 1/50 to 100,000 sec.) Flickerless - 1/100 Sec.  $10 \times \text{Optical Zoom} \text{ (3.8-38.0mm F1.8 to F2.8)}$  Selectable 8 x Digital Zoom (0ff/x2/x4/x8) H: Approx. 51.2° (Wide) to 5.8° (Tele) V: Approx. 39.3° (Wide) to 4.27° (Tele) 33-piece LED Assembly with CDS Photosensor 800mA Max. with IR LEDs ON using DC12V 12V dc or 24V ac 145x100mm Lens Angle of View LED Power consumption

Power consumptions
Power supply
Dimensions (DiameterxH)
Operating temperature
Weight 145x100mm -10°C - 50°C 900g

450295 450232

Description Order Code Camera Remote Control 129-4899 129-4900