Wire Black, 105/30AWG





Description:

10AWG (105/0.254mm) tinned copper, heat resisting PVC insulated.

Specifications:

Reel Length (Imperial) : 500ft
Reel Length (Metric) : 152.4m
Conductor Size AWG : 10AWG
Conductor Area CSA : 5.56mm²
Jacket Colour : Black

Jacket Material : PVC (Polyvinyl Chloride)

Conductor Material : Copper External Diameter : 4.65mm Voltage Rating : 600V

No. of Strands \times Strand Size : 105 \times 0.255mm Conductor Make-up : 105 / 30AWG

Current Rating : 64A

Operating Temperature Max : 105°C

Primary Insulation Thickness : 0.79mm

Conductors:

10AWG (105/0.254mm) tinned annealed copper bunch. Minimum cross-sectional area $\hspace{1cm} : 5.103 mm^2 \\ \text{Maximum lay of bunch} \hspace{1cm} : 63.5 mm$

Insulation:

PVC compound meeting the requirements of class 43 PVC

: Minimum thickness at any one point : 0.69mm : Minimum average thickness : 0.76mm : Nominal overall diameter : 5mm

Part Number Table

Description	Part Number
Wire, Black, 105/30AWG, 152.5m	SPEC 31702

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com www.cpc.co.uk

