Jack BNC Bulkhead, RG179, Crimp





Specifications:

Connector Type : BNC Coaxial

Body Style : Straight Bulkhead Jack

Coaxial Termination : Crimp Impedance : 75Ω RG Cable Type : RG-179 Frequency Max : 11GHz : Panel **Connector Mounting** Contact Resistance : 1.5mΩ : 1A DC Current Max Mounting Type : Bulkhead

Operating Temperature : -65°C to +165°C


Proof Voltage : 2kV VSWR : 1.35 Working Voltage : 500V


Bodies : Brass per JIS-C3604 Centre Contact : Brass per JIS-C3604


Insulation : PTFE per ASTM D1457 and ASTM D1710

Crimp Ferrule : Brass per JIS-C2700

Part to be clean and free of burrs








Dimensions: Millimetres (Inches)


www.element14.com www.farnell.com www.newark.com




Jack BNC Bulkhead, RG179, Crimp









Stripping Dimension

Mounting Hole

Dimensions: Millimetres (Inches)

Description	Material	Finish
Nut	Brass	Nickel 100μ" Min.
Washer	Iron	
Body	Brass	
Insulation	PTFE	None
Gasket	Silicone	
Chassis	Brass	Nickel 100μ" Min.
Crimp Ferrule		
Centre Contact		Gold

Part Number Table

Description	Part Number
Jack BNC, Bulkhead, RG179, Crimp	13-11-4 TGN RG179

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

