

Coaxial Cable

RG58BU

pro-POWER



Features:

- Solid polyethylene insulated 1/0.8mm copper clad steel conductor
- Braid screen
- Black PVC sheathed overall to MIL-C17D
- Continuous length in 1m multiples

Specifications:

Coaxial Cable Type	: RG-58B/U
Impedance	: 50Ω
Approval Bodies	: MIL Spec
Attenuation @ 100MHz	: 1.7dB
Attenuation @ 1GHz	: 5.6dB
Nominal Outside Diameter	: 4.95mm
Jacket Material	: PE

Cable Construction:

Conductor	: Copper Clad Steel	: 0.813
Insulation	: Solid P. E.	: 2.95mm
First braiding	: Tinned Copper Wire Braid	: 0.11 × 112mm
Outer jacket	: PVC	: 4.95mm

Cable Properties:

Bending	: Min. Bending Radius	: Loaded	: 20 times cable OD
		: Unloaded	: 10 times cable OD
Tensile strength	: Max. Pulling Tension		: 126lbs
Temperature	: Operation		: -20 to +75°C
	: Installation		: 0 to +60°C

Electrical Characteristics:

Parameter Unit Value

Capacitance	: 100pF/m
Max. Voltage	: 15kV DC
Max. RF Working Voltage	: 2.5kV peak
Nominal Velocity of Propagation	: 66%
Nominal Conductor Resistance at 20/km	: 156
Nominal Shield Resistance at 20/km	: 15
Structural Return loss (100 - 1000MHz)	: >18dB
Sparker	: 4,000V AC
Dielectric Strength	: 2,500V AC

Coaxial Cable

RG58BU

pro-POWER

Attenuation dB/100m:

Frequency	Max. Attenuation
1MHz	1.44
10MHz	4.6
50MHz	10.8
100MHz	16
400MHz	37.7
700MHz	55.8
900MHz	65.6
1,000MHz	60

Part Number Table

Description	Part Number
Cable, Coaxial, RG58BU	RG58BU PER M

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com
www.farnell.com
www.newark.com
www.cpc.co.uk

pro-POWER