
Coax Cable



Belden New Generation plenum coaxial cable. UL type CMP approval. Foam dielectric and natural Flamarrest jacket. 649948 is Siamese construction, 1 RG-59/U with 2/18AWG. Applications: CCTV and CATV (CATV 633938 and 6339Q8 only). Key: BC=Bare Copper, CCS= Copper covered steel, FB= Foil plus braid.

			Ctr./			
Order #	Length	RG/U	Shield	(ea.)	(2-4)	(5-up)
Mfr. # 64	13948					
24-4930	1000'	59	BC/BC	\$859.00	\$794.63	\$739.83
24-4935	500'	59	BC/BC	477.00	437.86	404.82
Mfr. # 63	3948					
24-4940	1000'	6	BC/BC	1089.00	1008.15	938.63
24-4945	500'	6	BC/BC	605.00	555.52	513.59
Mfr. # 63	3938					
24-4950	1000'	6	BC/FB	972.00	899.45	837.42
24-4955	500'	6	BC/FB	540.00	495.62	458.21
Mfr. # 64	19948					
24-4960	1000'	59	BC/BC	1245.00	1152.41	1072.94

Belden Coaxial Cable

Belden New Generation coaxial cable. UL type CM approval. Foam dielectric and black PVC jacket. 549945 is Siamese construction, 1 RG-59/U with 2/18 AWG. 573945 is miniature RG-59/U. Applications: CCTV and CATV (CATV 5339B5 and 5339Q5 only). Key: BC=Bare Copper, CCS= Copper covered steel, FB= Foil plus braid.

			Ctr./			
Order #	Length	RG/U	Shield	(ea.)	(2-4)	(5-up)
Mfr. #543	945					
24-4980	1000'	59	BC/BC	\$273.00	\$252.04\$	\$234.66
24-4985	500'	59	BC/BC	152.00	138.88	128.40
Mfr. # 533	8985					
24-4990	1000'	6	BC/FB	196.00	180.93	168.45
24-4995	500'	6	BC/FB	109.00	99.70	92.17
Mfr. # 533	3945					
24-5000	1000'	6	BC/BC	356.00	328.89	306.21
Mfr. # 533	19Q5					
24-5020	1000'	6	BC/FB	259.00	239.63	223.11
Mfr. # 573	3945					
24-5030	1000'	59m	BC/BC	247.00	228.71	212.94
Mfr. # 513	3945					
24-5040	1000'	11	BC/BC	760.00	702.97	654.49
24-5045	500'	11	BC/BC	422.00	387.35	358.12

Wire and Cable

Section 1

e company

Wire and Cable

Antenna Wire	Hook-Up Wire
Heat Shrink	XLR Cables

RG-6/U

RG-6/U coaxial cable with 18AWG copper covered steel, mylar foil and 60% aluminum braid providing 100% shield coverage. Sweep tested to 2250MHz. Polyethylene dielectric and PVC jacket. OD .275" nominal. Impedance: 75ohm nominal. Sequential feet marking every two feet.

€)?‱

Order #	Length	(ea.)	(2-4)	(5-up)
Black				
24-5525	100'	\$9.95	\$7.51	\$6.74
24-5530	500'	39.95	33.64	30.58
24-5536	1000'	66.95	62.76	59.69
White				
24-5540	100'	9.95	7.51	6.74
24-5545	500'	39.95	33.64	30.58
24-5550	1000'	66.95	62.76	59.69

⇒)?‱

RG-6/U w/Solid **Copper Center**

RG-6/U coaxial cable with 18AWG solid bare copper center conductor, mylar foil and 60% aluminum braid providing 100% shield coverage. Sweep tested to 2250MHz. Polyethylene dielectric and PVC jacket. OD .280" nominal. Impedance: 750hm nominal. Sequential feet marking every two feet.

Order #	Length	(ea.)	(2-4)	(5-up)
24-5645	100'	\$12.95	\$11.62	\$10.56
24-5650	500'	56.95	51.86	48.62
24-5655	1000'	143 00	117 42	104 38

RG-6/U CL-2 Rated Coax Cable

RG-6/U type coax cable. 18AWG solid bare copper center conductor. Mylar

aluminum foil shield plus 40% aluminum braid provides 100% shield. Foam dielectric and PVC jacket. Outside diameter .270" nominal. Impedance 75ohm nominal. Perfect cable for high frequency cable systems, satellite television and DBS. CL2 rated for in wall use

→)?‱

wan use.				
Order #	Length	(ea.)	(2-4)	(5-up)
24-1765	100'	\$17.95	\$15.75	\$14.66
24-1770	500'	79.95	72.56	67.08
24-1775	1000'	168.00	152.16	139.48

Belden RG-6/U

18AWG solid bare copper covered steel, Duobond II plus 60% aluminum braid, 100% shield coverage. Polyethylene dielectric and PVC jacket. OD .270' nominal. Impedance 75ohm nominal. Mfr. #9116.

Order #	Color	Length	(ea.)	(2-4)	(5-up)
24-5120	Black	1000'	\$126.00	\$116.30	\$108.28
24-5125	Black	500'	70.95	64.09	59.25
24-5130	White	1000'	126.00	116.30	108.28

RG-6 Cable

Belden RG-6/U Coaxial Cable

Brilliance RG-6/U coaxial cable. 18AWG solid bare copper center, foam



dielectric, Duofoil plus 61% tinned copper braid, black PVC jacket. Mfr. #9248. p)

Urder #	Length	(ea.)	(2-4)	(5-up
24-5140	1000'	\$517.00	\$478.34	\$445.3
24-5145	500'	287.00	263.58	243.6

Plenum RG-6/U

18AWG solid bare copper center conductor, foam fluornated ethylene propylene insulation, foil tape plus 65% tinned copper braid provide 100% shield coverage. Natural flamarrest jacket. 75ohm.

Order # Mfr. # Length (ea.) (2-4)(5-up) **24-7680** 82248 1000' \$1756.00 \$1625.75 \$1513.63

Precision Belden RG-6/U



Belden precision video cables are used in critical analog video circuits and high quality applications such as live broadcast in network studios and pre-production or post-production facilities. Precision video cables are also recommended for the latest digital video applications. 18AWG solid bare copper conductor, foam dielectric, Duofoil shield with 95% tinned copper braid. Black PVC jacket. Mfr. #1694A.

Order #	Length	(ea.)	(2-4)	(5-up)
24-5180	1000'	\$604.00	\$559.08	\$520.52
24-5185	500'	336.00	308.07	284.82

Reiden **RG-6/U Precision** Video Cable

Order #

24-7565

24-7570

Mfr. #

1695A

1695A



(2-4)

\$1933.00\$1789.26\$1665.87

1074.00 985.92 911.51

(5-up)

Belden precision video cables are used in critical analog video circuits and high quality applications such as live broadcast in network studios and pre-or post-production facilities. They should be used anywhere superior signal integrity is required. 18AWG solid bare copper center conductor, foam polyethylene insulation, foil shield with 95% tinned copper braid provides 100% shield coverage, Black flamarrest jacket. 75ohm. Brilliance precision video coax for analog and digital SDI/HDTV applications.

(ea.)

Length

500

35 68 Black 24-5570 100

Order #

500'	97.95	85.69	77.91
1000'	192.00	163.88	148.99
100'	21.95	17.52	15.92
500'	97.95	85.69	77.91
1000'	192.00	163.88	148.99
	1000' 1000' 100' 500'	1000' 192.00 100' 21.95 500' 97.95	1000' 192.00 163.88 100' 21.95 17.52 500' 97.95 85.69

(ea.)

\$21.95

RG-6/U Quad Shield Coax Cable

RG-6/U Quad Shield

RG-6/U coaxial cable with 18AWG copper

braid, mylar foil and 40% aluminum braid

jacket. OD .30" nominal. Impedance: 750hm

Length

nominal. Sequential feet marking every two feet.

18AWG copper clad steel weld. Mylar

(2-4)

\$17.52

U

aluminum foil plus 46% aluminum braid coverage plus mylar foil and 43% aluminum braid providing exceptional levels of shielding. Foam polyethylene dielectric and PVC jacket. Outside diameter .275" nominal. Impedance 750hm nominal. UL listed NEC type CL2/CATV.

Order #	Length	(ea.)	(2-4)	(5-up)
Black				
24-4070	100'	\$18.95	\$15.89	\$14.80
24-4075	500'	93.95	84.94	78.53
24-4080	1000'	199.00	180.53	165.48
White				
24-4085	100'	18.95	15.89	14.80
24-4090	500'	93.95	84.94	78.53
24-4095	1000'	199.00	180.53	165.48




1189A Quad Shield RG-6/U

18AWG, solid bare copper covered steel center conductor, foam polyethylene dielectric, bonded aluminum foil (Bonded Duofoil) shield plus aluminum braid shield with 60% shield coverage plus aluminum foil (Duofoil) shield plus aluminum braid shield with 40% shield coverage and jacket.

Order #	Color	Length	(ea.)	(2-4)	(5-up)
24-7150	Black	1000'	\$181.00	\$166.86	\$155.35
24-7155	Black	500'	101.00	91.94	85.00
24-7160	White	1000'	181.00	166.86	155.35
24-7165	White	500'	101.00	91.94	85.00





(5-up)

\$15.92



Section 1

RG-6/U Dual

Two RG-6/U coaxial cable with 18AWG copper covered steel, mylar foil and 60% aluminum braid providing 100% shield coverage. Sweep tested to 2250MHz. Polyethylene dielectric and PVC jacket. OD .275" nominal. Impedance: 750hm nominal. Sequential feet marking every two feet. Black.

€)2

Order #	Length	(ea.)	(2-4)	(5-up)
24-5555	100'	\$25.95	\$22.34	\$20.80
24-5560	500'	94.95	77.50	73.81
24-5565	1000'	164.00	134.83	129.17

Dual RG/6U Quad Shield **Coax Cable**

Dual RG/6U quad shield coax cable for use in satellite TV and other applications requiring high levels of cable shielding. 18AWG copper clad steel weld. Mylar aluminum foil plus 40% aluminum braid coverage plus mylar foil and 40% aluminum braid providing exceptional levels of shielding. Foam polyethylene dielectric and PVC jacket. Outside diameter .295" nominal. Impedance 750hm nominal. UL rating: CL2 and CATV.

Order #	Length	(ea.)	(2-4)	(5-up)
24-2015	100'	\$41.95	\$37.67	\$35.07
24-2020	500'	201.00	184.31	170.40
24-2025	1000'	437.00	396.94	363.86



RG-59/U

RG-59/U coaxial cable with 20AWG copper covered steel, mylar foil and 60% aluminum braid providing 100% shield coverage. Sweep tested to 2250MHz. Polyethylene dielectric and PVC jacket. OD .240" nominal, Impedance: 750hm nominal, Sequential feet marking every two feet.

Order #	Length	(ea.)	(2-4)	(5-up)	
Black					
24-5435	100'	\$8.95	\$6.88	\$6.12	
24-5440	500'	31.95	27.52	24.46	
24-5445	1000'	53.95	50.49	45.91	
White					
24-5450	100'	8.95	6.88	6.12	
24-5455	500'	31.95	27.52	24.46	
24-5460	1000'	53.95	50.49	45.91	

RG-59/U Copper Braid

•22 gauge solid copper-covered steel weld •Foam dielectric •80% nominal copper braid shield •.240" (O.D.) nominal •750hm nominal impedance

(· /						
Order #	Length	(ea.)	(2-4)	(5-up)		
24-155	100'	\$25.95	\$22.30	\$20.76		
24-150	500'	111.00	101.21	93.57		
24-158	1000'	238 00	215 78	197 80		





RG-6/U Siamese w/Copper Center RG-6/U coaxial



cable with 18AWG solid bare copper center conductor, mylar foil and 60% aluminum braid providing 100% shield coverage. Sweep tested to 2250MHz. Polyethylene dielectric and PVC jacket. OD .280" nominal. Impedance: 75ohm nominal. 18AWG bare copper stranded wire, PVC jacket, color coded for easy polarity identification. Sequential feet marking every two feet.

Order #	Length	(ea.)	(2-4)	(5-up)
White				
24-5690	100'	\$27.95	\$24.10	\$21.33
24-5695	500'	96.95	93.00	90.30
24-5700	1000'	179.00	172.80	169.20



RG-6/U coaxial cable with 18AWG copper covered steel, mylar foil and 60% aluminum braid providing 100% shield coverage. Sweep tested to 2250MHz. Polyethylene dielectric and PVC jacket. OD .275 nominal. Impedance: 750hm nominal. 18AWG bare copper stranded wire, PVC jacket, color coded for easy polarity identification. Sequential feet marking every two feet.

Order #	Length	(ea.)	(2-4)	(5-up)
Black				
24-5660	100'	\$26.95	\$22.43	\$19.84
24-5665	500'	92.95	89.13	86.54
24-5670	1000'	172.00	165.60	162.15

RG-59 Cable

White Jacket **RG-59/U Copper Braid** •22 gauge solid copper-covered steel weld •Foam dielectric •80% copper braid shield •.240" (O.D.) nominal •750hm nominal impedance

	· · · · · · · · · · · · · · · · · · ·				
Order #	Length	(ea.)	(2-4)	(5-up)	
24-1110	100'	\$24.95	\$22.13	\$20.61	
24-1485	500'	111.00	101.21	93.57	



RG-59/U coaxial cable. 20AWG bare copper covered steel, Duofoil plus 40% aluminum braid, foam dielectric, black PVC Jacket. Mfr .#9275.

Order #	Length	(ea.)	(2-4)	(5-up)
24-5160	1000'	\$98.95	\$90.38	\$84.14
24-5165	500'	55.95	49.80	46.04

Belden _{RG-59/U}

Special application,

TV camera cables and CCTV cables, brilliance, RG-59/U Type, 22AWG, stranded (7x30) bare copper, foam polyethylene, bare copper braid, 95% shield coverage, black PVC jacket, for CCTV applications. Mfr. #9259.

Order #	Length	(ea.)	(2-4)	(5-up)
24-5190	1000'	\$483.00	\$447.04	\$416.21
24-5195	500'	269.00	246.33	227.74

IBelderi

RG-59/U Precision Video Cable

Belden precision video cables are used in critical analog video circuits and high quality applications such as live broadcast in network studios and pre-or post-production facilities. They should be used anywhere superior signal integrity is required. 20AWG solid bare copper center conductor, foam flourinated ethylene propylene insulation, foil shield with 95% tinned copper braid providing 100% shield c

coverage.	Black f	lamarres	t jacket. 78	ohm.	
Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)
24-7575	1506A	1000'	\$1684.00\$	1558.71	\$1451.21
24-7580	1506A	500'	936.00	858.88	794.06

RG-6 Cable

WEST PENN WIRE/CDT 🔳 Aqua Seal RG-6/U Aqua Seal cable has a

unique wrap between the jacket and the braid that stops moisture from getting into the cable, changing the characteristics of the cable or destroying the dielectric. RG-6/U type coax cable. 18AWG solid bare copper. Bifoil with 35% aluminum braid provides 100% shield. Foam polyethylene dielectric and sunlight resistant PVC jacket. Outside diameter .275" nominal. Impedance: 75ohm nominal. CL2 and CM rated. This cable is perfectly suited for CATV/MATV and DBS installations. Mfr. #AQC841.

Order #	Length	(ea.)	(2-4)	(5-up)
24-4220	500'	\$110.00	\$103.83	\$100.63
24-4225	1000'	219.00	207.63	201.25

WEST PENN WIRE/CDT **RG-6/U Flooded Burial**

Flooding agent between the jacket and the braided shield prevents moisture from migrating into the cable from bad connections or cable nicks. RG-6/U type coax cable. 18AWG copper covered steel. Bonded Bifoil with 61% aluminum braid provides 100% shield. Foam polyethylene dielectric and sunlight resistant polyethylene jacket. Outside diameter .275" nominal. Impedance 75ohm nominal. This cable is perfectly suited for CATV/MATV and DBS installations when cable needs to be

Order #	(ea.)	(2-4)	(5-up)
24-4235	\$144.00	\$136.21	\$132.02

Belden RG-59/U Digital Coax

Belden precision video cables are used in critical analog video circuits and high quality applications such as live broadcast in network studios and pre-or post-production facilities. They should be used anywhere superior signal integrity is required. Precision video cables are also recommended for the latest digital video applications. 23AWG solid bare copper center conductor, Foam polyethylene insulation, aluminum foil shield plus 95% tinned copper braid provide 100% shield coverage. Black PVC jacket. 75ohm miniature precision video cable. Limited quantities

Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)
24-7670	1855A	1000'	\$473.00	\$437.60	\$407.42
24-7675	1855A	500'	263.00	241.13	222.93

Beiden **BG-59/II** Precision Video Cable



Belden precision video cables are used in critical analog video circuits and high quality applications such as live broadcast in network studios and pre-or post-production facilities. They should be used anywhere superior signal integrity is required. 20AWG solid bare copper center conductor, foam polyethylene insulation, foil shield with 95% tinned copper braid provides 100% shield coverage, black PVC jacket suitable for indoor and outdoor applications. 75ohm. Brilliance precision video coax for analog and digital SDI/HDTV applications

courrer analog and algorat SD111D1 (approximits)					cattonioi
Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)
24-7555	1505A	1000'	\$494.00	\$457.04	\$425.52
24-7560	1505A	500'	277.00	253.98	234.82


RG-59/U Coax Cable

RG-59/U coaxial cable. 20AWG bare copper



covered steel, foam dielectric, Duobond II plus 40% aluminum braid, black PVC jacket. Mfr. #9100.

Order #	Length	(ea.)	(2-4)	(5-up)
24-5150	1000'	\$107.00	\$98.71	\$91.90
24-5155	500'	64.95	58.58	54.16



buried. 100	0'. Mfr. #6140.		
Order #	(ea.)	(2-4)	(5-up)
24-4235	\$144.00	\$136.21	\$132.0

RG-59 Cable

WEST PENN WIRE/CDT 📃 **Plenecon®**

Plenum RG-59/U

RG-59/U plenum type coax cable. 20AWG solid bare copper. 95% bare copper braid shield. Foam Teflon dielectric with tape barrier and flexible plenum jacket. Outside diameter .207" nominal. Impedance 75ohm nominal. This cable is perfectly suited for CATV and CCTV installations. Mfr. #25815.

Order #	Length	(ea.)	(2-4)	(5-up)
24-4245	500'	\$254.00	\$241.87	\$234.43
24-4250	1000'	508.00	483.73	468.85

WEST PENN WIRE/CDT **RG-59/U Siamese Cable**

RG-59/U type Siamese cable. 20AWG solid bare copper. Bare

copper braid provides 95% shield. Polyethylene foam dielectric and PVC jacket. Outside diameter .232" nominal. Impedance 750hm nominal. 1-pair 18AWG unshielded cable. This cable is perfectly suited for CCTV installations. Mfr. #A2815.

Order #	Length	(ea.)	(2-4)	(5-up)
24-4265	500'	\$132.00	\$124.94	\$121.09
24-4270	1000'	263.00	249.86	242.17

WEST PENN WIRE/CDT 📃

RG-59/U Plenum Siamese Cable

RG-59/U type Siamese cable. 20AWG solid bare copper. Bare copper braid provides 95% shield foam Teflon dielectric with tape barrier and copolymer jacket. Outside diameter .207" nominal. Impedance 750hm

Ordor #	(02)	(2-1)	(5-un)
500'. Mfr. #2	52815.		
is perfectly s	suited for CCT	V installation	s. Length:
	oair 18AWG un		

Uruer #	(ea.)	(2-4)	(a-nh)
24-4275	\$303.00	\$288.10	\$279.23

WEST PENN WIRE/CDT 75ohm S-VHS Cable

Dual cable construction.

25AWG solid bare copper. 95% bare copper braid shield. Foam polyethylene dielectric and PVC jacket. Outside diameter .146" nominal. Impedance 750hm nominal. CL2 and CM rated. This cable is perfectly suited for custom home theater installations. 1000'. Mfr. #2825-1000.

Order #	(ea.)
24-4305	\$159.00



RG-59/U coaxial cable with 20AWG solid bare copper center conductor, mylar foil and 60% aluminum braid providing 100% shield coverage. Sweep tested to 2250MHz. Polyethylene dielectric and PVC jacket. OD .240" nominal. Impedance: 750hm nominal. 18AWG bare copper twisted pair, PVC jacket, color coded for easy polarity identification. Sequential feet marking every two feet.

Order #	Length	(ea.)	(2-4)	(5-up)
24-5510	100'	\$29.95	\$25.77	\$23.60
24-5515	500'	125.00	118.30	108.96
24-5520	1000'	239.00	216.30	200.24

RG-59/U Plus 18/2



perfect for installing cable television systems and closed circuit television systems. Constructed with one RG-59/U cable molded to a two conductor 18AWG cable.

Order #	Length	(ea.)	(2-4)	(5-up)
24-2650	100'	\$39.95	\$35.76	\$33.30
24-2655	500'	226.00	207.13	191.50
24-2660	1000'	505.00	458.55	420.34



RG-59/U coaxial cable with 20AWG copper covered steel, mylar foil and 60% aluminum braid providing 100% shield coverage. Sweep tested to 2250MHz. Polyethylene dielectric and PVC jacket. OD .250' nominal. Impedance: 75ohm nominal. 18AWG bare copper stranded wire, PVC jacket, color coded for easy polarity identification. Sequential feet marking every two feet.

Order #	Length	(ea.)	(2-4)	(5-up)
24-5495	100'	\$28.95	\$24.70	\$22.61
24-5500	500'	120.00	113.37	104.42
24-5505	1000'	229.00	207.29	191.89

Precision RG-59/U Coaxial Cable

Belden precision video cables are used in critical analog video circuits and high quality applications such as live broadcast in network studios and pre- or post-production facilities. Precision video cables are also recommended for the latest digital video applications. Brilliance, 750hm precision video cables, double braided RG-59/U type, 20AWG, solid bare copper, polyethylene, tinned copper double braid, 98% shield coverage, black polyethylene jacket. Mfr. #8281.

Order #	Length	(ea.)	(2-4)	(5-up)
24-5170	1000'	\$1111.00	\$1028.71	\$957.76
24-5175	500'	618.00	566.84	524.06

Mini Coax Cable

Brilliance, 75ohm miniature coax, 23AWG, solid

braid, 95% shield coverage, black PVC jacket.

bare copper covered steel, polyethylene, bare copper

(ea.)

\$356.00

201.00

Miniature RG-59/U

Length

1000

500

Mfr. #8241.

Order #

24-5200

24-5205

Wire and Cable



Section 1

Coax Cable



14AWG solid bare copper center conductor, foam polyethylene insulation, foil tape plus 60% tinned copper braid provide 100% shield coverage. Black PVC jacket suitable for indoor and outdoor use. 750hm

outdoor use. roomin.							
	Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)	
	24-7635	9292	1000'	\$946.00	\$875.38	\$815.00	

RG-8/U Cable

•13AWG (7 strands x 21 gauge) center conductor

•Black PVC insulation •Bare copper braid, 70% shield • Foam dielectric •.405" (O.D.) nominal •60ohm nominal impedance •22pF/ft nominal capacitance •Attenuation/100' at 100MHz 2.0dB,

200MHz 3.0dB, 400MHz 4.5dB, 900MHz 6.8dB						
Order #	Length	(ea.)	(2-4)	(5-up)		
24-1565	50'	\$56.95	\$50.21	\$46.06		
24-1570	100'	66.95	60.21	56.06		
24-1575	500'	371.00	340.27	314.59		

RG8/II



RF400 wireless 50ohm coax cable. 9AWG, solid copper clad aluminum conductors, foam polyethylene insulation, black polyethylene jacket, Duofoil tape plus 95% tinned copper braid shields. Use: Suitable for indoor, outdoor, aerial and direct burial applications. Mfr. #7810A.

Order #	Length	(ea.)	(2-4)	(5-up)
24-5235	500'	\$746.00	\$684.29	\$632.65



93ohm, RG-62A/U Type, 22AWG, solid bare copper covered steel, semi-solid polyethylene, bare copper braid, 95% shield coverage, black PVC jacket. Length: 500'. Mfr. #9269.

Order #	(ea.)	(2-4)	(5-up)	
24-5215	\$215.00	\$197.05	\$182.17	

WEST PENN WIRE CDT

Minimax

Miniature Coax 25AWG solid bare copper. 95% bare copper braid

shield. Foam polyethylene dielectric and PVC jacket. Outside diameter .146" nominal. Impedance 750hm nominal. CL2 and CM rated. This cable is perfectly suited for CCTV installations. Mfr. #825.

Order #	Length	(ea.)	(2-4)	(5-up)
24-4285	500'	\$76.95	\$72.03	\$69.82
24-4290	1000'	152.00	144.06	139.63

WEST PENN WIRE/CDT 🔳 Minimax Miniature Siamese Coax

25AWG solid bare copper. 95% bare copper braid shield. Foam polyethylene dielectric and PVC jacket. Outside diameter .146" nominal. Impedance 750hm nominal. CL2 and CM rated. 1-pair 22AWG. This cable is perfectly suited for CCTV installations. Mfr. #45825.



(2-4)

\$329.63

184.49

(5-up)

\$306.90

170.57

MCM -Miniature 750hm Coaxial Cable

Commonly used in crowded surveillance system racks. 24AWG bare copper center conductor with foam dielectric, 60% copper braid and PVC jacket. OD is 0.145" nominal. Swept tested to 2200MHz. Limited quantities.

Binnied qu			
Order #	Color	Length	(ea.)
24-8585	Black	500'	\$54.95
24-8590	Black	1000'	89.95




Order #	Length	(ea.)	(2-4)	(5-up)
24-4295	500'	\$132.00	\$124.94	\$121.09
24-4300	1000'	299.00	294.00	289.00



Section 1

In-Wall **Speaker Wire**

Two and four conductor wire for various audio applications including whole-house sound and home theater. Color coded conductors for quick identification. CL2 rated.



			()	()	()
2 Conduc	tor				
24-5750	18AWG	100'	\$37.95	\$34.56	\$32.76
24-5755	18AWG	500'	102.00	96.12	91.08
24-5760	18AWG	1000'	202.00	196.83	186.47
24-5765	16AWG	100'	41.95	39.66	37.57
24-5770	16AWG	500'	112.00	109.18	103.45
24-5775	16AWG	1000'	325.00	294.66	270.11
24-5780	14AWG	100'	53.95	51.00	48.33
24-5785	14AWG	500'	124.00	120.53	114.19
24-5790	14AWG	1000'	260.00	253.97	240.60
4 Conduc	tor				
24-5795	18AWG	100'	49.95	47.48	45.00
24-5800	18AWG	500'	135.00	132.03	125.10
24-5805	18AWG	1000'	269.00	262.88	249.04
24-5810	16AWG	100'	58.95	56.69	53.71
24-5820	16AWG	1000'	318.00	310.73	294.37
24-5825	14AWG	100'	116.00	113.44	107.48
24-5830	14AWG	500'	247.00	241.13	228.45

CL3 Rated High Strand In-Wall **Speaker Wire**

Multi-conductor unshielded cable.

White PVC jacket with 0.035" wall. Conductors color coded red and black for two conductor and black, red, white and green for four conductor. PVC conductor jackets with 0.012" wall. 65 strands per conductor in 16AWG wire and 41 strands per conductor in 14AWG

wire. Listings: UL 13, UL/NEC 725, Type CL2, CL3.					
Order #	Description	Length	(ea.)	(2-4)	(5-up)
24-3020	16/2	100'	\$29.95	\$26.82	\$24.97
24-3025	16/2	500'	168.00	153.80	142.19
24-3030	16/2	1000'	364.00	330.85	303.28
24-3035	16/4	100'	47.95	43.15	40.18
24-3040	16/4	500'	275.00	252.54	233.48
24-3045	16/4	1000'	606.00	550.78	504.88
24-3050	14/2	100'	40.95	36.13	33.64
24-3055	14/2	500'	234.00	214.68	198.48
24-3060	14/2	1000'	516.00	468.41	429.38
24-3065	14/4	100'	66.95	60.84	56.64
24-3070	14/4	500'	400.00	366.88	339.19
24-3075	14/4	1000'	889.00	807.41	740.13

CM Rated In-Wall Speaker Wire Multi-conductor

unshielded cable. Gray PVC jacket with



0.025" wall. Conductors color coded red and black for two conductor and black, red, white and green for four conductor. PVC conductor jackets with 0.010" wall. 19 strands per conductor. Listings: UL 444, UL/NEC 800, Type CM, C(UL) CMH. 1000'.

Order #	Description	(ea.)	(2-4)	(5-up)
24-3000	16/2	\$325.00	\$294.66	\$270.11
24-3005	16/4	585.00	531.71	487.40
24-3010	18/2	231.00	209.30	191.86
24-3015	18/4	317.00	275.31	250.28



In-Wall Speaker

Wire High quality

two or four



conductor wire for various audio applications. High flexibility allows for ease of installation through walls and around obstacles. Ideal for in-wall speakers and intercom systems. UL approved for in-wall use. Individual conductors in a common jacket for ease of installation. Color coded for quick identification.

		1		
Gauge	Length	(ea.)	(2-4)	(5-up)
ctor				
14	100'	\$49.95	\$44.71	\$41.63
14	500'	217.00	198.80	183.80
16	100'	33.95	30.45	28.35
16	500'	149.00	136.72	126.40
18	100'	24.95	21.63	20.14
18	500'	108.00	98.35	90.93
uctor				
14	100'	90.95	82.97	77.25
16	100'	60.95	54.95	51.16
16	500'	265.00	243.27	224.91
18	100'	44.95	40.71	37.90
18	500'	184.00	168.15	155.46
	ctor 14 16 16 18 18 ictor 14 16 18 ictor 14 16 18 ictor 14 16 18 18	ctor 14 100' 14 500' 16 16 100' 16 18 500' 18 18 500' 16 16 100' 16 16 500' 16 16 100' 16 16 500' 16 18 100' 18	ctor 449.95 14 100' \$49.95 14 500' 217.00 16 100' 33.95 16 500' 149.00 18 100' 24.95 18 500' 108.00 Ictor 14 100' 90.95 16 100' 60.95 16 16 500' 265.00 18 18 100' 44.95 10'	ctor 449.95 \$44.71 14 100' \$49.95 \$44.71 14 500' 217.00 198.80 16 100' 33.95 30.45 16 500' 149.00 136.72 18 100' 24.95 21.63 18 500' 108.00 98.35 ictor

Direct Bury Speaker Cable

Designed for use with our outdoor landscaping speakers, this direct bury cable may also be used for other low voltage



applications including alarm control or 12V landscape lighting. Rugged polyethylene outer sheath is UV resistant and will withstand harsh weather environments. CL2 rating makes this suitable for in-wall use in residential applications. 14AWG conductors are 41 strand copper, meeting the most stringent sonic and flexibility requirements. Inner conductors are color coded red, black (two conductor) and red, black, green and white (four conductor). Shipped on wooden spools.

Order #	Conductors	Length	Weight	(ea.)	(2-4)	(5-up)
24-8690	Two	500'	30 lbs.\$2	224.00	\$211.00	\$184.61
24-8691	Two	1000'	60 lbs. 4	479.00	464.00	454.00
24-8695	Four	500'	49 lbs	299 00	284 00	279 00

Stereo Audio Cable

Make custom audio cables with this dual audio cable.

Shielded	to eliminate	e external r	ium and int	erierence.
Order #	Length	(1-9)	(10-49)	(50-up)
24-2575	50'	\$8.19	\$7.43	\$6.60
24-2580	100'	16.95	15.16	13.16

Contraction of the local division of the loc			

High Resolution Audio Cable

For custom made interconnects between audio/video components, MCM now offers high resolution cable to meet your home theater needs. This cable is 100% shielded with teflon center insulator for optimum performance. To be used with our gold plated RCA connectors. Cable size 6mm.

Order #	Size	(1-9)	(10-49)	(50-up)
50-2170	25'	\$7.95	\$6.32	\$5.80
50-2175	50'	14.95	12.94	11.56
50-2180	100'	34 89	30 48	27 59


PHILIPS S

Speaker Wire •Clear insulation		
Order #	Description	(1-9)
M62105	18 gauge/25'	\$1.80
M62111	24 gauge/50'	7.49

Speaker Wire

Belderi Composite





Composite speaker cables are available over-all jacketed or Siamese. Save time when running home audio systems with IR remote control or system control. 16 and 18AWG wires are over-all jacketed and 14AWG wires are Siamese.

Order #	Mfr. #	Lenath	Bonded Pairs	(ea.)	(2-4)	(5-up)
			raits	(64.)	(2-4)	(J-uh)
One Cat5	e plus 16	6/4				
24-7950	7949A	500'	Yes	\$444.00	\$407.15	\$376.42
One Cat5	plus 16/	4				
24-7960	7950A	500'	No	443.00	406.13	375.48
One Cat5	plus 18/	4				
24-7970		500'	No	438.00	402.05	371.70
One Cat5	plus 14/	4 Siame	se			
24-7980	7952A	500'	No	664.00	609.49	563.50

Standard Speaker	······	211111111111
Wire	annaf	mmm

 Two conductor clear insulation, 	polarity identified
by wire color •Made in USA	

Order #	Gauge	Length	(ea.)	(2-4)	(5-up)
24-310	24	50'	\$5.95	\$4.56	\$4.25
24-320	24	500'	32.95	28.82	26.65
24-330	24	1000'	63.95	56.91	52.17
24-340	18	50'	9.95	8.25	7.68
24-350	18	500'	85.95	77.52	71.67
24-360	18	1000'	178.00	161.62	148.15
24-370	16	50'	13.95	11.43	10.64
24-380	16	500'	121.00	110.98	102.61
24-390	16	1000'	262.00	238.07	218.23
24-110	12	50'	28.95	25.62	23.85
24-120	12	100'	47.95	43.36	40.37
24-130	12	500'	286.00	262.60	242.78



"Sound King" Speaker Wire

• Finely stranded, oxygen free copper conductors cabled in a ropelay design to increase the conductive surface, reduce skin effect and insure maximum flexibility •Superflex extra soft, 60°C clear PVC insulation •Extremely low capacitance, resistance and inductance of these cables transfer music signals from amplifier to speakers with high clarity and definition •Surface printed for identification and polarity •Made in USA

16 Gauge

•105 strands of 36 gauge copper

Order #	Length	(ea.)	(2-4)	(5-up)
24-1055	30'	\$13.95	\$11.88	\$11.06
24-1060	50'	20.95	18.06	16.82
24-1115	100'	36.95	32.58	30.33
24-1120	250'	88.95	80.56	74.48
24-2030	1'	0.79	-	-

12 Gauge

•259 strands of 36 gauge copper wire

Order #	Length	(ea.)	(2-4)	(5-up)
24-1065	30'	\$28.95	\$25.84	\$24.06
24-1070	50'	39.95	35.34	32.90
24-1125	100'	72.95	65.80	61.26
24-1130	250'	187.00	170.84	157.95
24-2035	1'	1.39	-	-

10 Gauge

413 strands of 36 gauge copper wire

Order #	Length	(ea.)	(2-4)	(5-up)
24-1135	30'	\$45.95	\$40.95	\$38.13
24-1140	50'	58.95	52.89	49.25
24-1145	100'	110.00	101.76	94.75
24-1150	250'	289.00	265.19	245.17
24-2040	1'	1.89	-	-



Speaker Wire

Taperwire-

Taperwire Kits Taperwire is designed for applications where standard wire runs are difficult. Taperwire can be concealed behind wall coverings like wall paper, and joint compound for painting. These kits come complete with wire and connectors to tra



transition from standard wire.							
Order #	Mfr. #	Description	(1-9 kits)	(10 kits-up)			
50-1520	218MAT-16	18AWG/16'	\$24.95	\$23.18			
24-2185	218MAT-30	18AWG/30'	39.95	38.62			

Audio Control

(ea.)

\$9.45

15.75

14.18

15.75



Length

100

50

50

Control Cable Paired 18AWG

Order #

DT50SW

DT100SW

DT50SW4

DT50FSW

Belden

stranded, tinned copper conductors (16 x 30) and chrome PVC jacket. 8760 features overall Beldfoil shield with 20AWG drain wire.

CA Digital Speaker Wire

AWG

16

14

16

•Oxygen-free copper wire provides high conductivity

·Polarity identified wire for correct speaker phasing

Order #	Mfr. #	Pair/ AWG	Length	(ea.)	(2-4)	(5-up)
24-5050	8760	1/18	1000'	\$291.00	\$267.45	\$248.00
24-5055	8760	1/18	500'	220.00	201.74	186.51
24-5085	8690	3/18	500'	567.00	520.72	481.42



Control and Instrumentation Cable

Four conductor, 18AWG stranded tinned copper conductors with PVC insulation and chrome PVC jacket. Aluminum foil tape shield provides 100% shield coverage.

Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)
24-7385	9418	1000'	\$718.00	\$664.26	\$618.45
24-7390	9418	500'	399.00	366.03	338.40





Designed for flexibility, service and reliable signal transmission at audio frequencies. Shielded single conductor cable is used in high impedance systems and multi-conductor cable is used in low impedance applications. Rubber jacketed cable for abrasion and impact resistance, allows cable to lie flat. Tinned cadmium bronze conductors, rubber insulated and tinned copper braid shield. 100'.

					(2-4)
Order #	Туре	AWG	Cond.	(ea.)	(2-4)
36F026WA	8413	24	2	\$195.00	\$177.21
36F013WA	8424	20	4	296.00	269.10



One twisted pair, stranded tinned copper. Polyethylene insulation, aluminum foil tape and 22AWG tinned copper drain wire provide 100% shield coverage. CM rated chrome PVC jacket.

Order #	Mfr. #	AWG	Length	(ea.)	(2-4)	(5-up)
24-7345	8761	22	1000'	\$315.00	\$291.12	\$271.04
24-7350	8761	22	500'	175.00	160.41	148.31
24-7375	8762	20	1000'	289.00	266.27	246.91
24-7380	8762	20	500'	219.00	200.72	185.57
24-7395	8719	16	1000'	667.00	617.60	575.00
24-7400	8719	16	500'	371.00	340.31	314.63



Shielded Triad Audio, **Control and Instrumentation Cable**

One triad, three conductors, stranded tinned copper conductors with polyethylene insulation. Aluminum foil tape and 20AWG tinned copper drain wire provide 100% shield coverage. CM rated chrome PVC jacket.

Order #	Mfr. #	AWG	Length	(ea.)	(2-4)	(5-up)
24-7355	8770	18	1000'	\$556.00	\$514.82	\$479.32
24-7360	8770	18	500'	309.00	283.68	262.27
24-7485	8771	22	1000'	361.00	333.89	310.87
24-7490	8771	22	500'	201.00	183.98	170.10

Shielded Audio. Control and Instrumentation Cable

Three twisted pairs, 22AWG stranded tinned copper conductors. Polypropylene insulation and chrome PVC

jacket. Individual aluminum foil tape shielded pairs with a 22AWG stranded tinned copper drain wire provide 100% shield coverage.

Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)
24-7415	8777	1000'	\$741.00	\$686.12	\$638.80
24-7420	8777	500'	412.00	378.07	349.53





Plenum Audio.

Control and Instrumentation Cable

Two conductors, 18AWG, stranded tinned copper conductors with fluorinated ethylene propylene (FEP) insulation and jacket, aluminum foil shield and a 20AWG drain wire providing 100% shield coverage.

Order #	Mfr. #	AWG	Length	(ea.)	(2-4)	(5-up)
24-7365	88760	18	1000' \$	\$1050.00	\$971.67	\$904.66
24-7370	88760	18	500'	583.00	535.41	495.00
24-7520	88761	22	500'	560.00	514.09	475.29




Unshielded Audio, Control and Instrumentation Cable

One twisted pair, stranded tinned copper conductors. PVC insulation and chrome PVC jacket. 9740 is high strand count for added cable flexibility.

Order #	Mfr. #	AWG	Length	(ea.)	(2-4)	(5-up)
24-7425	8442	22	1000'	\$201.00	\$186.12	\$173.28
24-7430	8442	22	500'	112.00	102.56	94.82
24-7535	8205	20	1000'	254.00	234.82	218.63
24-7540	8205	20	500'	141.00	129.39	119.63
24-7475	9740	18	1000'	329.00	304.26	283.28
24-7480	9740	18	500'	183.00	167.66	155.00
24-7495	8461	18	1000'	342.00	316.49	294.66
24-7405	8471	16	1000'	604.00	558.71	520.18

Wire and Cable





Beiden

Microphone Cable Brilliance, 99.95% pure high conductivity



copper, two conductor

low impedance cables. 20AWG, two conductor stranded (26 x 34) tinned copper conductors, copper braid shield. Black rubber jacket for greater abrasion and impact resistance and extra limpness so the cable will lie flat on stage or on studio floors.

04 5005	E001	00000	00.000	<i>¢</i>EE0 40
Order #	Length	(ea.)	(2-4)	(5-up)
1111. #0412.				

Paired Audio and **Control Cable**



One twisted pair, 22AWG stranded, tinned copper conductors. Polypropylene insulation, foil tape with 22AWG stranded, tinned copper drain wire providing 100% shield coverage. Gray PVC jacket.

Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)
24-7605	9451	1000'	\$213.00	\$197.23	\$183.63
24-7610	9451	500'	120.00	110.00	101.70

Shielded Beinen Plenum Audio. Control. and Instrumentation

Paired 22AWG stranded, tinned copper conductors with foil tape and 22AWG drain wire to provide 100% shield coverage. FEP insulation and natural Flamarrest jacket.

Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)
24-7445	82761	1000'	\$582.00	\$538.34	\$501.21
24-7450	82761	500'	323.00	296.64	274.25



BHUHI **Paired Audio Cable**

1 twisted pair stranded (7 x 30) 22AWG tinned copper conductors. Polypropylene insulation, Beldfoil shield with 22AWG tinned copper drain wire providing 100% shield. PVC jacket is riser rated. 1000'. Mfr. #8451.

Order #	(ea.)	(2-4)	(5-up)
24-7175	\$209.00	\$193.52	\$180.18



many popular antenna rotators. Outer jacket 0.162" black PVC with 0.020" wall. Three 20AWG conductors color coded black, white and red.

Order #	Length	(ea.)	(2-4)	(5-up)
24-3080	100'	\$25.95	\$22.34	\$20.80
24-3085	500'	111.00	101.94	94.25
24-3090	1000'	238.00	215.80	197.82













Reiden

Wire and Cable



Unshielded Riser Cable

Մլ Belden New Generation riser fire alarm cable. UL, NEC approvals. Bare copper solid conductors. Red PVC jacket with

ripcord. **Applications:** Fire protective, alarm, signal, monitor/detection. Mfr. 5120UL. Order # Length Cond/AWG (ea.) (2-4)(5-un)

04 40 40	10001	0/4.4	0040.00		4070.00
24-4840	1000	2/14	\$318.00	\$294.08	\$273.80
24-4845	500'	2/14	177.00	162.05	149.82



• Multiconductor unshielded control, audio and computer cable. •Tinned copper stranded cable, PVC insulation, chrome PVC jacket •Working voltage 600V

Order #	Туре	Cond.	(0.D.)	(L)	(ea.)	(2-4)
22AWG						
36F040WF	8443	3	.172"	500'	\$158.00	\$144.49
36F041WA	8444	4	.185"	100'	51.95	45.50
36F041WF	8444	4	.185"	500'	188.00	171.84
37F3085WA	9421	8	.229"	100'	89.95	80.19
37F3085WF	9421	8	.229"	500'	330.00	302.96
37F3086WA	9423	9	.244"	100'	98.95	89.03
36F201WA	8457	12	.272"	100'	121.00	109.62
20AWG						
36F043WA	8446	6	.236"	100'	106.00	95.94
36F1086WA	9444	4	.217"	100'	66.95	59.53
36F1086WF	9444	4	.217"	500'	245.00	224.90
37F3089WA	9439	7	.260"	100'	115.00	104.05
36F1088WA	9455	9	.317"	100'	159.00	144.14
36F1089WA	9457	12	.338"	100'	79.89	65.22
18AWG						
36F1018WA	8467	7	.324"	100'	143.00	129.19
36F144WA	8466	12	.424"	100'	230.00	208.91
36F145WA	8468	15	.505"	100'	321.00	291.10
16AWG						
36F146WA	8620	4	.375"	100'	181.00	163.85
36F1095WA	9620	5	.405"	100'	227.00	205.69

Unshielded Riser Multi-Conductor

Belden New Generation riser alarm cable. UL NEC approvals. Bare copper conductors. 5582UE is stranded, all others are solid. Gray PVC jacket with ripcord. Applications: Security systems, intercom/PA systems, sound/audio, power limited controls.

Seiden

(U)

Order #	Mfr. #	Lenath	Cond/ AWG	(ea.)	(2-4)	(5-up)
24-4770	5300UE	1000'	-	<u> </u>	· /	\$129.66
24-4775		500'	2/18	88.95		74.06
24-4790	5582UE	1000'	4/22	129.00	118.71	110.52
24-4795	5582UE	500'	4/22	74.95	67.86	62.74
24-4810	5500UE	1000'	2/22	94.95	86.30	80.35
24-4815	5500UE	500'	2/22	58.95	52.56	48.59
24-4855	5200LIE	500'	2/16	11/ 00	10/ 00	06.23



Four conductor, 24AWG stranded, tinned copper conductors. Foil tape with 24AWG stranded tinned copper drain wire provides 100% shield coverage. PVC insulation and chrome PVC jacket.

Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)
24-7510	9534	500'	\$192.00	\$176.33	\$163.02



Multi-Conductor Wire




Belden New Generation unshielded plenum multi-conductor cable. UL, NEC, CMP approvals. Bare copper conductors. Natural Flamarrest jacket with ripcord. Applications: Security systems, intercom, PA systems, sound/ audio, power limited controls.

Order #	Length	Cond/ AWG	Length	n (ea.)	(2-4)	(5-up)
Mfr. #630	OUE					
24-4680	1000'	2/18	Gray	\$213.00	\$197.04	\$183.45
24-4685	500'	2/18	Gray	122.00	111.64	103.21
Mfr. #630)2UE					
24-4725	500'	4/18	Natura	204.00	187.05	172.93

Shielded **Riser Multi** Conductor Cable

New



Generation, four conductor, 22AWG stranded bare copper conductors. PVC insulation, foil tape with 24AWG stranded tinned bare copper drain wire providing 100% shield coverage. Gray PVC jacket. Common applications include: Broadcast, intercom/P.A. systems, sound/audio, power limited controls.

Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)
24-7700	5502FE	1000'	\$183.00	\$168.89	\$157.25
24-7705	5502FE	500'	105.00	96.43	89.16





Belden New Generation riser alarm cable. UL, NEC approvals. Bare copper stranded conductors. Beldfoil shield applied overall with a drain wire. Gray PVC jacket with ripcord. Applications: Security systems, broadcast, intercom/PA systems, sound/audio, power limited controls.

Order #	Mfr. #	Length	Cond AWG		(2-4)	(5-up)
24-4780	5300FE	1000'	2/18	\$199.00	\$183.89	\$171.21
24-4785	5300FE	500'	2/18	115.00	104.90	96.99
24-4830	5500FE	1000'	2/22	129.00	119.08	110.87
24-4835	5500FE	500'	2/22	75.95	68.68	63.50

Űl Reidei **Shielded Riser Multi-Conductor**



Belden New Generation riser alarm cable. UL, NEC approvals. Bare copper solid conductors. Beldfoil shield applied overall with a drain wire. Red PVC jacket with ripcord. Applications: Fire, broadcast, intercom/PA systems, sound/audio, power limited controls

Order #	Mfr. #	Length	Cond/ AWG		(2-4)	(5-up)
24-4820	5320FL	1000'	2/18 \$	178.00	\$164.45	\$153.11
24-4825	5320FL	500'	2/18	102.00	92.86	85.85
24-4860	5220FL	1000'	2/16	248.00	228.89	213.11
24-4865	5220FL	500'	2/16	96.95	88.37	81.30



Computer Cable

Non Paired

Four conductor, 24AWG stranded, tinned copper conductors. Foil tape with 24AWG stranded tinned copper drain wire provides 100% shield coverage. PVC insulation and chrome PVC jacket.

Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)
24-7510	9534	500'	\$192.00	\$176.33	\$163.02



Twisted Pair Riser Cable

Belden New Generation riser cable. UL, NEC approvals. Bare copper stranded conductors. Shielded cables are Beldfoil shield applied overall with a drain wire. Gray PVC jacket with ripcord. Applications: Security systems, intercom/PA systems, sound/audio, power limited controls. Pair/

Order #	Mfr. #	Length	AWG	(ea.)	(2-4)	(5-up)
Unshield	ed					
24-4905	5341FE	500'	2/18	\$273.00	\$250.11\$	\$231.23
Shielded						
24-4920	5541FE	1000'	2/22	283.00	261.86	243.80





Belden New Generation shielded plenum multi-conductor cable. UL, NEC, CMP approvals. Bare copper conductors. Natural Flamarrest jacket with ripcord. Beldfoil shield applied overall (foil side out plus 20AWG drain wire). Applications: Alarm, security, broadcast, intercom/PA systems, sound and audio, power limited controls, background music, nurse call. Natural color.

			Cond	/		
Order #	Mfr. #	Length	AWG	(ea.)	(2-4)	(5-up)
24-4670	6300FE	1000'	2/18	\$239.00	\$220.75	\$205.52
24-4675	6300FE	500'	2/18	133.00	121.64	112.46
24-4710	6500FE	1000'	2/22	176.00	162.78	151.56
24-4715	6500FE	500'	2/22	101.00	92.76	85.76
24-4750	6302FE	1000'	4/18	300.00	276.47	256.36
24-4755	6302FE	500'	4/18	228.00	208.88	193.12



Belden New Generation plenum cable. UL, NEC approvals. Bare copper stranded conductors. Shielded cables are Beldfoil shield applied overall with a drain wire. Natural Flamarrest jacket with ripcord. Applications: Broadcast, intercom/PA systems, sound/audio, power limited controls. Doin/

			rair/			
Order #	Mfr. #	Length	AWG	(ea.)	(2-4)	(5-up)
Shielded						
24-4870	6541FE	1000'	2/22	\$297.00	\$275.00	\$256.04
24-4875	6541FE	500'	2/22	165.00	151.54	140.10
24-4885	6342FE	500'	3/18	454.00	416.23	384.82
Unshielded						
24-4895	6341UE	500'	2/18	275.00	252.35	233.31
Plenum	Nata		Ø			

'lenum Data

Transmission Cable • Plenum cable is designed to be used without conduit in



ducts and ceiling plenum areas •Resists high temperatures, aging, cracking, chemicals and maintains its excellent mechanical and dielectric properties •Shielded 4 conductor wire with drain •22 gauge stranded wire •Color coded: Red, white, black and green • Meets UL Article #725 of the National Electric Code

Order #	Length	(ea.)	(2-4)	(5-up)
24-1000	100'	\$72.15	\$52.46	\$45.89
24-1005	500'	282.30	261.29	228.46
-		Belden	ndividuall Shielded	У

Paired Computer Cable

Tinned copper conductors. Black and red under Beldfoil® aluminum-polyester

Order #	Lenath	(ea.)	(2-4)			
	Pairs cabled on apacitance 35 pl neter: .165".					
shield. Stranded tinned common drain wire. Chrome						

Order #	Length	(ea.)	(2-4)
36F1033WA	100'	\$54.95	\$48.85
36F1033WF	500'	201.00	184.39
36F1033WM	1000'	362.00	334.63

Multi-Conductor Wire

Belden



Two twisted pairs, 24AWG stranded tinned copper conductors, foam polyethylene (datalene) insulation, individual aluminum foil shielded pairs each with

24AWG stranded tinned copper drain wire providing 100% shield coverage. Chrome PVC jacket. Order # Mfr. # Length (2-4) (ea.) (5-up)



Belden Paired **Computer Cable**



One twisted pair 24AWG, stranded tinned copper conductors Semi-rigid PVC insulation and chrome PVC jacket. Foil shield with 24AWG stranded tinned copper drain wire providing 100% shield coverage.


Order #	Mfr. #	Length	(ea.)	(2-4)	(5-up)
24-7550	9501	500'	\$138.00	\$126.43	\$116.89

Computer Cables

• Multiconductor, 28 gauge stranded wire • PVC type insulation •Complete shielding reduces

RF interference

Order #	Conductors	Length	(ea.)	(2-4)	(5-up)
83-0035	9	100'	\$51.19	\$44.86	\$40.38
83-0330	9	500'	216.79	201.30	189.69
83-0360	12	500'	267.79	246.98	228.29



Belden Multi-Conductor **Computer Cable** Multi-conductor computer cable for RS-232 applications.

15 conductor, 24AWG stranded conductors (7 x 32). Overall Beldfoil shield with 24AWG drain wire. Chrome PVC jacket. Mfr .#9541.

Order #	Length	(ea.)	(2-4)	(5-up)
24-5065	500'	\$556.00	\$510.31	\$471.80

Enamel Magnet Wire

•Used for making custom coils, transformers, etc. Copper wire with ename insulation •Temperature range: -30°~80°C • Sold in ¼ lb. spools

	\bigcirc
1	
	THE

	A	pproximat	е		
Order #	Gauge	Length	(ea.)	(2-4)	(5-up)
24-825	30	770'	\$9.84	\$8.91	\$8.09
24-828	28	500'	8.65	8.22	7.54
24-830	26	300'	10.11	9.19	8.22
24-833	24	200'	7.98	7.26	6.57
24-835	22	125'	9.31	8.49	7.67
24-838	20	75'	7.98	7.26	6.57
24-840	18	50'	7.98	7.05	6.38
24-843	16	63'	15.93	13.31	11.97

Shielding and Belaen Bonding Cable

Tinned copper braided wire provides approximately 90% shield coverage when applied over recommended diameter 50'

Order #	Туре	(I.D)	(ea.)	(2-4)
36F220WB	8660	.125"	\$83.95	\$75.27
36F225WB	8663	.21875"	49.23	43.90

For the latest Product Additions www.mcminone.com

Data Cable






Unshielded, paired telephone cable. 2 pair, 24AWG solid conductors, chrome PVC jacket. Mfr. #9562.

r #	Length	(ea.)	(2-4)	(5-up)
070	1000'	\$344.00	\$318.15	\$296.21
075	500'	191.00	175.31	162.08

Telephone Line Cord •Color-coded stranded wire •Custom design

your own

24-50



modular extension cords to any length •Silver PVC jacket •26 gauge

Order #	Length	(1-9)	(10-up)
4 Conductor			
36-460	100'	\$12.88	\$12.31
36-465	500'	39.57	36.33
6 Conductor			
36-615	100'	10.26	9.24
36-620	500'	82.49	74.67
8 Conductor			
36-625	100'	17.27	15.31

Four Conductor Telephone Wire

Four conductor 24AWG solid bare copper conductors. Polyethylene insulation color coded red, green, black and yellow. Natural color PVC jacket. Available; four conductor cable, four conductor with drain wire and shielded four conductor with drain wire.

Order #	Length	(ea.)	(2-4)	(5-up)
24-7235	1000'	\$38.95	\$35.17	\$32.11


Telephone **Station Wire**

•4 conductor •22 gauge solid wire • Color coded: Red.

green, yellow and black • PVC/polyethylene jackets

n

Urder #	Length	(ea.)	(2-4)	(5-up)
24-055	50'	\$10.95	\$9.12	\$8.49
24-060	100'	17.95	15.00	13.97
24-050	500'	76.95	69.33	64.10



installations. Order# Length (ea.) 24-6385 \$7.95 50' 24-6390 27.99 24-6395 30 00 24-6400 500 66.95

Ground Wire

Type THHN wire commonly used as ground wire. 10AWG stranded or solid copper with oil and gas resistant coating. Available in stranded and solid.

Order #	Description	(ea.)	(2-up)
24-5365	Stranded, 500' spool	\$129.94	-
24-5370	Solid, 500' spool	129.94	\$107.06
24-5375	Solid, sold per foot	1.11	0.88

Wire and Cable

e company

Section 1

Category 6 Keinen Mediatwist® **UTP Cable**



Belden's 1000' MediaTwist®


Cat6 UTP cable is a unique cable design delivering the ultimate in unshielded twisted pair performance. Media Twist features 24AWG solid bare copper conductors, and four twisted pairs bonded in a PVC jacket to effectively separate and isolate each pair minimizing NEXT interference. Jacket sequentially marked at two foot intervals, and nominal O.D. is 0.365. Mfr. #1872A.

Order #	(ea.)	(2-4)	(5-up)
24-7170	\$258.70	\$245.70	\$232.70

Twisted Unshield pair cabl used in h data app		nly	No and a second		
Order #	Conductors	Length	(ea.)	(2-4)	(5-up)
24-5915	4 pair	100'	\$13.95	\$10.84	\$9.98
24-5920	4 pair	500'	42.95	40.45	38.23
24-5925	4 pair	1000'	75.95	71.88	69.07

Paired Category 5e UTP Cable

Twisted pair wire is most commonly used in high speed signal applications. These include computer, telephone, video and



security. 24AWG solid, category 5e. PVC jacket, F+4, 75°C maximum rated, UL CMR and CSA listed.

Order #	Length	(ea.)	(2-up)	
24-1740	500'	\$59.95	\$53.96	
24-1745	1000'	119.00	107.10	

l Beiden **Paired Category 5e UTP Cable** Unshielded, four pair,

24AWG solid bare copper

conductors. 1585A: Blue Flamarrest® Plenum jacket with nylon ripcord. 1583A: Blue PVC jacket with nylon ripcord. 1000'

Order #	Mfr. #	(ea.)	(2-4)	(5-up)
24-5100	1583A	\$164.00	\$151.86	\$141.38
24-5105	1585A	279.50	261.10	247.72



Solid bare copper 24AWG conductors. 1700A, Blue PVC jacket with ripcord. 1701A, Blue Flamarrest jacket with ripcord. 1000'.

Order	Mfr. #	(ea.)	(2-4)	(5-up)
24-5110	1700A	\$217.00	\$200.19	\$186.38
24-5115	1701A	443.00	410.19	381.90



Orde 24-50



Section 1

'Amp King" Primary Wire

• Multi-stranded single conductor primary wire • 99.9% pure electrolytic copper, cabled in a ropelay design for maximum flexibility and conductivity • Made of a flame retardant



compound that is highly resistant to oil, water, alkalies, ozone, grease and diesel fumes •High gloss finish •Surface printed with gauge, description and one-foot markers •Made in USA

10 Gauge \bullet **4**13 strand ropelay construction

Order #	Length	Color	(ea.)	(2-4)	(5-up)
24-1390	100'	Red	\$45.95	\$41.67	\$38.80
24-1395	100'	Black	45.95	41.67	38.80
24-1400	250'	Red	131.00	120.23	111.16
24-1405	250'	Black	131.00	120.23	111.16
24-2050	1'	Black	0.79		-

8 Gauge •665 strand ropelay construction

Order #	Length	Color	(ea.)	(2-4)	(5-up)
24-1410	100'	Red	\$68.95	\$62.28	\$57.99
24-1415	100'	Black	68.95	62.28	57.99
24-1420	250'	Red	202.00	185.31	171.33
24-2055	1'	Red	0.99	-	-
24-2060	1'	Black	0.99	-	-

4 Gauge •1672 strand ropelay construction							
Order #	Length	Color	(ea.)	(2-4)	(5-up		
24-1430	100'	Red	\$155.00	\$142.89	\$133.04		
24-1435	100'	Black	155.00	142.89	133.04		
2 Gauge •Strand ropelay construction							
Order #	Length	Color	(ea.)	(2-4)	(5-up		
24-1950	25'	Red	\$50.57	\$49.23	\$47.91		

Clear	Blue

50.57

317.00

49.23

292.93

47.91

272.73

Black

Primary Wire

24-1965 25

100

24-1940

Add distinctiveness to any automotive sound system with this clear/blue primary wire. Made from high strand, oxygen free tinned copper for maximum flexibility and performance.

Order #	AWG	Length	(ea.)	(2-4)	(5-up)
Blue					
24-4130	8	100'	\$66.95	\$61.02	\$56.82
24-4135	8	250'	175.00	160.60	148.48
24-4150	8	1'	1.29	-	-
Clear					
24-4170	8	100'	66.95	61.02	56.82
24-4190	8	1'	1.29	-	
24-4195	4	1'	2.36	-	-

Kynar Wire

Kynar wire commonly used for wire wrap projects. 30 gauge solid wire in various colors to ease circuit identification.

Order #	Description	(ea.)	(2-4)	(5-up)
24-1805	25' red	\$6.64	\$5.48	\$4.10
24-1810	50' red	10.65	9.59	8.22
24-1815	25' black	6.64	5.48	4.10
24-1820	50' black	10.65	9.59	8.22
24-1830	50' green	10.65	9.59	8.22
24-1845	25' yellow	6.64	5.48	4.10
24-1850	50' yellow	10.65	9.59	8.22
24-1855	25' white	6.64	5.32	3.98
24-1860	50' white	10.65	9.59	8.22



Automotive Primary Wire

•Multi-stranded single conductor automotive



primary wire •Soft bare electrolytic copper for maximum flexibility and conductivity •Made of a flame retardant compound that is highly resistant to oil, water, alkalies. ozone, grease and diesel fumes •Made in USA

Order #	Length	Color	(ea.)	(2-4)	(5-up)
16 Gauge	-19 strand	is of 29 g	jauge copp	er wire	
24-1250	100'	Red	\$16.95	\$14.17	\$13.19
24-1255	100'	Black	16.95	14.17	13.19
24-1260	250'	Red	33.95	29.90	27.65
		is of 27 g	jauge copp		
24-1270	50'	Red	13.95	11.26	10.49
24-1275	50'	Black	13.95	11.26	10.49
24-1280	100'	Red	22.95	19.86	18.49
24-1285	100'	Black	22.95	19.86	18.49
24-1290	250'	Red	51.95	46.15	42.67
24-1295	250'	Black	51.95	46.15	42.67
			lande cobb		
24-1300	50'	Red	18.95	16.08	14.97
24-1305	50'	Black	18.95	16.08	14.97
24-1310	100'	Red	30.95	27.69	25.78
24-1315	100'	Black	30.95	27.69	25.78
24-1320	250'	Red	77.95	70.70	65.36
24-1325	250'	Black	77.95	70.70	65.36
			jauge copp		
24-1330	50'	Red	24.95	21.65	20.16
24-1335	50'	Black	24.95	21.65	20.16
24-1340	100'	Red	43.95	39.13	36.44
24-1345	100'	Black	43.95	39.13	36.44
24-1350	250'	Red	114.00	104.03	96.17
24-1355	250'	Black	114.00	104.03	96.17
			luge coppe		
24-1360	50'	Red	37.95	33.95	31.61
24-1365	50'	Black	37.95	33.95	31.61
24-1370	100'	Red	69.95	63.71	59.32
24-1375	100'	Black	69.95	63.71	59.32

Automotive "Zip" Cord

Multi-stranded soft bare electronic copper conductors. Insulated with



80° "GPT" automotive grade VW-1 flame retardant PVC. One conductor is all red and one conductor is all black (for polarity) in "zip cord" construction. Useful as "CB" power cord, stereo, alarm and other general purpose applications.

Order #	Length	(ea.)	(2-4)	(5-up)
18 Gauge				
24-1875	50'	\$11.95	\$10.17	\$9.47
24-1870	100'	19.95	16.88	15.71
24-1865	250'	48.95	43.60	40.31
24-2070	1'	0.39	-	
16 Gauge				
24-1890	50'	14.95	12.88	11.99
24-1885	100'	27.95	24.28	22.61
24-1880	250'	69.95	62.62	57.89
14 Gauge				
24-1905	50'	20.95	18.38	17.11
24-1900	100'	37.95	34.15	31.80
24-1895	250'	101.00	92.76	85.76
12 Gauge				
24-1920	50'	31.95	28.54	26.57
24-1915	100'	58.95	53.13	49.47
24-1910	250'	165.00	150.90	139.51
24-2080	1'	0.89	-	-
10 Gauge				
24-1935	50'	40.95	36.52	34.00
24-1930	100'	75.95	69.28	64.50
24-1925	250'	217.00	199.05	184.02

Kynar Wire

300' spool of Kynar wire commonly used for wire wrap and prototyping. 30AWG solid wire in various colors for easy circuit identification.

Order #	Color	(ea.)	(2-up)
24-7300	Black	\$16.16	\$15.25
24-7305	Red	16.16	14.81
24-7310	Yellow	16.16	14.81
24-7315	Green	16.16	14.81
24-7320	Blue	16.16	14.81
24-7325	Violet	16.16	14.81
24-7330	White	16.16	14.81

Belden PVC Insulated Hook-Up Wire

General Purpose Wire

(anna)

Hook-up wire with tinned copper and PVC insulation. PVC is flame and ozone resistant, as well as being inert to most chemicals, oils and solvents. .016" insulation thickness. 100' rolls.

	e i	. 100 10113.	()
Order #	Color	(ea.)	(2-4)
28AWG Type 992	8		
37F3199WA-1	Brown	\$29.95	\$25.87
37F3199WA-3	Orange	29.95	25.87
37F3199WA-9	White	29.95	25.87
37F3199WA-10	Black	29.95	25.87
26AWG Type 992	6		
37F3200WA-2	Red	31.95	27.66
37F3200WA-4	Yellow	31.95	27.66
37F3200WA-9	White	31.95	27.66
37F3200WA-10	Black	31.95	27.66
24AWG Type 992			
37F3201WA-2	Red	32.95	29.07
37F3201WA-4	Yellow	32.95	29.07
37F3201WA-5	Green	32.95	29.07
37F3201WA-9	White	32.95	29.07
37F3201WA-10	Black	32.95	29.07
22AWG Type 992		02.30	23.01
37F3202WA-1	Brown	37.95	33.62
37F3202WA-1	Orange	37.95	33.62
37F3202WA-3	Yellow	37.95	33.62
37F3202WA-4	Green	37.95	33.62
37F3202WA-9	White	37.95	33.62
37F3202WA-9	Black	37.95	33.62
20AWG Type 991		01.50	00.02
37F3204WA-1	Brown	46.95	41.30
37F3204WA-2	Red	46.95	41.30
37F3204WA-2	Orange	46.95	41.30
37F3204WA-3	Yellow	46.95	41.30
37F3204WA-4	Green	46.95	41.30
37F3204WA-9	White	46.95	41.30
37F3204WA-9			
18AWG Type 991	Black	46.95	41.30
37F3206WA-1	Brown	51.95	46.05
37F3206WA-1		51.95	46.05
37F3206WA-2 37F3206WA-3	Red Orange	51.95	46.05
37F3206WA-3 37F3206WA-4			46.05
37F3206WA-4 37F3206WA-5	Yellow	51.95 51.95	46.05
37F3206WA-5 37F3206WA-9	Green	51.95	46.05
	White		46.05
37F3206WA-10	Black	51.95	46.05
16AWG Type 991		74.05	66 40
37F3207WA-2	Red	74.95	66.48
37F3207WA-3	Orange	74.95	66.48
37F3207WA-4	Yellow	74.95	66.48
37F3207WA-5	Green	74.95	66.48
37F3207WA-9	White	74.95	66.48
37F3207WA-10	Black	74.95	66.48
	0	A.IIIIIIIIIIIII	5
	¥		



•Solid or stranded •50' roll •22 gauge

Order #	Туре	Color	(ea.)	(2-4)	(5-up)
24-535	Solid	Black	\$2.29	\$2.03	\$1.76
24-530	Solid	White	2.29	2.03	1.76
24-550	Stranded	Black	2.43	2.03	1.89

Stranded

Test Lead Wire

Rubber/PVC test lead wire for making custom probe leads or clip leads. 18 gauge stranded conductor (65 gauge x 36 strands). Insulation thickness .045, outside diameter .140. Working voltage 5,000V. Construction resists oils, acids and solvents. UL listed. 50' length.

Order #	Description	(ea.)	(2-4)	(5-up)
24-1795	50' 18 gauge, red	\$11.80	\$11.47	\$10.80
24-1800	50' 18 gauge, black	14.95	14.67	13.80
Standar	d Lamp Wire			

• 2 conductor: One bare copper, one tinned copper • 18 gauge standard • 1 conductor ribbed for polarity identitication • 300V suggested working voltage • Brown jacket • SPT-1 • Made in USA Order # Length (ea.) (2-4)

- 01 1-1 - 1	aue in Obr	.		
Order #	Length	(ea.)	(2-4)	(5-up)
24-570	50'	\$10.99	\$9.75	\$8.73
24-575	100'	15.93	15.03	13.71
24-580	500'	89.95	80.84	74.74
24-2065	1'	0.18	-	-

Type Patch Cables

Push On "F" to "F" Jumper Cables

•High-quality coaxial cable •750hm •RG-59 • Molded strain relief •Nickel plated

• Male connectors

Order #	Length	(1-9)	(10-49)	(50-up)
Nickel Pla	ted			
32-3675	3'	\$2.29	\$1.98	\$1.71
32-3680	6'	5.19	4.46	3.80
32-3685	12'	9.29	6.79	5.66
Gold Plate	d			
32-600	3'	5.89	5.43	4.94
32-605	6'	7.49	5.76	5.00
32-607	12'	8.59	7.71	6.39

Right Angle Push On "F" to "F" Jumper Cables

• Right angle connectors on both ends for use where space is limited •High quality, 750hm RG-59 cable Molded strain relief

Order #	Length	(1-9)	(10-up)
32-930	3'	\$2.79	\$2.03
32-935	6'	3.39	2.54

3.5mm to "F" Patch Cable

Order #	Longth	(1.0)
a 3.5mm i	input jack.	
		1011
	elevision w	
an antenr	na or VCR t	oa
plug. Use	for connect	ing 📄
	F" to 3.5mr	
D	TW 4 - 9 F	

a 3.5mm i	input jack.			
Order #	Length	(1-9)	(10-49)	(50-up)
24-2530	3'	\$2.09	\$1.84	\$1.53
24-2535	6'	2.59	2.22	2.08
24-25/0	10'	3 60	2 25	2 70

RG Digital Coaxial Cable

•RG-6 •24K gold-plated

DT250

•Anti–kink strain relief wrap					
Order #	Length	(ea.)			
DT6C	6'	\$5.51			
DT12C	7.01				

Thomas&Betts Waterproof Patch Cables

Waterproof "F" to "F" patch cables for use with DSS and outdoor antennas. Features unique Snap-N-Seal connectors to keep moisture out of the connection. Made of RG-6 quad shield cable.

Order #	Length	(1-9)	(10-49)	(50-up)
33-4200	3'	\$5.11	\$4.74	\$4.21
33-4205	6'	6.14	5.80	5.26
33-4210	10'	7.16	6.85	6.32
33-4215	15'	9.21	8.96	8.44
33-4220	50'	20.45	19.99	19.42
33-4230	100'	35.82	35.36	34.80

"F" to "F" **Patch Cables**

•High quality jumper

cables •750hm •Ideal for cable, TV, and VCR connections Male connectors



9.45

Order # Length (1-9)(10-up) Gold plated 32-580 \$3.19 \$2.38 3 32-585 3.19 2.69 Nickel plated 33-544 3.09 1.51 33-548 6' 2.29 2.00 33-1150 3.29 2.50 33-4030 25 4.39 3.76 33-4035 9.59 8.77



Stellar Labs **SLP Series "F" Type Miniature Coaxial Cables**

The Stellar Labs SLP Series "F" type RF Coaxial Cables are ideal for transporting cable TV, DSS or 750hm RF antenna signals to your TV, or monitor. The flexible, UL listed wire features a thin 4.00 mm outer diameter making it ideal in tight spots and patch panel environments. The screw-lock "F" type connector features a gold-plated, corrosion free construction ensuring long-lasting, securely fastened interconnects. Limited lifetime warranty.

Order #	Length	(1-10)	(11-50)	(51-up)
24-8930	1.5'	\$6.39	\$5.70	\$5.34
24-8931	3'	6.99	5.85	5.48
24-8932	6'	8.89	6.05	5.68
24-8933	9'	9.59	6.36	5.95
24-8934	12'	10.79	6.73	6.30
24-8935	25'	11.39	7.58	7.19
24-8936	50'	16.95	10.84	10.17



Stellar OLabs **SLP Series F-Type RG-6 Coaxial Cables**

The Stellar Labs SLP Series "F" type RG-6 Coaxial Cables are ideal for transporting cable TV, DSS or 750hm RF antenna signals to your TV, or monitor. The flexible, UL listed wire features a 7.0mm outer diameter, dual EMI/RFI shielding technology, and thick polyethylene dielectric surrounding OFC conductors. The screw-lock "F" type connectors feature gold-plated, corrosion free construction to further reduce interference and attenuation, and improve video signal transmission. Limited lifetime warranty.

Order #	Length	(1-10)	(11-50)	(51-up)
24-8920	1.5'	\$6.89	\$5.69	\$5.34
24-8921	3'	7.19	6.36	5.88
24-8922	6'	7.49	6.14	5.67
24-8923	9'	8.09	6.65	6.24
24-8924	12'	9.39	7.11	6.65
24-8925	25'	7.95	5.70	5.34
24-8926	50'	15.95	10.56	9.89

RG-59 Cable

• 10' extension • 750hm • Male connectors		3		
Order #	Туре	(1-9)	(10-49)	(50-up)
33-520	BNC to BNC	\$17.95	\$15.05	\$13.01
33-530	BNC to RCA (shown)	11.39	11.10	8.67
33-540	RCA to RCA	8.29	7.63	7.03

White RF Patch Cables

75ohm patch cables with male "F" connectors at each end. White jacket to

blend with decor inside as well as outside the house. Length (1-9) (10-49) (50-up)

0.00	_0g	()	()	(00 00)
24-2545	3'	\$2.49	\$1.97	\$1.77
24-2550	6'	2.99	2.26	2.08
24-2555	10'	5.39	4.66	3.04
24-2560	25'	5.79	5.11	4.66
24-2565	50'	13.49	12.23	11.69

Bulk Screw Type RF Cables

Order #

Save money by purchasing bulk. These cables are



available 20 per package for home theater installation or use to give away when doing service calls. 75ohm cable with screw on "F" connectors on each end.

Order #	Length	Price per Cable	(pkg.)
24-2515	3'	\$1.05	\$20.95
24-2520	6'	1.50	29.95
24-2525	10'	1.75	34.95

Wire and Cable



Section 1

BNC Patch Cables

Molded strain reliefs to ensure long life. Male BNC connectors on each end Perfect for use with professional video equipment and closed circuit television (CCTV) applications



Order #	Length	(ea.)	(2-4)	(5-up)
75ohm				
24-1605	1'	\$6.09	\$5.40	\$4.63
24-1610	3'	6.59	5.88	4.97
24-1615	6'	7.79	6.88	5.76
24-1620	10'	8.29	7.46	6.96
24-5350	25'	23.95	21.37	20.16
24-1625	50'	33.95	30.83	24.30
24-1630	100'	58.95	54.10	46.74
24-1635	250'	137.00	122.65	105.12
50ohm				
24-1455	1'	8.19	7.78	7.14
24-785	3'	8.99	7.80	7.28
24-790	6'	9.49	8.40	7.50
24-795	12'	10.49	9.93	8.63
24-1515	30'	19.95	17.30	14.67

Composite Video Patch Cables

RCA to RCA Patch Cables

 Made of high-quality, 75ohm RG-59 cable •Molded strain relief

•Male connectors



Order #	Length	(1-9)	(10-up)
Gold Plated			
32-5265	1'	\$2.89	\$2.45
32-5275	2'	3.29	2.94
32-590	3'	3.49	3.17
32-595	6'	3.99	3.30
32-597	12'	4.99	3.69
32-4500	25'	5.39	5.20
32-4505	50'	13.39	12.67
Nickel Plate	d		
32-5270	1'	2.49	1.98
32-5280	2'	2.89	2.51
32-4540	3'	3.29	2.74
32-4545	6'	3.49	2.66
32-4550	10'	4.49	3.47
32-4555	25'	5.49	4.79
32-4560	50'	10.29	9.24

Fully Shielded Cables with Teflon Insulated Gold Connectors



These attractive cables offer the very best in signal quality and style designed around our

#50-2130 gold plated teflon insulated connectors. These cables feature 100% shielded pure copper braiding with teflon shielded center conductors, wrapped in a midnight blue outer jacket with silver connectors. 6mm diameter. Sold in pairs.

Order #	Length	(1-9 prs.)	(10-49 prs.)	(50 prsup)
50-2150	1½"	\$11.36	\$9.69	\$8.78
50-2155	3'	12.37	10.35	9.58
50-2160	6'	14.65	12.37	11.06
50-2165	12'	18.69	16.13	14.51





nu-by caple
Extensions
•10' extension •75ol •Male connectors
Order # Type



Section 1

Composite Video Patch Cables



Stellar<u>© Labs</u> **SLP Series** Composite Video Cables Stellar Labs SLP

Composite Video Cables are ideal for long cable runs where EMI/RFI shielding and

signal integrity are crucial. Featuring twisted pair, oxygen free 75ohm coaxial copper construction, and a 7.0mm thick, but flexible PVC jacket, these cables are ideal for transporting video signals with minimal degradation. •UL listed wire •Limited lifetime warranty •Available in lengths up to 150

Order #	Length	(1-10)	(11-50)	(51-up)
24-8871	3'	\$8.99	\$8.28	\$7.77
24-8872	6'	9.19	8.98	8.42
24-8873	9'	9.39	7.99	7.49
24-8874	12'	8.89	7.23	6.78
24-8875	25'	14.29	11.00	10.96
24-8876	50'	14.39	12.32	11.56
24-8877	75'	20.95	17.45	16.37
24-8878	100'	24.95	20.60	19.31
24-8879	150'	33.95	28,16	26.40

Stellar@<u>Labs</u> **SLV Series Composite** Video Cables

The Stellar Labs Value Series Composite Video Cables are high quality interconnect

assemblies commonly used to connect the composite video signal on you're audio/video equipment. Features: • EMI/RFI shielded, low-loss, 750hm video coaxial wire helps reduce interference and improve resolution, color and brightness •Long-lasting, corrosion resistant, gold plated barrel connectors with fully over-molded, custom tooled strain reliefs. •Color-coded connectors for easy identification

Order #	Length	(1-9)	(10-up)
24-9410	1½'	\$3.19	\$2.22
24-9411	3'	3.89	2.71
24-9412	6'	4.99	3.48
24-9413	12'	6.69	4.69
24-9414	25'	14.79	10.57
24-9415	50'	21.95	14.45
24-9416	75'	30.95	21.35
2/-0/17	100'	38.05	27 72

Video Patch Cable	V	ÍC	eo	Pa	tch	Ca	ble	
-------------------	---	----	----	----	-----	----	-----	--

•RCA male plug to RCA male plug				
Order #	Length	(1-3)	(4-up)	
VMC-10	3'3"	\$3.09	\$2.87	
VMC 20	0'0"	2 70	2 70	

S-VHS Unterminated Cable

High flexibility S-VHS cable for making custom S-VHS cables.

Ideal for applications in home theaters for video projectors and jumper cables. Two individually shielded cables made of oxygen free copper.

Order #	Length	(ea.)	(2-4)	(5-up)
24-4100	50'	\$20.95	\$17.86	\$14.91
24-4105	100'	43.95	39.75	36.23
VISA	MasterCard	NOVUS	Contact Contact	NET 30 Terms
26	14/14		Online	

Composite to S-Video Patch Cables



Stellar () Labs SLP Series S-Video to **Composite Video Cables**

The Stellar Labs SLP Series S-Video to Composite Video Cables covert S-video signals into a composite video format for use on display equipment without S-video

connections. The twisted pair, oxygen free coaxial copper construction provides the ideal media for converting your video signal with minimal degradation to signal quality. SLP cables feature dual EMI/RFI shielding, tangle free bonded wires, gold plated corrosion free shielded S-video connectors, and secure split-lock ring composite video RCA connectors. Limited life-time warranty.

Order #	Length	(1-10)	(11-50)	(51-up)
24-8852	6'	\$10.59	\$9.82	\$9.21
24-8853	9'	11.09	8.86	8.30
24-8854	12'	12.39	9.37	8.78
24-8855	25'	13.19	10.59	9.94

Stellar©<u>Labs</u>

SLV Series Composite/ S-Video and Stereo Audio Cables The Stellar Labs Value



Series Composite/S-Video and Stereo Audio Cables are uniquely designed for connecting your audio/video sources and receivers. Their bonded, tangle-free construction and flexible PVC cable jacket reduces cable clutter and makes cabling interconnections effortless. The combination of S-video and composite video wires enables worry-free compatibility with video components, and the long-lasting, corrosion-resistant, gold plated barrel connectors include custom tooled strain reliefs engineered to improve durability and reliability. Features: • EMI/RFI shielded, low-loss, dual conductor 75ohm coax S-video wire to deliver high-resolution video images •Color-coded composite video 750hm coaxial cable that delivers clear, crisp images • Dual 26AWG shielded audio wires protect against noise and distortion •Color-coded red and white RCA audio connectors

Order #	Length	(1-9)	(10-up)
24-9390	1½'	\$4.99	\$3.51
24-9391	3'	6.19	4.34
24-9392	6'	10.29	7.32
24-9393	12'	13.39	9.57
24-9394	25'	17.95	12.24
24-9395	50'	24.95	17.42



Composite Video to S-Video Adaptor Cables

With precision machined gold plated connectors and a unique circuit, these cables are designed to connect standard composite video devices to S-video inputs and vice versa. These cables are the perfect solution to problems associated with mixing composite and S-video inputs and outputs. Note: This unit is a passive device and although it will allow composite video signals to be used in S-video inputs the signal will remain the quality of composite video.

Order #	Length	(ea.)	(2-4)	(5-up)
24-6500	1'	\$17.51	\$16.16	\$13.51
24-6505	2'	18.86	17.51	14.81
24-6510	3'	20.23	18.86	16.16
24-6515	6'	22.93	22.23	19.43
24-6520	10'	25.64	24.28	21.58
24-6525	15'	29.69	26.99	24.28
24-6530	25'	33.75	31.04	28.34

S-Video Patch Cables



Stellar 🔘 Labs

SLP Series S-Video Cables

Commonly used with DVD players, satellite receivers and VCRs, Stellar Labs SLP

S-Video Cables provide excellent signal integrity and superior video quality. The twisted pair, oxygen free coaxial copper construction provides the ideal media for separating and transporting color and brightness signals. SLP cables feature dual EMI/RFI shielding, tangle free bonded wires, and gold plated corrosion free shielded S-video connectors. •UL listed wire •Limited lifetime warranty 8Available in lengths up to 150'.

	,			
Order #	Length	(1-10)	(11-50)	(51-up)
24-8821	3'	\$20.95	\$14.21	\$12.69
24-8822	6'	21.95	19.52	13.08
24-8823	9'	31.95	18.53	15.47
24-8824	12'	29.95	17.60	14.77
24-8825	25'	35.95	20.55	18.34
24-8826	50'	54.95	33.49	29.90
24-8827	75'	71.95	42.49	37.94
24-8828	100'	78.95	41.82	37.34
24-8829	150'	88.95	60.36	53.90

Stellar

SLV Series S-Video Cables

The Stellar Labs Value Series S-Video Cables are high quality interconnect assemblies commonly used with DVD



players, satellite receivers and VCRs. Features: • Individually shielded, low-loss, dual 750hm video coaxial conductors, which separate color and

brightness signals to maximize video signal transfer •Long-lasting, corrosion resistant, gold plated barrel connectors with fully over-molded, custom tooled strain relief

Order #	Length	(1-9)	(10-up)
24-9360	1½'	\$3.59	\$2.42
24-9361	3'	3.69	2.49
24-9362	6'	4.99	3.53
24-9363	12'	6.29	4.45
24-9364	25'	12.29	8.52
24-9365	50'	18.95	13.29
24-9366	75'	29.95	21.28
24-9367	100'	33.95	24.00
24-9368	150'	49.95	35.11

Stellar@<u>Labs</u> SLV Series S-Video "Y" Splitting Cables



Perfect for splitting the video

from one to two S-video devices, the Stellar Labs Value Series S-Video "Y" Splitting Cables are high quality interconnect assemblies commonly used with DVD players, satellite receivers and VCRs. Features: •Individually shielded, low-loss, dual 750hm video coaxial conductors, which separate color and brightness signals to maximize video signal transfer •Long-lasting, corrosion resistant, gold plated barrel connectors with fully over-molded, custom tooled strain relief •4 pin DIN male to two 4 pin DIN male

	- p		
Order #	Length	(1-9)	(10-up)
24-9370	1½'	\$3.79	\$2.66
24-9371	3'	4.49	3.16
24-9372	6'	5.99	4.21
24-9373	12'	7.49	5.27
24-9374	25'	14.89	10.61


MCM **Bulk S-Video Cables** Save money by purchasing

your S-video cables in bulk. These cables are available 20 per package for home theater installations or use to give away when doing service calls.

Order #	Length	(pkg.)
24-6365	6'	\$98.95
24-6370	12'	102.00
24-6375	25'	168.00

www.mcminone.com

S-Video Patch Cables



Not recor	nmended for using	two sourc	es on on	e input.
Order #	Description	(ea.)	(2-4)	(5-up)
24-7830	1 male to 2 female	\$7.29	\$6.78	\$5.97
24-7835	1 female to 2 male	8.49	7.87	6.93



S-Video Splitting Cables make extending your S-video signals quick and easy. The cables allow you to

split the chrominance and luminance signals over standard coaxial cable.

This separation allows you to minimize signal loss and maximize cable run length. For best performance, be sure to keep coaxial cables the same length and free from kinks. Available with "F" type male or BNC female connectors. Must be purchased in pairs.

Order # Description

(1-9)24-9000 S-video to 2 BNC(f) splitter \$23 95 24-9005 6' S-video to 2 "F" type(m) splitter 25.95

#24-9000

#24-9005



Wire and Cable

Gold Plated S-Video Jumper Cables

For use in any number of video applications including DVDs, S-VHS VCRs, DBS satellite receivers and video games High quality cables with molded strain reliefs and gold connectors.



Section 1

one company

8010 000			
Order #	Length	(ea.)	(2-4)
32-1205	6'	\$6.39	\$5.22
32-1210	12'	11.39	8.58
32-3845	24'	14.79	11.19
24-7335	50'	29.95	23.53
24-7340	100'	33.95	27.52

Component Video Patch Cables



Stellar **Component Video Cables (3RCA to HD15)**

These Stellar Labs Value Series video cables are uniquely designed to connect your component video output to the component RGB, and Y-Pb-Pr video input on HDTVs, LCD projectors, and satellite TVs. Now you can connect your component video device (DVD player, for example) to the VGA input connector on HDTV compatible displays, like a home theater DLP projector. **Features:** •100% shield with an overlapped foil and copper braid helps reduce interference and improve resolution, color and brightness • Fully molded, 360° soldered HD15 connector •Long-lasting, corrosion resistant, gold plated barrel connectors with custom tooled strain reliefs •Color-coded connectors for easy identification Note: The video display with a "VGA" connector (HD15) needs to support component video (Y-Pr-Pb) in order to properly synchronize.

Order #	Length	(1-9)	(10-up)
24-9450	1½'	\$5.29	\$3.76
24-9451	3'	8.69	6.14
24-9452	6'	10.79	7.70
24-9453	12'	10.89	7.77
24-9454	25'	20.95	14.15
24-9455	50'	35.95	25.25
24-9456	75'	50.95	35.82
24-9457	100'	65.95	46.62
24-9458	150'	44.95	40.62

Stellar

SLV Series Component Video Cables (3 RCA to DVI-I)

The Stellar Labs Value Series Component Video Cables are uniquely designed to connect your component video outputs to the DVI-I (component RGB video, and $Y\!/Pb/Pr$ video) input on HDTVs, LCD projectors, and satellite TVs. Features: •Three analog 28AWG coax conductors are shielded with braided tinned copper to reduce EMI/RFI, and improve video resolution, color and brightness • Shielded DVI connector under-mold is 360° soldered to resist interference and improve signal transmission •Long-lasting, corrosion resistant, gold plated RCA connectors with custom tooled strain relief •Color-coded connectors for easy identification Note: The video display with a "DVI-I" connector (DVI-I) needs to support component video (Y-Pr-Pb) in order to properly synchronize.

Order #	Length	(1-9)	(10-up)
24-9460	3'	\$11.19	\$8.00
24-9461	6'	13.99	9.98
24-9462	12'	15.95	10.93
24-9463	25'	22.95	16.05



The Stellar Labs Value Series Component Video

SLV Series

Component

Video Cables

Cables deliver the signal integrity, superior resolution, and crisp, clear video image you expect from high quality HDTV receivers, progressive scan DVDs, and other high-definition sources. Their bonded, tangle-free construction and flexible PVC cable jacket reduce cable clutter and make cabling installations effortless. Features: • EMI/RFI shielded, low-loss, 750hm video coaxial wire helps reduce interference and noise, and accurately separate the component color signal (Y-Pr-Pb) for better resolution and greatly improved color saturation •Long-lasting, corrosion resistant, gold plated barrel connectors with fully over-molded, custom tooled strain reliefs •Color-coded connectors for easy identification

Order #	Length	(1-9)	(10-up)
24-9430	1½'	\$4.89	\$3.42
24-9431	3'	6.39	4.53
24-9432	6'	8.59	6.10
24-9433	12'	12.09	8.37
24-9434	25'	18.95	12.96
24-9435	50'	38.95	27.73
24-9436	75'	54.95	38.87
24-9437	100'	69.95	49.73
24-9438	150'	87.95	62.53



Stellar@Labs **SLP Series RCA to BNC** Component Video Cables

The Stellar Labs SLP Series



RCA to BNC Component Video Cables are precision engineered to provide superior picture quality and excellent signal integrity. SLP cables feature oxygen free coaxial copper

construction, tangle free bonded wires, gold plated, corrosion free split-lock ring RCA connectors, and sure-lock BNC connectors. The flexible, UL listed cables feature a 7.0mm out diameter, dual EMI/RFI shielding technology, and a thick polyethylene dielectric to precisely transport the red, blue and green component video signal. Limited lifetime warranty.

Order #	Length	(1-10)	(11-50)	(51-up)
24-8902	6'	\$29.95	\$28.41	\$26.66
24-8903	9'	34.95	25.31	23.73
24-8904	12'	37.95	27.22	25.51



Stellar <u>Labs</u> **SLP Series**

Component Video Cables The Stellar Labs SLP Series

Component Video Cables are precision engineered to provide superior picture quality and excellent signal integrity. SLP cables feature oxygen free coaxial

copper construction, tangle free bonded wires, and gold plated, corrosion free split-lock ring RCA connectors. The flexible, UL listed cables feature a 7.0mm outer diameter, dual EMI/RFI shielding technology, and a thick polyethylene dielectric to precisely transport the red, blue and green component video signal. Limited lifetime warranty.

Order #	Length	(1-10)	(11-50)	(51-up)
24-8891	3'	\$52.95	\$37.49	\$33.48
24-8892	6'	55.95	37.79	33.74
24-8893	9'	72.95	45.37	40.51
24-8894	12'	69.95	42.98	38.39
24-8895	25'	94.95	54.93	45.86
24-8896	50'	149.00	121.43	75.80
24-8897	75'	153.00	95.43	85.20
24-8898	100'	208.00	118.72	106.00
24-8899	150'	281 00	165 05	147 38



SLP Series BNC Component Video Cables The Stellar Labs SLP Series BNC Component Video Cables make connecting your equipment a snap. These cables are specifically designed with sure-lock BNC

connectors and feature dual EMI/RFI shielding technology, which covers the thick polyethylene dielectric and OFC conductors. The red, blue and green component video signal is precisely transported on the flexible, UL listed cables that feature a 7.0mm outer diameter to reduce attenuation, and improve impedance. Limited lifetime warranty.

Order #	Length	(1-10)	(10-50)	(51-up)
24-8912	6'	\$29.95	\$26.85	\$26.27
24-8913	9'	34.95	29.15	27.32
24-8914	12'	36.95	31.13	29.19
24-8915	25'	42.95	36.61	34.32
24-8916	50'	60.95	52.23	48.96
24-8917	75'	74.95	65.10	61.04
24-8918	100'	89.95	79.62	74.63
24-8919	150'	119.00	107.39	100.68





Component Video Patch Cables

Component Video Cables

Component video cables made from RG-59U coaxial cable. Color coded strain reliefs for quick identification (red/green/blue)

		-		-					
Order #	Length	(ea.)	(2-4)	(5-up)	Order #	Length	(ea.)	(2-4)	
Gold Plated					Nickel Plat	ed			
24-4570	6'	\$17.95	\$16.29	\$15.45	24-4540	3'	\$9.09	\$8.80	
24-4575	10'	24.95	21.67	20.86	24-4545	6'	14.49	12.81	
24-4580	15'	30.95	27.32	24.70	24-4550	10'	21.95	18.90	
24-4585	25'	49.95	45.54	41.94	24-4555	15'	20.95	19.42	
					24-4560	25'	33.95	30.86	

Stellar Labs SLV Series **Component Video and Stereo Audio Cables**

e company

Section 1

The Stellar Labs Value Series Component Video and Stereo Audio Cables deliver the signal integrity, superior resolution, and crisp, clear video image you expect from high quality HDTV progressive scan DVDs, and other high-definition sources. Their bonded, tangle-free construction and flexible PVC cable jacket reduce cable clutter and make cabling installations effortless. Features: • EMI/RFI shielded, low-loss, 750hm video coaxial wire helps reduce interference and accurately separate the component color signal (Y-Pr-Pb) for better resolution and greatly improved color saturation •Oxygen-free copper wires produce crisp, clear audio signal transfer •Long-lasting, corrosion resistant, gold plated barrel connectors with fully over-molded, custom tooled strain reliefs •Color-coded connectors for easy identification.

Order #	Length	(1-9)	(10-up)
24-9440	1½'	\$8.95	\$4.46
24-9441	3'	11.69	8.32
24-9442	6'	12.95	8.06
24-9443	12'	24.95	17.51
24-9444	25'	30.95	21.61
24-9445	50'	40.95	28.56

Stellar () Labs HDMI Male/Male

DVI and **HDMI Cables**

HDMI enables true high-definition audio/video content for consumers. It combines high-definition video and multi-channel audio in a single digital interface to provide crystal-clear digital quality over a single cable. One cable for audio and video

dramatically simplifies home theater system installation and eliminates the cable mess behind entertainment system components. HDMI is fully backward compatible with PCs and displays incorporating DVI. HDMI systems will automatically configure to display content in the most effective format. Take advantage of the best quality available by connecting your HDMI equipment with cable by Stellar Labs HDMI

certifie	d ca	ab	le.

Order #	Length	(1-4)	Order #	Length	(1-4)
HDMI ma	le/male		HDMI ma	le to DVI-	D male
24-9600	1½'	\$35.95	24-9635	1½'	\$36.95
24-9605	3'	42.95	24-9640	3'	42.95
24-9610	6'	67.95	24-9645	6'	67.95
24-9615	10'	85.95	24-9650	10'	69.95
24-9620	15'	114.00	24-9655	15'	114.00
24-9625	25'	189.00	24-9660	25'	189.00
24-9630	50'	296.00	24-9665	50'	296.00
HDMI ma	le/male				
CL2 rated	l in-wall				
24-9626	25'	219.00			
24-9631	50'	316.00			
					DCT 20



Audio and Video Patch Cables

HDMI Adaptors

Designed to meet rigid and demanding HDMI compliant standards, these adaptors are ideal for connecting high



definition set top boxes to components with HDMI inputs. HDMI to DVI adaptors are 100% backward compatible with DVI (Note: DVI does not pass audio signal). Features: 24-karat gold-plated connectors, multi-layer shielding to reduce EMI/RFI, crystal-clear digital quality and simplified interconnect installation.

Order #	Description	(1-9)	(10-up)
24-9345	HDMI male to DVI female adaptor	\$19.95	\$12.39
24-9350	HDMI female to DVI male adaptor	19.95	12.39



Stellar<u>©Labs</u> SLP Series Composite Video and Stereo Audio Cables

The Stellar Labs SLP Series Composite Video and Stereo Audio Cables make connecting your

equipment a snap. The cables provide superior picture quality and excellent signal integrity for an unforgettable audio/video

experience. SLP cables feature oxygen free coaxial copper construction, tangle free bonded wires, and gold plated split-lock RCA connectors. The flexible, UL listed cables have a 7.0mm outer diameter, plus dual EMI/RFI shielding technology, and a thick polyethylene dielectric to significantly reduce attenuation, and improve impedance. Limited life-time warranty.

Order #	Length	(1-10)	(11-50)	(51-up)
24-8882	6'	\$55.95	\$36.97	\$30.92
24-8883	9'	66.95	37.43	33.44
24-8884	12'	69.95	34.42	30.74
24-8885	25'	103.00	51.73	46.19

Stellar CLabs **SLV Series** Composite Video and Stereo Audio Cables



The Stellar Labs Value Series Composite Video and Stereo Audio Cables are high quality interconnect assemblies that provide excellent picture quality and signal integrity. Their bonded, tangle-free construction and flexible PVC cable jacket reduces cable clutter and make cabling installations effortless. Features: • EMI/RFI shielded, low-loss, 750hm video coaxial wire helps reduce interference and noise, and improve resolution, color and brightness •Long-lasting, corrosion resistant, gold plated barrel connectors with fully over-molded, custom tooled strain reliefs •Color-coded connectors for easy identification

Order #	Length	(1-9)	(10-up)
24-9420	1½'	\$5.59	\$3.94
24-9421	3'	6.99	4.93
24-9422	6'	7.39	5.23
24-9423	12'	11.09	7.70
24-9424	25'	18.95	12.96
24-9425	50'	25.95	17.46

Stereo VCR Patch Cables

 Used for dubbing on stereo VCRs Triple cable with shielded RG-59U coaxial cable for video •RCA male connectors



Order #	Length	(1-9)	(10-up)
Gold Plated			
24-4650	1'	\$4.29	\$3.91
24-4655	2'	7.79	7.31
32-960	3'	6.39	5.52
32-965	6'	7.19	5.66
32-4535	10'	8.59	7.00
24-5320	25'	21.95	18.94
24-5325	50'	36.95	32.46
Nickel Plate	d		
24-4640	1'	5.29	3.35
24-4645	2'	4.39	3.65
32-4670	3'	4.19	3.92
32-4675	6'	4.99	4.39
32-4680	10'	7.09	6.65
24-5335	25'	19.95	17.39
24-5340	50'	27.95	24.30

Bulk Audio Video Dubbing Cables

Save money by purchasing your audio/video cables in bulk. These cables are available 20 per package for home theater installation or use to give away when



doing service calls. Three conductors, one video and two audio. Color coded for quick identification.

Order #	Length	Price per Cable	(pkg.)
24-2485	3'	\$3.20	\$63.95
24-2490	6'	3.30	65.95
24-2495	10'	3.75	74.95

Conductor RCA to RCA Patch Cables

• Four color-coded RCA plugs to four color-coded RCA plugs •Ideal for interconnection of tape deck play and



record •Cables molded together for neater appearance $\bullet 7'$ length

Order #	Plating	(ea.)	(2-4)	(5-up)
24-700	Nickel	\$17.95	\$13.13	\$11.59
24-1105	Gold	16.95	13.87	12.44







Audio and Video Patch Cables



MCM S-Video Stereo A/V Cables

Useful when connecting a DVD, DSS or S-VHS VCR to a television. Triple cable construction with S-video cable and two RCA audio cables.

Order #	Length	((1-9)	(10-up)
Gold				
24-6285	1'	\$	7.39	\$6.94
24-6290	2'		9.89	9.42
24-6295	3'	1	2.89	12.42
24-6300	6'	1	8.95	15.69
24-6305	10'	1	9.95	16.41
24-6310	15'	2	4.95	21.25
24-6315	25'	2	5.95	23.64
24-6320	50'	4	3.95	39.66
Order #	Length	(ea.)	(2-4)	(5-up)
Order # Nickel	Length	(ea.)	(2-4)	(5-up)
	Length 1'	(ea.) \$5.99	(2-4) \$5.36	(5-up) \$5.19
Nickel	<u> </u>	· /	()	(1)
Nickel 24-6325	1'	\$5.99	\$5.36	\$5.19
Nickel 24-6325 24-6330	1' 2'	\$5.99 8.99	\$5.36 8.49	\$5.19 8.32
Nickel 24-6325 24-6330 24-6335	1' 2' 3'	\$5.99 8.99 9.79	\$5.36 8.49 9.35	\$5.19 8.32 9.21
Nickel 24-6325 24-6330 24-6335 24-6340 24-6345 24-6350	1' 2' 3' 6' 10' 15'	\$5.99 8.99 9.79 10.59	\$5.36 8.49 9.35 10.36	\$5.19 8.32 9.21 10.12
Nickel 24-6325 24-6330 24-6335 24-6340 24-6345	1' 2' 3' 6' 10'	\$5.99 8.99 9.79 10.59 17.95	\$5.36 8.49 9.35 10.36 16.65	\$5.19 8.32 9.21 10.12 15.81

Mono VCR Patch Cables

 Used for dubbing on stereo VCRs • Dual RCA cable with shielded RG-59U coaxial cable for video • RCA male connectors

non maio	connectors		
Order #	Length	(1-9)	(10-up)
Gold Plated			
32-980	3'	\$7.09	\$6.25
32-985	6'	10.19	8.99
Order #	Length	(ea.)	(2-4)
Nickel Plate	b		
32-4655	3'	\$4.89	\$4.50
32-4660	6'	4 89	4 41

Mono to Stereo A/V Patch Cables

Connect a standard television or VCR to your home theater system. Also useful for dubbing from mono to stereo VCRs.

Order #	Length	(1-9)	(10-up)
24-4615	2'	\$6.09	\$5.60
24-2440	3'	6.29	5.29
24-2445	6'	8.79	7.79
24-2450	12'	11.49	10.16



SONY

Mono to Stereo Audio/Video Patch Cable

•Dual RCA male plugs to three RCA male plugs



SONY **Stereo VCR**

Patch Cables

•Three RCA male

• Three RCA is plugs to three male plugs			1 Comment
Order #	Length	(1-3)	(4-up)
VMC-810S	3'3"	\$5.99	\$5.65
VMC-820S	6'6"	7.99	7.49
VMC-830S	9'8"	9,99	9.77



Stellar Labs SLV Series S-Video and Stereo Audio (3.5mm to Dual RCA) Cables

The Stellar Labs Value Series S-Video and Stereo Audio Cables are perfect for connecting your audio/video sources (MP3, DVD, and XMTM or Sirrius[™] satellite radio players) to TVs, home theater projectors, or A/V receivers. The unique 3.5mm to dual RCA stereo audio cable design is incorporated into the bonded, tangle-free construction to help facilitate flexibility and compatibility among audio interconnects while reducing cable clutter. The long-lasting, corrosion resistant, gold plated barrel connectors are designed with custom tooled strain reliefs engineered to improve durability and reliability. Features: • EMI/RFI shielded, low-loss, dual conductor 750hm coax S-video wire to deliver high-resolution video images •Dual 26AWG shielded audio wires to protect against noise and distortion •Color-coded red and white RCA audio connectors •Male 4 pin DIN S-video to male

RCA composite video

Order #	Length	(1-9)	(10-up)
24-9400	1½'	\$5.69	\$4.02
24-9401	3'	7.09	5.04
24-9402	6'	8.89	6.35
24-9403	12'	11.49	8.22
24-9404	25'	17.95	12.08
24-9405	50'	25.95	18.32

Stellar©<u>Labs</u> **SLV Series S-Video Plus Stereo Audio Cables**

Value Series S-Video Plus Stereo Audio Cables are perfect for connecting your



audio/video sources (VCRs, DVD players, satellite receivers) to TVs, home theater projectors, or A/V receivers. Their bonded, tangle-free construction and flexible PVC cable jacket reduces cable clutter and make cabling interconnections effortless. The long-lasting, corrosion-resistant, gold plated barrel connectors are designed with custom tooled strain reliefs engineered to improve durability and reliability. Features: • EMI/RFI shielded, low-loss, dual conductor 750hm coax S-video wire to deliver high-resolution video images •Dual 26AWG shielded audio cables protect against noise and distortion ·Color-coded red and white RCA audio connectors.

Order #	Length	(1-9)	(10-up)
24-9380	1½'	\$4.89	\$3.46
24-9381	3'	6.09	4.30
24-9382	6'	8.89	6.35
24-9383	12'	9.89	7.05
24-9384	25'	14.49	10.36
24-9385	50'	23.95	16.25

SONY Mono VCR Patch Cable

VMC-730M


• Dual male RCA plugs to dual male RCA plugs

9'8'

Dual male non plugs to dual male non plugs						
Order #	Length	(1-3)	(4-up)			
VMC-710M	3'3"	\$5.79	\$5.66			
VMC-720M	6'6"	6.99	6.85			

DIN Plug to RCA Cable

•5 pin DIN plug to four RCA connectors •Connects tape decks and receivers with 5 pin DIN to equipment with standard RCA connectors •5' length Order # (ea.) 24-600 \$3.74



\$3.16

\$3.43

Wire and Cable



SLP Series S-Video and Stereo Audio Cables The Stellar Labs SLP Series S-Video and Stereo Audio Cables are precision engineered to provide superior luminance and chrominance S-video signal transmission and precise twisted pair, balanced audio performance. SLP cables feature oxygen free coaxial copper construction, tangle free bonded wires, gold plated corrosion free shielded S-video connectors, and secure, split-lock ring RCA connectors. The flexible, UL listed cables feature a 7.0mm outer diameter, dual EMI/RFI shielding technology, and a thick polyethylene dielectric to significantly reduce attenuation, and improve impedance. Limited life-time warranty

Order #	Length	(1-10)	(11-50)	(51-up)
24-8832	6'	\$26.95	\$22.73	\$21.31
24-8833	9'	29.95	23.14	21.69
24-8834	12'	31.95	24.02	22.52
24-8835	25'	35.95	29.50	27.65

Stellar abs SLP Series Composite/S-Video and Stereo Audio Cables

Now you can be prepared for either composite or S-video connections with only one cable! The Stellar Labs Professional Composite/S-Video and Stereo Audio Cables feature a unique tangle free bonded wire interconnect design, and gold plated, corrosion free, shielded metal connectors that make a perfect connection every time. The cables are precision engineered to provide superior luminance and chrominance S-video signal transmission, excellent composite video translation, and precise twisted pair balanced audio performance. SLP cables feature oxygen free coaxial copper construction, UL listed wire, and a limited lifetime warranty.

Order #	Length	(1-10)	(11-50)	(51-up)
24-8842	6'	\$29.95	\$24.29	\$22.77
24-8843	9'	31.95	26.26	24.62
24-8844	12'	33.95	28.16	26.40
24-8845	25'	36.95	30.78	28.85



Composite Video and Stereo Audio Cables

The Stellar Labs SLP Series S-Video and 3.5mm Audio to Composite Video and Stereo Audio Cables are ideal for PC to TV applications. Convert the analog audio and video signal from your PC or Notebook to a format that can be displayed or recorded to your TV/VCR. The cables are precision engineered to provide superior luminance and chrominance S-video signal transmission, excellent composite video translation, and precise twisted pair balanced audio performance. SLP cables feature oxygen free coaxial copper construction, UL listed wire and a limited lifetime warranty

Order #	Length	(1-10)	(11-50)	(51-up)
24-8862	6'	\$26.95	\$21.31	\$19.97
24-8863	9'	27.95	22.84	21.42
24-8864	12'	30.95	24.46	22.92
24-8865	25'	35.95	28.69	26.90
NET 30 Terms	Contraction Comis	NOVUS	MasterCard	VISA
1-800	Order To - 543-4		ax 800-765-696	0 29



The Stellar Labs



Section 1

Stellar©<u>Labs</u> **SLV Series S-Video Plus Toslink Audio Cables**

Get high quality S-video

and digital sound from

your advanced gaming



systems, DVD, S-VHS, or Dolby Digital[®]/DTS[®] integrated systems. The Stellar Labs Value Series S-video plus tosLink audio cables combine high performance fiber optic digital audio with crisp, clear S-video images in a bonded, tangle-free construction that reduces cable clutter and makes cabling interconnections effortless.

Order #	Length	(1-9)	(10-up)
24-9540	1½'	\$10.69	\$7.61
24-9541	3'	13.69	9.80
24-9542	6'	17.95	11.99
24-9543	9'	21.95	15.25
24-9544	12'	32.95	22.84



Audio and Video Patch Cables

Stellar)

SLV Series Component Video plus Toslink Audio Cables

The Stellar Labs Value Series toslink



audio/component video cables deliver the crisp, clear, superior video resolution you expect from component video together with the high signal transmission and low distortion characteristic of optical digital Toslink's natural sounding tuned spectral attenuation. Features: •EMI/RFI shielded, low-loss, 750hm video coaxial wire helps reduce interference and noise, and accurately separate the component color signal (Y-Pr-Pb) for better resolution and greatly improved color saturation •Bonded, tangle-free construction reduces cable clutter •Long-lasting, corrosion resistant, gold plated barrel connectors with fully over-molded, custom tooled strain reliefs • Precision-polished fiber optic connectors for optimum signal transfer and corrosion resistance . Color-coded connectors for easy identification.

Order #	Length	(1-9)	(10-up)
24-9550	1½'	\$12.19	\$8.72
24-9551	3'	15.95	10.88
24-9552	6'	20.95	14.13
24-9553	9'	24.95	17.55
24-9554	12'	33.95	24.14



MCM **Foslink Plus** S-Video Cable Molded audio/video

cable for video

installations with digital audio. S-video cable provides a high resolution video connection and the Toslink cable provides the optical audio connection needed for Dolby Digital sound.

Order #	Length	(ea.)	(2-4)
24-6135	3'	\$14.81	\$14.20
24-6140	6'	16.16	15.55
24-6145	10'	21.58	20.97
24-6150	15'	26.99	26.38
24-6155	25'	36.45	35.10



Toslink Plus Video Cable

audio/video cable for video installations with digital audio. RG-59 video cable provides a low loss video connection and the Toslink cable provides the optical audio connection needed for Dolby Digital sound.


Order #	Length	(ea.)	(2-4)
24-6110	3'	\$13.51	\$12.83
24-6115	6'	14.81	14.20
24-6120	10'	20.23	19.62
24-6125	15'	25.64	25.03
24-6130	25'	33.75	32.40

Stellar<u>© Labs</u> **SLV Series Stereo Audio Cables**

The Stellar Labs Value Series Stereo Audio Cables are high

quality directional analog stereo interconnects ideally suited for capturing the depth and detail in your favorite music or home theater presentations. The dual conductor 90% spiral-wrapped cable helps protect against noise and distortion and produces rich, defined bass tones, warm midranges, and crisp clear highs. Specifications: • Color-coded connectors •Dual RCA Male plugs to dual RCA plugs.

Order #	Length	(1-9)	(10-up)
24-9510	1½'	\$4.19	\$2.86
24-9511	3'	5.79	4.06
24-9512	6'	6.09	4.29
24-9513	12'	8.59	6.09
24-9514	25'	9.79	6.76
24-9515	50'	17.95	12.13
24-9516	75'	22.95	16.05
24-9517	100'	33.95	23.57
24-9518	150'	44.95	32.00





Audio Patch Cables



Stellar <mark>© Labs</mark> SLP Series Stereo Audio Cables

RCA to RCA **Stereo Cables**

•High-quality molded construction • Dual RCA plugs •Color coded red and gray

	R	1
ea)	(2-4)	(5-un)

Order #	Length	(ea.)	(2-4)	(5-up)
Gold Plate	d			
24-4620	1'	\$5.29	\$4.74	\$3.10
24-4625	2'	5.49	4.95	4.38
24-760	3'	5.79	4.60	4.09
24-765	6'	6.49	5.48	4.80
24-768	12'	8.79	7.40	6.42
24-769	20'	8.89	6.63	6.40
Nickel Plat	ed			
24-4600	1'	3.19	2.65	2.60
24-4605	2'	2.79	2.43	2.17
24-090	3'	5.29	4.79	2.96
24-100	6'	4.29	3.64	3.29
24-103	10'	5.89	5.19	4.72
24-5345	15'	7.39	6.77	6.26
24-104	20'	8.59	7.38	6.89
24-1470	25'	7.79	7.15	6.33
24-1475	50'	12.39	11.61	10.81

Dual RCA Extension Cable •Two RCA plugs to two RCA jacks • Extends length of patch cables •Molded strain relief •Color coded red and gray •6' length

Mark .	/
2	Tille
4	
4	1 and 1

Order #	(ea.)	(2-4)	(5-up)
24-595	\$8.09	\$7.32	\$6.64

SONY **Stereo Patch Cables** •Dual male RCA to dual male RCA

male RCA			
Order #	Length	(1-3)	(4-up)
RK-C310	3'3"	\$2.99	\$2.77
RK-C320	6'6"	3.79	3.49
RK-C330	9'8"	4.39	4.11

The Stellar Labs SLP Series Stereo Audio Cables provide excellent signal

integrity for an unforgettable audio experience. SLP stereo audio cables feature twisted pair, oxygen free coaxial copper construction, tangle free bonded

wires, and gold plated, split-lock, stereo audio RCA connectors. The flexible, UL listed cables have a 7.0mm outer diameter, plus dual EMI/RFI shielding technology, and a thick polyethylene dielectric to precisely transport superior audio quality, and maintain excellent balanced audio integrity. Limited life-time warranty.

Order #	Length	(1-10)	(11-50)	(51-up)
24-8941	3'	\$24.95	\$23.77	\$21.21
24-8942	6'	40.95	26.64	23.78
24-8943	9'	49.95	24.34	21.63
24-8944	12'	52.95	25.75	22.99
24-8945	25'	55.95	34.60	30.91
24-8946	50'	71.95	58.87	43.52
24-8947	75'	84.95	56.34	50.29
24-8948	100'	101.00	68.80	61.43
24-8949	150'	144.00	96.15	85.84

Bulk Stereo Patch Cables

Save money by purchasing your audio cables in bulk. These cables are available 20 per



package for home and automotive audio installation or use to give away when doing service calls. Two conductors, color coded for quick identification.

Order #	Length	Price per Cable	(pkg.)
24-2500	3'	\$1.55	\$30.95
24-2505	6'	1.75	34.95
24-2510	10'	2.50	49.95

Audio Patch Cables

MCM Audio Patch Cables

These audio patch cables are made from shielded cable with 22AWG center conductor and 3.0mm outer diamter. Use



these cables in any audio application including home theater and mobile audio.

Order #	Length	(ea.)	(2-4)	(5-up)
Gold				
24-7115	1'	\$5.79	\$5.17	\$4.74
24-7120	2'	5.79	5.42	5.04
24-7125	3'	8.69	8.16	7.67
24-7130	6'	9.89	9.42	8.76
24-7135	10'	12.59	11.97	11.48
24-7140	15'	15.95	14.65	14.16
24-7145	25'	17.95	16.80	15.74
Nickel				
24-7080	1'	4.59	4.15	3.74
24-7085	2'	6.39	5.63	5.16
24-7090	3'	5.39	4.95	4.59
24-7095	6'	8.19	7.86	7.37
24-7100	10'	8.29	7.86	7.51
24-7105	15'	14.95	13.62	12.96
24-7110	25'	16.95	15.49	14.86




RCA Piggyback **Patch Cables**

•RCA patch cable with two RCA plugs on one end and combination RCA plug/jack on other end •Allows

connection of two audio/video components to one input





A. 10' RCA to RCA Plug

•24 gauge, stranded wire •Molded plugs

Order #	(ea.)	(2-4)	(5-up)
24-300	\$4.29	\$3.79	\$2.96

B. 8' RCA to Tinned Wire

•24 gauge, stranded wire •RCA plug one end, stripped and tinned on the other end

Order #	(ea.)
28-580	\$1.19

3.5mm to RCA Female

Use for connecting a 3.5mm line outr or other input. 12 Order #

24-4590

24-4595

put to an amplifi RCA type line 2" in length.	er	0	P
Description	(ea.)	(2-4)	(5-up
Stereo	\$6.59	\$4.46	\$3.79
Mono	4.39	3.70	2.89



SLP Series **Digital Coaxial Audio Cables**

The Stellar Labs SLP Series Digital Coaxial Audio Cables are precision engineered digital coaxial interconnects ideal for DVD players, satellite reveivers/TiVo®, Dolby Digital

Surround Sound components, and high performance DTS. The oxygen free coaxial copper construction incorporates noise canceling technology which reduces bit error, and maintains the ideal data path to send up to six channels of surround sound audio from a single cable. The flexible, UL listed cable has a 7.0mm out diameter, plus dual EMI/RFI shielding technology, and a thick polyethylene dielectric to significantly reduce attenuation, and improve impedance. Limited lifetime warranty.

Order #	Length	(1-10)	(11-50)	(51-up)
24-8970	1.5'	\$7.59	\$5.97	\$5.60
24-8971	3'	8.09	6.21	5.81
24-8972	6'	8.89	6.80	6.39
24-8973	9'	9.49	7.39	6.93
24-8974	12'	10.79	8.06	7.56
24-8975	25'	11.39	9.19	8.61



Designed for subwoofer and mono-audio applications, the Stellar Labs SLP Series Single Channel RCA Cables are the ideal

interconnect for transporting single channel audio. SLP audio cables feature twisted pair, oxygen free coaxial copper construction and gold plated, split-lock, audio RCA connectors. The flexible, UL listed cables have a 7.0mm outer diameter, plus dual EMI/RFI shielding technology, and a thick polyethylene dielectric to reduce attenuation and precisely transport superior audio quality. Limited

	0			
Order #	Length	(1-10)	(11-50)	(51-up)
24-8961	3'	\$8.69	\$6.90	\$6.47
24-8962	6'	9.39	7.47	7.00
24-8963	9'	10.69	8.14	7.63
24-8964	12'	11.89	8.74	8.20
24-8965	25'	11.09	9.16	8.59
24-8966	50'	15.95	13.12	12.29
24-8967	75'	21.95	17.50	16.41
24-8968	100'	30.95	25.04	23.48
24-8969	150'	41.95	34.85	32.67

RCA "Y" Adaptor Cables

•Divides a RCA input in two outputs	to		
Order #	(1-4)	(5-9)	(10-up)
RCA Jack to T	NO RCA Plugs	s (shown)	
24-770	\$5.69	\$4.63	\$3.99
RCA Plug to T	vo RCA Jacks	S	
24-650	5.29	4.35	3.57

Switchcraft[®] Phone Y-Adaptor

(RCA Type)

• Flexible Y-adaptor phone plug to two phone jacks •Mfr. #330F1

Order # 101-050

SONY Audio Cable

• Dual RCA plugs to stereo 3.5mm mini plug with attenuator

 Connects Hi-Fi components to stereo mini jack of stereo cassette recorder for recording •4' 9" length

(1-9)

\$10.50

(10-up)

\$8.76

Order #	Descripton	(1-3)	(4-up)
RK-G128	W/attenuator	\$5.99	\$5.65
RK-G129	W/O attenuator	5.99	5.65



SLV Series 3.5mm to Dual RCA Stereo Cables

Perfect for connecting audio sources (iPod, MP3, DVD, PC, and XMTM or SiriusTM satellite radio players) to an amplifier or home theater system, the Stellar Labs Value Series 3.5mm to dual RCA stereo cables feature bonded wires and tangle-free construction to help facilitate flexibility and compatibility among audio interconnects while reducing cable clutter. The long-lasting, corrosion resistant, gold plated barrel connectors are designed with custom tooled strain reliefs engineered to improve durability and reliability. Specifications: • Color-coded connectors •3.5mm male plug to dual RCA male plugs.

Order #	Length	(1-9)	(10-up)
24-9490	1½'	\$3.19	\$2.13
24-9491	3'	4.19	2.85
24-9492	6'	4.29	3.19
24-9493	12'	4.99	3.47
24-9494	25'	7.39	5.23

Stellar O <u>Labs</u>

SLV Series Analog Audio "Y" Splitting Cables Stellar Labs Value



Series Analog Audio "Y" Splitting Cables connect a single audio source to two devices, or split a mono audio signal for connection to a stereo input. Constructed of corrosion resistant copper conductors and precision gold-plated connectors, these splitting cables are ideal for delivering stereo audio to mono devices, like older TVs and VCRs, or creating another set of stereo inputs on your receiver using two splitting cables.

Order #	Length	(1-9)	(10-up)	
Male plug to	dual female jacks			
24-9470	1½'	\$3.69	\$2.52	
24-9471	3'	3.79	2.55	
24-9472	6'	4.49	3.16	
24-9473	12'	5.99	4.21	
24-9474	25'	8.89	6.35	
Female jack to dual male plugs				
24-9480	1½'	3.69	2.52	
24-9481	3'	4.29	3.01	
24-9482	6'	4.49	3.16	
24-9483	12'	5.99	4.21	
24-9484	25'	8.89	6.35	

Stellar CLabs **SLV Series Sinale**

Channel Audio Cables

Stellar Labs Value Series single channel audio cables are ideal for connecting your home theater



receiver, satellite receiver, or any mono-audio single channel audio source to your subwoofer, or mono-audio installation. The dual conductor 90%spiral-wrapped cable helps protect against noise and distortion and produces rich, defined bass tones. Specifications: • Color-coded connectors. Single RCA male plug on both ends

• Single noA male plug on both enus.				
Order #	Length	(1-9)	(10-up)	
24-9500	1½'	\$3.59	\$2.43	
24-9501	3'	4.09	2.89	
24-9502	6'	5.49	3.88	
24-9503	12'	6.89	4.85	
24-9504	25'	13.99	10.01	
24-9505	50'	21.95	15.02	
24-9506	75'	27.95	19.46	
24-9507	100'	35.95	25.30	





Stellar<u>© Labs</u> SLP Series Single Channel

time v	varranty.	1	1	
ler #	Length	(1-10)	(11-50)	(51-up)
8961	3'	\$8.69	\$6.90	\$6.47
8962	6'	9.39	7.47	7.00
8963	9'	10.69	8.14	7.63
8964	12'	11.89	8.74	8.20
8965	25'	11.09	9.16	8.59
8966	50'	15.95	13.12	12.29
8967	75'	21.95	17.50	16.41



0

Section 1

Stellar<u>© _{Labs</u></u>}

SLP Series 3.5mm Stereo Audio Cables

The Stellar Labs SLP Series 3.5mm Stereo Audio Cables carry both left and right audio channels over a single cable creating a clean tangle free connection. Now you can easily playback MP3 and mini disk portable audio players on your 3.5mm input sound stereo equipment. The gold plated, corrosion free 3.5mm connectors are designed to mate securely, and the flexible, UL listed cable features a thick 7.0mm outer diameter, twisted-pair OFC construction, dual EMI/RFI wire shielding, and a thick polyethylene dielectric to significantly reduce attenuation, an improve impedance. Limited lifetime warranty.

Order #	Length	(1-10)	(11-50)	(51-up)
24-8980	1.5'	\$8.69	\$6.74	\$6.33
24-8981	3'	9.39	7.06	6.62
24-8982	6'	9.99	7.62	7.14
24-8983	9'	10.69	8.29	7.77
24-8984	12'	11.99	8.88	8.32
24-8985	25'	12.09	9.85	9.23
24-8986	50'	19.95	14.71	13.80
24-8987	75'	25.95	19.98	18.74
24-8988	100'	31.95	25.20	23.62
24-8989	150'	41.95	35.07	32.88

Stellar Labs SLV Series 3.5mm Stereo Audio Cables

Now you can easily adapt your audio connections to meet your application needs. Use the Stellar Labs 3.5mm Stereo Audio Cables to adapt from


one connection to another, or extend an existing cable connection. Low-loss, spiral wrapped dual conductor provides excellent protection against EMI/RFI. Fully molded connectors provide excellent strain relief.

Order #	Length	(1-9)	(10-up)
3.5mm male to	male		
24-9520	1½'	\$2.69	\$1.86
24-9521	3'	3.49	2.99
24-9522	6'	4.39	3.06
24-9523	12'	4.89	3.44
24-9524	25'	7.19	5.07
24-9525	50'	11.29	8.02
24-9526	75'	14.79	10.58
24-9527	100'	19.95	13.83
3.5mm male to	female		
24-9530	1½'	2.99	2.09
24-9531	3'	4.09	2.85
24-9532	6'	4.49	3.14
24-9533	12'	4.99	3.49
24-9534	25'	6.49	4.58
24-9535	50'	11.89	8.48
24-9536	75'	16.95	11.70
24-9537	100'	21.95	14.82

RCA to RCA "Y" Cable

•Lenght 1.2m Order # (1-9)(10-up) AV00251 \$1.55 \$1.52









Stellar <u>Labs</u>

SLP Series 3.5mm to RCA **Stereo Audio Cables** The Stellar Labs SLP Series 3.5mm to RCA Stereo Audio

Cables feature a tangle-free bonded wire construction that

easily facilitates converting from 3.5mm stereo audio components like MP3, or mobile DVD players, to RCA stereo audio receivers, or speakers. Gold plated, corrosion free 3.5mm and RCA split-ring connectors are designed to mate securely, and the flexible, UL listed cables feature a thick 7.0mm outer diameter, twisted-pair OFC construction, dual EMI/RFI wire shielding, and a thick polyethylene dielectric to significantly reduce attenuation, an improve impedance. Limited life-time warranty.

Order #	Length	(1-10)	(11-50)	(51-up)
24-8990	1.5'	\$9.29	\$7.83	\$7.27
24-8991	3'	10.59	9.18	8.61
24-8992	6'	11.79	9.71	9.10
24-8993	9'	13.09	10.36	9.72
24-8994	12'	14.29	11.05	10.36
24-8995	25'	20.95	17.57	13.63
24-8996	50'	22.95	16.49	15.46
24-8997	75'	25.95	21.69	20.34
24-8998	100'	31.95	26.90	25.21
24-8999	150'	44.95	-	-

3.5mm to RCA ΡΙι Ochle

Plug Cables			
•3.5mm n to RCA pl	nono plug		
Order #	Length	(ea.)	(2-4)
24-665	3'	\$2.59	\$1.93
24-670	6'	4.59	3.86
In			/M

СМ 3.5mm Extension Cables 3.5mm audio

(5-up)

\$1.69

3.19

extension cables for use with personal audio equipment. Molded strain reliefs. Nickel plated plugs. Available stereo or monaural.

Order #	Length	(ea.)	(2-4)	(5-up)
Stereo				
24-6230	3'	\$3.19	\$2.64	\$2.31
24-6235	6'	4.29	3.90	3.58
24-1050	12'	5.69	5.05	4.76
24-6240	20'	8.29	7.90	7.58
24-6245	25'	11.39	10.74	10.58
Monaural				
24-6250	3'	2.59	2.17	1.89
24-6255	6'	4.09	3.64	3.28
24-1045	12'	4.99	4.13	3.83
24-6260	20'	6.69	6.29	6.02
24-6265	25'	9.79	9.37	9.08

MCM

3.5mm Patch Cables 3.5mm audio patch cables for use with personal audio equipment. Molded strain reliefs. Nickel plated plugs.

Available stereo or monaural.				
Order #	Length	(ea.)	(2-4)	(5-up)
Stereo				
24-6170	1'	\$3.19	\$2.82	\$2.51
24-6175	3'	5.39	4.81	3.31
24-815	6'	5.89	4.78	4.12
24-6180	10'	7.19	6.87	6.54
24-6185	15'	7.69	7.31	7.17
24-6190	20'	10.79	10.17	10.02
24-6195	25'	16.95	13.54	13.38
Monaural				
24-6200	1'	3.29	2.75	2.57
24-6205	3'	4.99	3.14	2.97
24-810	6'	5.19	4.34	3.60
24-6210	10'	6.69	6.18	5.88
24-6215	15'	9.99	8.27	7.93
24-6220	20'	10.89	10.15	9.84
24-6225	25'	10.49	10.06	9.81

Audio Patch Cables

3.5mm "Y" Cable 3.5mm male plug to two 3.5mm female jacks.

Description

Mono

Stereo

Order #

24-2595

1

24-2596

1-9)	(10-49)	(50-up)
5 /0	\$4.83	\$4.25

4.74

4.15

¹ /4" Plug to Two	3.5mm Jacks	Dual	Headphone
------------------------------	-------------	------	-----------

5.29

Adaptor Ca	ibles 🛛 🚬	III.	
•Allows two headphones	to be	-	
plugged into)		
one jack			
Order #	(ea.)	(2-4)	(5-up)
24-685	\$4.39	\$3.87	\$3.45

1/4" "Y" Adaptor Cable

•¼" stereo p to two ¼" ste jacks •Allow simultaneou of two pairs	ereo vs	from one jack	
Order #	(ea.)	(2-4)	(5-up)
24-690	\$7.79	\$6.30	\$5.63


	gs Cable lug to two RCA vith amplifiers		1
Order #	(ea.)	(2-4)	(5-up)
24-1040	\$6.59	\$4.33	\$4.00

RCA Plug t Mono Plug •Adapts ½" : RCA plug •6	Cable mono plug to a		
Order #	(ea.)	(2-4)	(5-up)
24-675	\$5.59	\$4.63	\$4.13

•¼" stereo p	Adaptor Cable lug to 3.5mm 3' coiled length;		
Order #	(ea.)	(2-4)	(5-up)
24-695	\$10.79	\$9.19	\$9.03

	Cable nstruction relief •3' coiled extended length		
Order #	(ea.)	(2-4)	(5-up)
24-080	\$8.99	\$8.21	\$7.46

3.5mm Plug to 6.3mm Stereo Jack



Audio Patch Cables



correct for tolerance errors in optical cable jacks and result in a more accurate signal transfer. 10mm outer diameter cable provides added protection to the fiber optics.

Order #	Description	(ea.)	(2-4)	(5-up)
24-6405	1 meter	\$10.80	\$9.73	\$8.34
24-4420	2 meter	13.38	12.05	10.73
24-6410	3 meter	16.16	14.81	13.51
24-4425	5 meter	20.14	18.68	17.36
24-4430	10 meter	30 75	30.30	27 57

MCM Spring-Loaded

Toslink Cables Spring-loaded plugs

correct for tolerance errors in optical cable jacks and result in a more accurate signal transfer.

Order #	Description	(ea.)	(2-4)	(5-up)
24-6415	1 meter	\$8.10	\$7.64	\$6.95
24-4405	2 meter	10.29	9.09	7.61
24-6420	3 meter	13.09	11.78	10.31
24-4410	5 meter	15.69	15.03	13.54
24-4415	10 meter	25.95	25.44	24.12

MCM

Rotary Fiber Optic Switches

These optical selector switches allow you to expand the input/outputs of your optical devices. No need to swap your expensive optical cables between multiple recorders and players. The construction of these units provides optimum light signal transfer for

high quality recording and playback.

Order # Descintion

	Desciption	(ca.)
24-6580	Toslink	\$26.99
24-6585	3.5mm	26.99

Digital Signal Convertors

Converts digital optical toslink cables to coaxial (RF) and vice versa. These adaptors are perfect for

OUT

situations when your equipment does not have the input

or output you would prefer. Power: 9VDC 250mA. adaptor sold separately (#28-2790)

Order #	Input	Output	(ea.)	(2-4)
24-4440	Coaxial	Toslink	\$19.99	\$19.29
24-4445	Toslink	Coaxial	19.99	19.29
24-4451	Adaptor		3 00	_

Analog to **Digital Signal** Convertors

Turn analog audio signal to a digital audio data stream for use with amplifiers with

digital inputs. Accepts stereo audio input via two RCA type connectors and gives digital output via coaxial (RF) and toslink. Power: 6VDC 250mA,

adaptor so	ld separately (#24	1-4451)	
Order #	Description	(ea.)	(2-4)
24-4435	Convertor	\$60.32	\$59.27
24-4451	Adaptor	3.99	-

MCM Neon Spring-Loaded **Toslink Cables**

Add distinction to the digital audio system with neon cables. Spring-loaded plugs correct for tolerance errors in optical cable jacks and result in a more accurate signal transfer.

J				
Order #	Length	(ea.)	(2-4)	(5-up)
Red				
24-6425	1 meter	\$8.99	\$7.64	\$6.95
24-4360	2 meter	9.99	8.31	6.95
24-6430	3 meter	12.95	11.12	9.73
24-4365	5 meter	14.95	13.78	12.41
Blue				
24-6445	1 meter	8.99	7.64	6.95
24-4390	2 meter	9.99	8.31	6.95
24-6450	3 meter	12.95	10.80	9.45
24-4395	5 meter	14.95	13.78	12.41
24-4400	10 meter	26.95	26.20	24.84
Green				
24-4375	2 meter	9.99	8.31	7.50
24-6440	3 meter	12.95	10.80	9.45
24-4380	5 meter	14.95	13.38	12.05
24-4385	10 meter	26.95	26.20	24.84

Fiber-Optic Audio Cable

Popular replacement audio cable assembly for many different brands. Optical connector on both ends. 3" length.

Order #	Length	(ea.)	(2-4)	(5-up)
24-1451	3'	\$5.29	\$4.77	\$4.09
24-2585	6'	6.59	6.13	5.45
24-2590	9'	7.99	7.50	6.82

Panasonic Fiber Optic Cables

• Designed for digital AV equipment •Optical fiber cable transmits signals digitally • P.M.M.A. fiber achieves wide-band and high purity transmission

		51 0	
Order #	Length	(1-3)	(4-up)
STD. to STD.			
P-RP-CA201	3'3"	\$17.99	\$15.50
P-RP-CA202	6'6"	22.50	19.50
P-RP-CA2030A	9'8"	26.96	-
Mini to STD.			
P-RP-CA2110A	3'3"	17.96	-
Mini to Mini			

17 96

3'3'

MCM **Glass Digital Optical** Cables

P-RP-CA2210A

For the true

audio purist nothing but high purity glass optical cables will do. These glass optical cables offer optimal frequency response and broader bandwidth through the use of high purity glass fiber cores and sophisticated mirror polishing techniques. The superior performance of these interconnects deliver audiophile quality sound in high-end home music systems.

Order #	Length	(ea.)	(2-4)	(5-up)
24-6485	1 meter	\$26.99	\$25.64	\$24.28
24-6490	2 meter	33.75	31.97	29.19
24-6495	3 meter	40.51	38.93	36.15

MCM **Toslink Couplers** Toslink cour extend the of digital

Toslink couplers to	
extend the length	
of digital	
optical cables.	

Order #	Description	(ea.)	(2-4)	(5-up)
24-4320	Black	\$2.77	\$2.59	\$2.45
24-4325	Gold	2.77	2.51	2.38
24-4330	Nickel	2.77	2.59	2.45



e company

Section 1



Stellar<u>© Labs</u> **SLP Series**

TosLink Optical Digital Audio Cables The Stellar Labs SLP Series TosLink Optical

Digital Audio Cables provide superior audio quality and excellent signal integrity. The optical fiber provides the ideal media for transporting your audio data with no degradation to digital audio signal quality. The spring-loaded metal connectors make a perfect, high-speed contact every time. The optical fiber is immune from EMI/RFI interference, making it the connection of choice suitable for all environments. The cable has a thick, but flexible 6.00mm outer diameter for quality that you can hear

and feel. Available in lengths up to 25'.

		· ·		
Order #	Length	(1-10)	(11-50)	(51-up)
24-8951	3'	\$19.95	\$18.40	\$15.20
24-8952	6'	28.95	22.45	18.50
24-8953	9'	35.95	24.53	21.90
24-8954	12'	40.95	21.69	19.36
24-8955	25'	53.95	33.50	29.90

Stellar Labs **SLV Series Toslink Optical Digital Audio Cables**

The Stellar Labs Value Series Toslink Optical Digital Audio Cables are precision engineered to maximize digital audio



signal transfer by minimizing interference and distortion and delivering pure optical bit stream data. The result is superior sound quality and accurate transfer of digital audio source signals from DVD, surround sound receivers, digital cable boxes, and advanced gaming systems. High-quality precision-polished fiber optic connectors optimize signal transfer, while the PVC jacket adds flexibility and durability for years of listening enjoyment.

Order #	Length	(1-9)	(10-up)
24-9560	1½'	\$5.59	\$3.95
24-9561	3'	6.99	4.82
24-9562	6'	8.39	5.97
24-9563	9'	11.19	7.96
24-9564	12'	13 00	9 97

Toslink Signal Splitters

These digital optical splitters allow the use of one digital audio device for two inputs. Connect a minidisc player or MP3 player to your computer and stereo receiver simultaneously. Order # (ea.) (2-4)

\$9.99

24-4455



MCN Toslink A Convert b Toslink an mini optic simply sna adaptor on mate with	daptors etween d 3.5mm al plugs, ap the	o device.			A	
Order #	Descriptio	n	(ea.)	(2-4)	(5-up)	
24-6570	Toslink to	3.5mm	\$4.04	\$3.91	\$3.78	I
24-6575	3.5mm to	Toslink	4.04	3.91	3.78	
NET 30 Terms	fictions and the form	DUCO	wus	asterCard	VISA	

Order Toll Free Fax 1-800-543-4330 1-800-765-6960 33

\$9.57



Audio Patch Cables

Section 1

STLE Eight Channel XLR Snake Cable

High quality, highly flexible cable provides eight balanced audio channels, terminated with XLR male connectors at one end, female on the other. Length listed below is overall, including break out.

Order #	Length	(1-3)	(4-up)
555-8605	10'	\$32.95	\$29.50
555-8606	20'	46.19	41.59



PYLE Eight Channel XLR to %" Snake Cable

High-quality, highly flexible cable provides eight unbalanced audio channels, terminated with two conductor ¼" male connectors at one end, and XLR male on the other. Length listed below is overall, including break out.



Lef Eight Channel XLR to $\frac{1}{3}$ Snake Cable

High quality, highly flexible cable provides eight unbalanced audio channels, terminated with two conductor ¼" male connectors at one end, and XLR female on the other. Length listed below is overall, including break out.

Order #	Length	(1-3)	(4-up)
555-8600	10'	\$27.39	\$24.50
555-8601	20'	39.95	35.99



1 YEAR LIMITED WARRANTY audio-technica Premium Quality Microphone Cables

Constructed with two conductor, shielded, vinyl jacketed, broadcast type cable, with hand soldered connectors.

Order #	Length	(1–3)	(4–up)
XLR Male to	Female Cable		
35-1340	10'	\$16.95	\$15.40
35-1341	20'	17.95	16.68
35-1342	25'	19.95	17.60
35-1343	30'	21.95	18.43
35-1344	50'	24.95	21.25
35-1345	100'	42.95	33.22
XLR Male to	1/4" Cable		
35-1346	10'	10.39	9.47



NEW! NEW! NEW! NEW! NEW! NEW!



PYLE[•] Eight Channel RCA Phono Snake Cable High-quality, highly flexible cable provides eight

High-quality, highly liexible cable provides eight unbalanced audio channels, terminated with male RCA connectors at each end. Length listed below is overall, including break out.

Order #	Length	(1-3)	(4-up)
555-8625	10'	\$19.95	\$17.95
555-8626	20'	31.19	27.95



PYLE[®] Eight Channel ¼" to RCA Phono Snake Cable

High-quality, highly flexible cable provides eight unbalanced audio channels, terminated with two conductor ¼" male connectors at one end and male RCA connectors at the other. Length listed below is overall, including break out.

Order #	Length	(1-3)	(4-up)
555-8620	10'	\$19.95	\$17.95
555-8621	20'	31.19	27.95



High quality, highly flexible cable provides eight unbalanced audio channels, terminated with two conductor %" male connectors at each end. Length listed below is overall, including break out.

Order #	Length	(1-3)	(4-up)
555-8610	10'	\$19.95	\$17.95
555-8611	20'	31.19	27.95

Banana Speaker Cables

Speaker cables for use when connecting home theater equipment with banana type connectors for speaker terminals.



Available in 16 and 18AWG with gold plated banana connectors. Sold one cable per package.

Order #	Length	(ea.)	(2-4)	(5-up)
18 Gauge				
24-2600	6'	\$4.06	\$3.91	\$3.48
24-2605	10'	5.42	5.30	4.89
24-2610	25'	8.14	7.46	6.77
16 Gauge				
24-2625	6'	5.42	5.30	3.48
24-2630	10'	6.77	6.51	6.10
24-2635	25'	9.36	8.94	8.26
24-2640	50'	13.38	12.70	12.04



Balanced TRS Snake Cable

High-quality, highly flexible cable provides eight balanced audio channels, terminated with male three conductor $\chi^{\prime\prime}$ connectors at each end. Length listed below is overall, including break out.

Order #	Length	(1-3)	(4-up)
555-8630	10'	\$23.59	\$21.25
555-8631	20'	37.39	33.50

PYLE

Stereo Patch Cable High-quality, highly flexible cable provides L/R unbalanced audio channels,

terminated with male RCA phono connectors on one end, and female XLR at the other. 5' length.

Order #	(1-3)	(4-up)
555-8635	\$7,99	\$7 19



visit www.mcminone.com for our complete offering

20 Channel Cable Snakes

This is the perfect cable snake when high quality and low cost are important. All 20 channels (16 send and four return) utilize XLR type



connectors, harnessed to a single heavy duty, highly flexible multi-conductor cable. The input box features durable steel construction and includes 20 chassis mounted XLR connectors, 16 female sends and four male returns. The output side features a steel cable strain relief to prevent excess stress to the connectors, both on the snake and your mixing console. •Box dimensions: 3" (H) x 7" (W) x $11\frac{y_2}{y_2}$ (D) •Cable diameter: 1"

Order #	Length	(1-2)	(3-up)
555-1530	100'	\$259.00	\$232.38
555-1535	150'	397.00	339.08

Audio Patch Cables



Designed for rugged pro sound and stage use, these heavy-duty cables are available in 12 and 16 gauge configurations, to accommodate the most stringent circumstances. Various connector configurations allow compatibility with most amplifiers and speakers in use today.
 Connectors: •Twist-lock: Compatible with popular Speakon[™] connectors •¼" phone plug: Molded insulator on 16 gauge cable, hand soldered metal barrel on 12 gauge cable •Banana: Pairs set at standard spacing

Fig. Order #	Connectors	Length	(1–3)	(4–up)
12 Gauge				
A 24-8645	Twist lock to twist lock	25'	\$29.63	\$25.94
A 24-8646	Twist lock to twist lock	50'	46.79	40.96
B 24-8650	Twist lock to ¼" male	25'	26.51	23.21
B 24-8651	Twist lock to ¼" male	50'	43.67	38.23
C 24-8655	¼" male to ¼" male	25'	22.87	19.44
C 24-8656	1/4" male to 1/4" male	50'	39.51	34.59
C 24-8657	¼" male to ¼" male	100'	73.83	64.63
16 Gauge				
A 24-8660	Twist lock to twist lock	25'	19.75	17.28
A 24-8661	Twist lock to twist lock	50'	28.07	24.58
B 24-8665	Twist lock to ¼" male	25'	15.59	13.65
B 24-8666	Twist lock to ¼" male	50'	23.91	20.93
C 24-8680	1/4" male to 1/4" male	12'	6.75	5.90
C 24-8681	1/4" male to 1/4" male	25'	10.91	9.55
C 24-8682	1/4" male to 1/4" male	50'	18.71	16.38
C 24-8683	1/4" male to 1/4" male	100'	32.23	27.39
D 24-8685	¼" male to banana	12'	7.27	6.37
D 24-8686	1/4" male to banana	25'	11.43	9.71
D 24-8687	¼" male to banana	50'	19.23	16.83
D 24-8688	¼" male to banana	100'	32.75	28.66

XLR to ¼" Patch Cables



8

an unbalanced input on an equalizer or amplifier.

Order #	Length	(1-9)	(10-up)
24-2350	2'	\$4.00	\$3.85
24-2355	3'	4.41	4.25
24-2360	6'	4.94	4.81
24-2365	10'	6.01	5.92
24-2370	15'	7.06	6.77
24-2375	25'	11.29	10.81

XLR to RCA Patch Cables

XLR male to RCA male
patch cable for use in
professional audio. Ideal
for use when connecting
an unbalanced source to a

ale	
ı	ALL COMPANY
leal	
ing	
o to a	balanced input on an

an unbalanced source to a balanced input on an equalizer or amplifier.

Order #	Length	(1-9)	(10-up)
24-2380	2'	\$5.49	\$5.29
24-2385	3'	5.99	5.83
24-2390	6'	6.99	6.20
24-2395	10'	7.99	7.64
24-2400	15'	8.99	8.25
24-2405	25'	9.89	9.68

XLR Male to Female Patch Cables

XLR male to XLR female patch cable for use in professional audio when connecting from a microphone, mixer, equalizer



Ordor #	Longth	(1.0)	(10
source to an	amplifier or	other balanced in	put.
microphone	, mıxer, equa	lizer or other bala	nced

Order #	Length	(1-9)	(10-up)
24-2290	2'	\$6.01	\$5.92
24-2295	3'	6.42	6.15
24-2300	6'	8.09	7.78
24-2305	10'	9.29	8.94
24-2310	15'	9.49	9.23
24-2315	25'	13.09	12.61

XLR to RCA Patch Cables

XLR female to RCA male patch cable for use in professional audio. Ideal for use when connecting a balanced source to an unbalanced



input on an equalizer or amplifier.

Order #	Length	(1-9)	(10-up)
24-2410	2'	\$4.67	\$4.41
24-2415	3'	5.15	4.75
24-2420	6'	5.34	5.08
24-2425	10'	6.42	6.19
24-2430	15'	7.46	7.27
24-2435	25'	9.49	9.10

Electric Guitar Cable

•¼" mono plug to ¼" right angle mono plug •Coiled cord extends to 20'

Order #	(ea.)	(2-4)	(5-up)
24-660	\$8.89	\$7.54	\$6.55
Quality			

Quality Guitar/Instrument Cables

Utilizes ultra flexible Matte, PVC

jacketing material

for added durability. Nickel plated ¼" connector offers years of superior performance and maximum value. **Specifications:** •Conductors 24 gauge (high-z) •Shield: 65% coverage pure copper •O.D.: 0.242" Capacitance: 25pf/ft. @ 1KHz •Resistance 230hm per 1000' @ 20°C

Order #	Length	(1-3)	(4-up)
555-1570	3'	\$4.60	\$3.89
555-1575	5'	5.01	4.32
555-1580	10'	6.04	5.16
555-1585	15'	7.06	6.43
555-1595	25'	8.98	8.11

WHOTIZON Music Incorporated

Speaker Cable

Using bare copper stranded, twisted pair conductors each individually jacketed with an overall jacket added for durability. Standard with $\frac{1}{2}$ " connectors.

Order #	Length	AWG	(1-3)	(4-up)
555-1779	5'	16	\$11.22	\$10.55
555-1780	10'	16	12.25	10.51
555-1785	15'	16	13.07	11.43
555-1790	25'	16	14.70	12.74
555-1795	50'	16	20.45	18.48
555-1800	15'	14	20.24	18.31
555-1805	25'	14	23.52	20.00
555-1810	50'	14	26.21	24.08
555-1820	25'	12	28.03	24.49
555-1825	50'	12	40.25	38.23



Honzon Music Incorporated Commercial Speaker Cable

Heavy gauge, commercial grade speaker cable features individually jacketed 12AWG conductors, and a highly flexible, durable outer PVC jacket. One end includes a hand soldered, all metal % plug, the other, a pair of heavy–duty banana plugs. Each banana plug is attached separately, allowing compatibility with any binding post arrangement, regardless of spacing.

8					
Order #	Length	(1-3)	(4-up)		
555-1835	15'	\$22.95	\$20.08		
555-1840	25'	29.95	26.26		
555-1845	50'	44 95	39 40		

Wire and Cable





A set of six color coded patch cables (yellow, red, green, blue, black and white) to make identification much easier. $\frac{1}{2}$ " monaural, right angled plugs on each end. Ideal for PA and music sound systems.

Order #	Length	(1-9)	(10-up)
24-5395	1'	\$12.89	\$12.11
24-5400	6'	13.99	12.86

%" to %" Pa Stereo and r patch cables microphone staging app	s for guitar, , sound and		4
Order #	Length	(1-9)	(10-
Monaural			
24-2230	2'	\$3.39	\$2.
24-2235	3'	4.29	3.
24-2240	6'	6.09	4.
24-2245	10'	5.49	4.
04.0050	1.51	6.00	

24-2250	15'	6.99	6.26
24-2255	25'	7.59	7.03
Stereo			
24-2260	2'	7.09	6.18
24-2265	3'	7.59	6.87
24-2270	6'	7.89	7.23
24-2275	10'	9.59	9.01
24-2280	15'	8.29	7.99
24-2285	25'	10.09	9.39

SONY. Audio Plug Adaptor



plug into stereo phone plug •Used to connect headphones with stereo mini plug to headphone jack of stereo amplifier

Order #	(1-3)	(4-up)
PC-234S	\$3.99	\$3.08

Music Incorporated Zip Speaker Cable



Using two parallel conductors, one silver, the other copper. Using rugged PVC jacketed material and standard nickel plated ¼" connectors.

Order #	Length	AWG	(1-3)	(4-up)
555-1750	3'	18	\$6.49	\$5.96
555-1755	10'	18	7.06	6.43
555-1760	25'	18	9.08	7.58
555-1765	50'	18	13.27	11.35
555-1770	100'	18	18.40	16.00
555-1772	25'	16	11.53	11.22
555-1773	50'	16	18.19	15.78
555-1774	25'	14	17.27	14.91





Specifications: •Conductors: (1) 18 gauge (High-Z) •Shield: 95% coverage pure copper •Jacket: Matte PVC •O.D.: 0.226" •Capacitance: 45pf./ft. @ 1KHz •Resistance: 5.60hm @ 20°C/1000' •Limited lifetime manufacturers warranty.

manaraovar	ers marraney.		
Order #	Length	(1-3)	(4-up)
555-1630	10'	\$24.04	\$21.27
555-1635	15'	25.37	22.43
555-1640	20'	27.21	25.29
555-1650	30'	30.60	28.03





Section 1

EPS Series Adhesive Lined Shrink Tubina

Tubing is made of flame retardant flexible polyolefin and lined with a special layer of thermoplastic adhesive. When heated, the outer layer rapidly shrinks forcing the melted adhesive to flow and cover the connection. This forms a watertight seal that is far superior to standard heat shrink and tape coverings. Applications include automotive, truck and marine environments. Available in 2:1 and 3:1 ratios. Packaged in 6" pieces, black color.

EPS-200 2:1 Shrink Ratio

Order #	Size	Quantity	(pkg.)
108-830	1½"	4 pcs.	\$16.95
108-831	1"	8 pcs.	16.95
108-832	1/2"	14 pcs.	16.95
108-833	1/4"	20 pcs.	16.95
108-834	1/8"	28 pcs.	16.95
108-835	3/16"	24 pcs.	16.95
108-836	3/4"	12 pcs.	16.95
108-837	3%"	20 pcs.	16.95

EPS-300 3:1 Shrink Ratio

Order #	Size	Quantity	(pkg.)
108-840	1½"	4 pcs.	\$27.95
108-841	1"	8 pcs.	25.95
108-842	1/2"	14 pcs.	25.95
108-843	1/4"	20 pcs.	21.95
108-846	3/"	12 pcs.	25.95
108-847	3/8"	20 pcs.	27.95

Heat Shrink Tubing

Spools General purpose, flexible

polyolefin tubing in 100' rolls is perfect for electrical insulation over connectors, splices and wire bundling.

2:1 shrink ratio. Black in color. UL listed.

Order #	Size (I.D.)	(1-9 spools)	(10 spools-up)
108-3300	1/8"	\$23.95	\$21.56
108-3301	3/16"	27.95	25.16
108-3302	1⁄4"	34.95	31.46
108-3303	3⁄8"	37.95	34.16
108-330/	1Z"	/2 05	33.85

KORALLY

Colored Heat Shrink

•Package contains 6"

pieces of polyolefin heat shrink tubing in 11 assorted colors •Ideal for wire identification and coding •11 pieces per package

iuentinua	identification and counig - 11 pieces per package					
Order # Size		(1-9 pkgs.)	(10 pkgsup)			
95-750	3⁄8"	\$6.10	\$5.71			
95-755	1/4"	5.64	5.02			
95-760	3⁄16"	4.61	3.96			
95-765	1/8"	4.05	3.43			
95-770	3∕32"	3.59	3.11			





Heat Shrink Tubing 4' Sections

High-quality polyolefin FP-301 series heat shrink tubing meets your most stringent electrical performance requirements. Dual wall tubing provides maximum environmental protection. 2:1 shrink ratio is ideal for cable splices and terminations, lightweight wire harness covering, wire marking, component packaging and fire resistant covering. Meets

MIL-I-23053/5 Class 1 and 2 and AMS 3636, AMS 3637 requirements. UL recognized and CSA certified at 600V 125°C. Each piece is 48" long.

Size I.D.	Black Order #	Blue Order #	Clear Order #	Red Order #	White Order #	Yellow Order #	(1-9 pkgs.)	(10 pkgsup)
1/16"	108-2805	108-2810	108-2815	-	-	108-2830	\$1.59	\$1.52
3/32"	108-2705	108-2710	108-2715	108-2720	-	-	1.59	1.53
1/8"	108-2605	108-2610	108-2615	108-2620	108-2625	108-2630	1.69	1.62
3⁄16"	108-2505	108-2510	108-2515	108-2520	108-2525	-	1.99	1.91
1/4"	108-2405	108-2410	108-2415	108-2420	108-2425	108-2430	2.29	2.19
3/8"	108-2305	-	108-2315	108-2320	108-2325	108-2330	2.99	2.86
1/2"	108-2205	108-2210	108-2215	108-2220	108-2225	-	3.39	3.24
3/1"	108-2105	-	-	-	-	-	3.63	3.11
1"	108-2005		108-2015	-	-	-	5.99	5.61



different sizes

Assorted color refills 108-3196

Order #

108-3195

108-3202

108-3197

108-3198

108-3199

Heat Shrink **Tubing Kits and Refill Packs** •Versatile assortment of 6" flexible polyolefin heat shrink

(ea.)

\$69 95

60.95

9.29

9.29

9.29

9.29

tubing (4' for #108-3206) with

a 2:1 shrink ratio •Available

colors or black •Assorted color kit contains a total of

133 pieces, in six different sizes and seven different

Assorted color kit

3/2" dia., 35 pcs.

¹⁄₆" dia., 28 pcs. ³∕₁₆" dia., 21 pcs.

1/4" dia., 21 pcs

colors: Black, red, white, yellow, blue, green and

Description

Black kit

clear •Black kit contains 102 pieces, in six

Tubing 4' Sections High quality polyolefine FP-3001 series heat in two different types: Assorted shrink tubing meets your



most stignent electrical performance requirements. Dual wall tubing provides maximum environments protection. 2:1 shrink ratio. Meets MIL-I-23053/5 Class1 and 2 and AMS 3636, AMS 3637 UL recognized and CSA certified at 600 V, 125°C. Each piece is 48" long. •Black color.

Order #	Size (I.D.)	Qty.	(1-9 pkgs)
108-1305	3⁄8"	12	\$22.95
108-1405	1/4"	12	22.95
108-1505	3/16"	25	36.95
108-1605	1/8"	25	31.95
108-1705	3⁄32"	25	29.95

KORALLY

4' Sections

·Polyolefin heat shrink in assorted colors

Size (I.D.)	Black Order #	Clear Order #	White Order #	Red Order #	Yellow Order #	Blue Order #	(1-9)	(10-up)
1/16"	-	95-055	95-105	95-155	95-205	95-250	\$1.63	\$1.36
3⁄32"	95-010	95-060	95-110	95-160	95-210	95-255	1.83	1.68
1/8"	95-015	95-065	95-115	95-165	95-212	95-260	1.94	1.78
3/16"	95-020	95-070	95-120	95-170	95-215	95-265	2.35	2.20
1/4"	95-025	95-075	95-125	95-175	95-220	95-270	2.86	2.73
3/8"	95-030	95-080	95-130	95-180	95-225	95-275	3.27	3.17
1/2"	95-035	95-085	95-135	95-185	95-230	95-280	3.58	3.47
3/4"	95-040	95-090	95-140	95-190	-	95-285	4.91	4.70
1"	95-045	95-095	-	95-195	-	95-290	6.75	6.43
1½"	95-050	95-100	-	-	-	95-295	11.88	10.65



KORALLY

Heat Shrink Spools

•Polyolefin heat shrink in assorted colors

1 Oryoletini neat sin nik in assorice colors									
Size (I.D.)	Spool Length	Black Order #	Clear Order #	White Order #	Red Order #	Yellow Order #	Blue Order #	(ea.)	
1/16"	70'	95-300	95-345	95-390	-	95-480	-	\$22.17	
3⁄32"	65'	95-305	95-350	95-395	-	-	95-530	22.50	
1/8"	60'	95-310	95-355	95-400	95-445		95-535	22.50	
3/16"	50'	95-315	95-360	95-405	95-450	95-495	95-540	22.50	
1/4"	40'	95-320	95-365	95-410	95-455	95-500	95-545	22.50	
3/"	35'	95-325	95-370	-	95-460	-	95-550	22.50	
1/2"	32'	95-330	95-375	95-420	95-465	-	95-555	22.50	
3/4"	24'	95-335	95-380	-	95-470	-	-	22.50	
1"	16'	95-340	95-385	-	-	-	-	22.50	





CORALLY Mini Heat Gun and Heat Shrink Tubina Kit

This kit includes a compact, lightweight heat gun and 60 pieces of heat shrink tubing. The mini heat gun is ideal for shrinking heat shrink tubing. Heat gun features: •Nozzle temperature to 1,000°F



•6' electrical cord with workbench storage loop •Uses standard 110V outlet •The general purpose heat shrink tubing shrinks to ½ of its original size •Includes a total of 60 pieces •Sizes include ¹/₈", ³/₁₆", 1/4", %" and 1/2"

		Price	per kit
Order #	Description	(1-3)	(4-up)
95-810	Mini heat gun and shrink tubing kit	\$39.95	\$38.06
95-815	Replacement heat shrink tubing kit only (60 pcs.)	9.95	9.77



•A fast and easy way to waterproof coax fittings •Wraps around fittings and can be molded to any shape •Works with vinyl and poly vinyl outer

covers •Stays flexible for years (1-9) (10-24)(25-49)\$3.49 \$3 16 \$2 95

ЮЯЛЦЧ

"Beans"

Order #

21-1140



and security applications •100 per bag •White Order # (1-9 bags) (10 bags-up) 95-670

ELKAY

Cable Glands Complete

cable glands with washer

and locknut suitable for use where a cable needs to pass through sealed enclosures or panels.

Fi	g.Order #		Thread & Pitch	Cable Size	(1-99)	(100-up)
А	CBGLM20/1	249	M20 x 1.5	4~7mm	\$1.14	\$1.03
В	CBGLM20/2	251	M20 x 1.5	7~10.5mm	1.14	1.06
С	CBGLM20/3	252	M20 x 1.5	8~13mm	1.14	1.06

KORALLY

Vinyl Grommet Assortment Pack



•Includes a total of 28 pieces •Assorted sizes: $\ensuremath{\rlap{\sc 12}}\xspace"$, $\ensuremath{\rlap{\sc 16}}\xspace"$ and $\ensuremath{\sc 8}\xspace"$ \bullet Black (10 pkgs.-up)

Order # 95-575

Order #

22-3064

KORALLY

Vinyl Grommet





Variety Pack • Includes a total of 26 pieces •Assorted sizes: %", %", %", %", %", %", %", 2%", %" and 1" •Black

Order #	(1-9 pkgs.)	(10 pkgsup)
95-580	\$3.02	\$2.59

Cable Staples

•Carbon steel, insulated. •Secures and protects NM IDEA sheathed cable, UF cable and TV lead wires •Sharp pointed legs will not split wood •500 pieces per box



\$20.15

Professional Quality **Heat Gun** •Heavy-duty heat gun for shrinking heat

shrink tubing •Versatility of two temperature ranges allows selection of 600° and 1000°F •Includes a heat dispersion nozzle \bullet Operates on 110VAC, 1200W Order # (1-4)

(5-9)(10-24)21-1915 \$44.9 \$43.1 \$36.96

CORALLY Flex Guard

Protect wire harnesses with Flex Guard wire loom. The unique convoluted design installs quickly over multiple wire strands through an easy opening seam. Made of flame retardant polyethylene. Flex Guard is ideal for car stereo installations or other wiring applications that require protection against temperature, weather and corrosive conditions. Available in gray. 50' length.

Order #	(I.D.)Size	(ea.)
95-705	1/4"	\$15.48
95-710	38"	20.05
95-715	1/2"	26.51
95-720	5/8"	29.67
95-725	3/4"	35.10

KORALLY Rally-Rap[®]

This spiral-cut wrap applies a strong grip on wire harnesses due to the torsional cut and memory properties of polyethylene plastic. Rally-Rap will retain its strength under repeated flexing over complex, long and continuous wire paths. Ideal for car stereo installations that require break out of multiple leads and resistance to ultraviolet rays. Available in black on a 100' spool.

Order #	Bundle Size	(ea.)
95-735	1/4 ^m	\$24.95
95-740	3/8"	29.95
95-745	1⁄2"	37.95



shrink tubing kit meets UL and Mil-Spec

standards •Shrinks to 50% of original diameter using heat application of 250°F •23 pieces of 6" (10-24 kits) (25-49 kits) (1-9 kits) Order #

\$8.39

KORALLY

Moisture-Proof Heat Shrink

21-1565



\$7.78

heat shrink tubing designed to insulate, seal and protect components and electrical splices from moisture and corrosion. Available in black 6" lengths.

Order #	Size	Qty. Per Pkg.	(1-9 pkgs.) ((10 pkgsup)
95-630	1⁄8"	14	\$10.20	\$9.45
95-635	3⁄13"	12	10.20	9.17
95-640	1/4"	10	10.20	9.45
95-645	3⁄6"	9	10.20	9.45
95-650	1⁄2"	8	10.20	9.45
95-655	3/"	5	10.20	9.45
95-660	1"	4	10.20	9.45
95-665	1½"	3	10.20	9.45

KORALLY

Heat Shrink Kit Refill •This kit features high quality ICO-Rally heat shrink products and saves you 11% off list prices •72



pieces of the most

Wire and Cable



popular heat shrink sizes and colors •6" length **Kit contains:**

Size Black Clear Red White Blue Yellow Green Refill

3/16"	6	4	4	3	3	2	2	95-675
1/4"	6	4	2	2	2	2	2	95-680
3%"	3	2	2	1	1	1	1	95-685
1/2"	2	2	1	1	1	1	1	95-690
3/4"	1	1	1	1	1	-	-	95-695
3/1"	1	1	1	-	-	-	-	95-700
#102	2-011							\$29.95(kit)

SPC TECHNOLOGY

Heat Shrink Tubing

•Excellent general purpose heat shrinkable tubing •Highly resistant to fungi and chemicals. Shrinks to



less than half of original diameter •Black •6" length

Order #	Quantity	Size	(1-9 pkgs.)	(10 pkgsup)
28-650	28	1/8"	\$7.16	\$6.85
28-651	24	3/16"	7.16	6.85
28-652	20	1/4"	7.16	6.85
28-655	14	1/2"	7.16	6.85
28-657	12	3/1	7.16	6.85

👁 Telecrafter Products

Clip Guns With increasing demands for high performance drops. the telecomunications industry is turning to Telecrafter Products for cable clips that can be relied upon to preserve the integrity of the signal. Both of



the clip guns produce flawless, right the first time drop cable installations. Cable is fastened quickly, accurately and permanently, with no chance of damage to the cable. Loading is easy. Each row contains 25 clips, no more fumbling with tools and loose, hard to control manual clips. Clips come 400 to a pack.

Order #	Mfr. #	Description	(ea.)
33-3985	RB-2	Single clip gun	\$52.79
33-3995	06ES	Single clips	27.52

Self Adhesive **Cable Clamps**



Durable nylon clips securely hold cable up to ¾" diameter. Ring

can be re-opened for easy removal and reinsertion of

cable. 50 per bag. Black.

Order #	I.D.	(1-4)	(5-9)	(10-up)
21-3652	1/4"	\$10.05	\$8.58	\$7.34
21-3656	1/2"	12.93	10.80	9.13
21-3660	3/"	16.77	14.43	12.20



For The Latest (box)



Section 1

HellermannTyton **Cable Clamps**

•Securely fastens loose wires •50 per bag						
Order #	Size	Color	(1-3 bags)	(4 bags-up)		
21-1515	1⁄4"	Natural	\$3.33	\$2.86		
21-2465	1/4"	Black	3.33	2.86		
21-1520	3/8"	Natural	3.54	3.31		
21-2470	3/8"	Black	3.54	3.31		
21-1525	1/2"	Natural	3.64	3.31		
21-2475	1/2"	Black	3.64	3.31		
21-1530	3⁄4"	Natural	4.73	4.40		
21-2480	3/"	Black	4.73	4.53		
21-1535	1"	Natural	5.69	4.97		
21-2485	1"	Black	5.69	4.97		

Nylon Cable Clamps

Standard screw mount clamp holds wire up to

1/2" diameter. Natural color. 50 per bag.

Order #	I.D.	Width	(1-4 bags)	(5-9 bags)	(10 bags-up)
21-3668	1⁄8"	3⁄8"	\$1.64	\$1.34	\$1.11
21-3672	1/4"	¹³ / ₃₂ "	1.83	1.44	1.22
21-3676	3⁄8"	1/2"	2.05	1.66	1.44
21-3680	1/2"	1/2"	2.63	2.25	1.91

Telecrafter Products

Flex Clips

Flex Clips are exceptionally strong, long lived clips that deliver holding power without utilizing rigid materials that damage cable installations.



Flexible, polyethylene wraps around the cable, adjusts to size, and clamps into place. The Flex Clip is pliable so it will not crimp the cable. Its unique design eliminates the ongoing stresses that shorten the lives of other clips. 100 per package.

Order #	Mfr. #	Description	(pkg.)	
33-4005	S4BK	Single flex clip	\$16.41	
33-4010	D4BK	Dual flex clip	16.41	

Telecrafter Products

Drywall Clips

Drywall clips provide a safe, damage-free attachment that is long lasting and secure. Assembly is easy; drill a $\frac{1}{4}$ " hole, place the clip over the

cable and push the clip into the wall. The profile of the drywall clip allows it to almost disappear. The drywall clip is suitable for most surfaces including wood and masonry. 100 per package.

Order #	Description	(pkg.)
33-6930	Black drywall clips	\$8.09
33-6935	White drywall clips	8.09

HellermannTyton Cable Tie Mounting Base

•Adhesive or screw mounting

•Insertion can be made from all four sides • Fits nylon ties up to 6.15mm (W) x 1.58mm (thick)

x 1.58mm	(tnick)			
Order #	Color	Quantity Per Pack	(1-3 pkgs.)	(4 pkgsup)
21-1460	White	100	\$16.95	\$15.02
21-2700	Black	100	16.95	15.02
21-2705	White	25	6.49	5.86



#21-1470 #21 #21-1480

HellermannTyton Masonry Cable Clips

•Masonry clips are a low cost, easy method for mounting telephone wire and CATV cable to cinderblock, masonry and concrete •50 per bag

Order #	Dimensions (W) x (H) x (D)	Cable Diameter (Max.)		Per Bag (4-up)
21-1470	.625" x .250" x .250)".188"(Phone)	\$16.95	\$15.23
21-1475	1.25" x .500" x .500	".500"(CATV)	27.93	26.55
21-1480	.875" x 500" x 500	" 500"(CATV)	30.41	28.54

Self Adhesive **Cable Tie Mounts**

Nylon tie mount base accepts standard cable ties up to 3/16 wide. Self adhesive backing attaches to any smooth surface. 100 per bag. Available in black or natural color.



#21-3686 #21-3690 Base

		Dimensio	ons Pri	ce Per Bag	J
Order #	Color	(mm)	(1-4)	(5-9)	(10-up)
21-3684	Natural	21 x 21	\$8.59	\$7.22	\$6.23
21-3686	Black	21 x 21	8.59	7.22	6.23
21-3688	Natural	28 x 28	12.95	11.02	9.48
21-3690	Black	28 x 28	12.95	11.02	9.48

Saddle Type Wire Tie Mount

Screw mounted nylon saddle anchor accepts all standard nylon wire ties. Ideal for applications where large cable must be secured and appearance is critical. 50 per bag. Natural color.

	Base Dimensions	Max. T Width		ce Per Ba	ag
Order #	(mm)	(mm)	(1-4)	(5-9)	(10 -up)
21-3662	19.0 x 09.5	3.4	\$1.96	\$1.57	\$1.34
21-3664	15.0 x 10.0	3.0	2.08	1.69	1.34
21-3666	23 0 x 16 0	60	2.73	2.25	2 02

Self-Adhesive Coated Aluminium Cable Clips

White matt polyester coated aluminium cable clips suitable for use in situations where the clip may be visible. Can also be used as a lightweight hook

fitting. •Arm size: 44.4 x 7.9mm •Base size: 25.4 x 25.4mm •100 per package

Order #	(1-9 pkgs.)	(10 pkgsup)
CBA-ACC07/PK	\$22.48	\$22.07

cables on a 2 x 4 framing compliance with article 300-4-(d) of the National Electrical Code. It organizes

28-6285



\$2.08

cable runs and aids in identification, putting an end to tangled wires and the potential heating that could occur when cables are held together tightly under a single fastener. Installation is easy with cables snapping in for a positive lock, simplifying compliance with the spacing requirements of the National Electric Code. 25 per pack.



HellermannTyton Cable Tie Masonry Mount

•Permanent method of attaching wire and cable to masonry surfaces • Masonry mounts simply tap into predrilled ¼" hole •Black • Fits nylon cable ties with up to 9.48mm (W) x 2.45mm (thick) •50 per bag



Order #	(1-3 bags)	(4 bags-up)
21-1465	\$16.95	\$15.23

SPC TECHNOLOGY **Cable Clamp** Assortment Kits •Cable clamps are

lightweight and chemical resistant • Ideal for cables and wire bundles •Secure quickly with a single nail or screw • Excellent shock resisting properties •Temperature range of -40°F



to 185°F • Each kit contains 175 pieces of varying widths •Includes 6 compartment storage case


Order #	Description	(kit)
28-6535	Plastic, screw mounted	\$15.32
28-6540	Nylon, screw mounted	15.32

300 Piece

Cable Tie Set	
•Contains	
150 4" cable ties	L
including 25 green,	
25 yellow, 25 black,	0
	sparent •Contains 150 8" cable
ties including 50 re	d, 50 blue, and 50 transparent
Order #	(set)
21-7565	\$7.63

HellermannTyton Identification Cable Ties

- Tie and identify cable in one operation
- •Natural color •4¼" length •100 per bag •18 lbs. tensile strength •¾" bundle size
- Priced per bag
- Order # (1-3)





Bulk Cable Ties

•Length: 8" •Width: 0.098" •Tensile strength: 250 lbs. •Color: Natural •Packaged 1,000 per box for large users

-	Price per box				
Order #	(1-3)	(4-9)	(10-up)		
21-7650	\$16.95	\$16.43	\$15.40		

SPC TECHNOLOGY

Wire Tie

Assortment Kit •Kit contains a total of 300 wire ties $\bullet Includes$ 50 each of TWT-3, TWT-4, TWT-5, TWT-8 twist type natural color ties; 50 each of beaded type ties in red, yellow, and blue colors; 50 each of nylon beaded type natural color ties Includes 6 compartment storage case

Order #	(kit)
28-6530	\$15.32





Cable Stackers Centers multiple



member, allowing simplified





quality automatic tensioning tools

comparable to those commonly found at twice the price. Ratcheting action tightens tie, to a tension preset on the tool handle, then automatically cuts

off excess tie length. Works with all nylon wire ties.				
Order #	Description	(1-3)	(4-up)	
21-3225	Plastic	\$14.95	\$12.20	
21-3230	Metal	27.79	22.43	

HellermannTyton Heavy-Duty Cable Ties

•50 per bag •120 lbs. tensile strength

			Bundle	Price	Per Bag
Order #	Length	Color	Size	(1-3)	(4-up)
21-1370	81/8"	Natural	2"	\$12.86	\$10.75
21-1375	8%	Black	2"	12.86	11.07
21-1380	11%"	Natural	3"	13.19	11.04
21-1385	11%"	Black	3"	13.19	11.04
21-1390	15¼"	Natural	4"	14.79	12.67
21-1395	15¼"	Black	4"	14.79	12.67

Interior Wall Cable Support

Designed for attaching to metal or wood studs, these supports securely hold up to six runs of Category



5 cable, plus one run of coaxial cable. May be mounted horizontally or vertically. Sold in bags of 100.

Order #	(1-3 bags)	(4 bags-up)
28-6380	\$29.95	\$26.96

Self-Nailing Safety Plate

RACC

Stamped steel plate is designed to protect wire runs in wood structures. Simply attach to the stud to protect wiring that passes through the stud from future nails, screws and drilling. Box of 100. Mfr. #2709.

Order # 502-2709

HUBBELL

Telecrafter Products

Cable Markers

Where versatility is most important, write on tags serve many needs. Used with the proper pen, these markers can highlight many wiring characteristics and

be a valuable aid to identification. 100 per package.



HellermannTyton Mounting **Cable Ties** Natural color (#21-7320 black) •100 per bag Tensile Bundle Per Bag Order # Mounting Length Strength Size (1-3) (4-up)

Natural						
21-1400	#4 screw	4¼"	18 lbs.	3⁄4"	\$7.49	\$6.64
21-1405	#8 screw	6¼"	30 lbs.	1¼"	7.69	6.80
21-1410	#10 screw	8½"	50 lbs.	1¾"	10.95	8.96
Black						
21-7320	#10 screw	8½"	50 lbs.	1¾"	10.95	8.96

Catamount[®] Releasable **Cable Ties** •Great for temporally



wrapping up cables for transportation or prototyping work •Available in black or natural colors • Tensile strength: 50 lbs. 100 per package

			Bund	le	
Order #	Color	Length	Size	(1-3 pkgs.)	(4 pkgsup)
21-4735	Black	5.9"	11/4"	\$7.41	\$6.86
21-4736	Black	7.8"	2"	8.06	7.63
21-4737	Black	11.75"	3"	12.67	11.74
21-4738	Natural	5.9"	1¼"	7.41	6.86
21-4739	Natural	7.8"	2"	8.06	7.63
21-4740	Natural	11.75"	3"	12.67	11.74

Neon Wire Tires

These wire ties have become popular among auto electronic installers and are used to dress-up professional auto sound installations. Use these ties anywhere to "brighten-up" the look of your installation. These come 100 per bag in 6%" lengths

motuntuti	instantation, these come too per sug in out tenguist					
Order #	Color	(1-9 bags)	(10 bags-up)			
95-605	Neon yellow	\$5.11	\$4.84			
95-585	Neon pink	5.11	4.84			
95-600	Neon orange	5.11	4.84			
95-590	Neon green	5.11	4.84			
95-595	Neon blue	5.11	4.84			

Cable Tie Assortment Pack

(box)

\$17.79

These cable ties secure



(pkg.)

(kit)

\$10.49

wire bundles and harness components quickly,

without slipping. The self-locking head, with heavy double teeth on the one-piece lock mechanism assures reliability. Ties are designed to meet a wide range of temperatures from -40°F~185°F. This assortment pack contains 100 of the most commonly used ties. Sizes include 4", 5", 7.5", and 11" in natural and black weather resistant colors.



1100 Piece Cable Tie Kit

•Contains 1100 of the most popular sizes of cable ties •Ideal for light duty applications •Each size is color coded for easy identification **Kit includes:** 300 each of sizes %" x 4", %" x 5"; 250 each of %" x 6"; 100 each of %" x 7"; 80 each of %" x 8"; 50 each of %" x 10"; and 20 each of 5/16" x 12".

Order # 22-7556

Order #

Wire and Cable



Section 1

HellermannTyton Standard Cable Ties

•100 per bag

Ouder #	Longil	Color	Tensile		e Price F	
Order #	Length	Color	Strength	Size	(1-3)	(4-up)
21-1320	4"	Natural	18 lbs.	3/4"	\$2.86	\$2.29
21-1325	4"	Black	18 lbs.	3⁄4"	3.07	2.50
21-1330	6"	Natural	30 lbs.	1¼"	4.19	3.55
21-1335	6"	Black	30 lbs.	1¼"	4.19	3.55
21-1340	8"	Natural	30 lbs.	2"	5.66	4.64
21-1345	8"	Black	30 lbs.	2"	5.66	4.64
21-1350	11¼"	Natural	30 lbs.	3"	9.74	8.51
21-1355	11¼"	Black	30 lbs.	3"	9.74	8.26
21-1360	14½"	Natural	30 lbs.	4"	9.85	8.51
21-1365	14½'	Black	30 lbs.	4"	9.85	8.51



Cable Ties

•100 per bag						
		Bundle		P	rice Per Ba	ag
Order #	Length	Color	Size	(1-9)	(10-49)	(50-up)
21-3552	4"	Black	3/4"	\$2.58	\$2.33	\$2.00
21-3562	4"	Natural	3⁄4"	2.58	2.33	2.00
21-3554	6"	Black	1¼"	3.34	3.11	2.55
21-3564	6"	Natural	1¼"	3.34	3.11	2.55
21-3556	8"	Black	2"	4.27	3.85	3.19
21-3566	8"	Natural	2"	4.27	3.85	3.19
21-3568	11¼"	Natural	3"	6.48	6.00	4.89
21-3560	14½"	Black	4"	7.28	6.72	5.50
21-3570	14%	Natural	4"	7.35	6.78	5.66

HellermannTyton **Bulk Cable Ties**

 Packaged 1,000 per box for

large use	rs				
0	Length	Tensile		rice per bo	
Order #	Color	Strength	(1-3)	(4-9)	(10-up)
21-7550	4" Natural	18 lbs	\$9.96	\$9.72	\$9.18
21-7552	4" Black	18 lbs.	9.96	9.72	9.18
21-7554	8" Natural	30 lbs.	20.95	20.50	19.42
21-7556	8" Natural	50 lbs.	23.05	21.58	19.42
21-7558	5.5" Natural	18 lbs.	17.80	17.25	16.17
21-7560	8" Black	40 lbs.	23.05	21.58	19.42

HellermannTyton

Cable Tie Kit

1-800-543

•Durable polypropylene kit contains 300 of the most popular sizes of cable ties •50 adhesive backed mounts and one Tytonwyster tool •Ideal for maintenance engineering prototyping, field repairs and construction sites



1-800-765-6960

39

Order #				(kit)
21-1540				\$55.69
NET 30 Terms	Contraction of Contraction	NAVUS	MasterCard	VISA



Section 1



FLEX(Wrap Nylon Braided Cable Wrap

Features: •Ideal for audio/video and computer systems for a professional look •Heavy duty hook and loop fasteners for frequent access to cables •Lightweight and flexible •UV resistant •High abrasion resistance • Cuts easily with a hot knife

(MCM #21-6815 iron and #21-6845 tip) •Operating temperature: -103°F~257°F • Must be cut with a hot knife to avoid unraveling •Available in 6' and 25' lengths Nominal

Order #	Diameter	Length	(1-3)	(4-up)
21-8306	3⁄4"	6'	\$16.95	\$15.95
21-8308	1¼"	6'	21.95	20.55
21-8310	2"	6'	21.95	21.10
21-8312	3/11	25'	49.95	47.95
21-8314	1¼"	25'	79.95	76.95
21-8316	2"	25'	84.95	81.95

RIP-TIE WrapStrap

•Sometimes it is not necessary to attach the cable wrap to the cable •Perfect for car installs or where the wiring might need to be rerouted or removed •Wrapstrap[™] is a single strip of double-sided hook and loop fastener that quickly and easily wraps around almost anything

• Cut to 1	engui • Diack		
Order #	Dimensions (W) x (L)	(1-2 pkgs.)	(3 pkgsup)
21-4757	½" x 10'	\$6.45	\$5.31
21-4759	1⁄8" x 75'	22 22	18 03

RIP,-TIE

CableWrap

• Fastest, easiest, and tidiest way to keep harnessed cords organized and coiled cables neat and ready for storage Specifically designed to eliminate the frustration, inconvenience and mess associated with older cable organization methods

 Attaches to any cable permanently, patented Velcro[®] and nylon tie design means they are reusable for 10.000 times • Available in different colors and lengths •Ten pieces per package

Order #	Dimensions (W) x (L)	Color	(1-2 pkgs.)	(3 pkgsup)
21-4745	1" x 6"	Black	\$25.78	\$21.00
21-4746	1" x 6"	Rainbow	25.78	21.00
21-4747	1" x 9"	Black	28.58	23.49





CLEAN (ST Clean Cut™ Fray Resistant Sleeving

Flexo Clean Cut is ideal for field installers and other situations where access to a hot knife is impossible. Simply cut with scissors for an easy, safe, and professional installation. **Features:** •Lightweight and flexible •UV resistant •Cuts easily with scissors •Increased braid density for fuller coverage •High abrasion resistance •Operating temperature: -103°F~257°F •Melting temperature: 446°F •Color: Black

Nominal Order # Diameter Lenath (1-3)(4-up) 21-8282 \$10.99 \$10.50 21-8284 25 11.99 11.53 1/ 14.10 21-8286 14.89 21-8288 1' 25 16.99 15.65 21-8290 19.95 18.49 21-8292 23.16 1½" 25 24.95 21-8294 100 44.95 44.24 21-8296 1/2" 100 46.95 44.79 21-8298 44.95 42.73 21-8300 1" 50' 36.95 34.49 21-8302 1% 50 42.95 41.15 21-8304 53.95 49.39 1% 50

RIP-TIE

CableCatch • Tidy way to organize cables against a surface Permanently adheres to desks and equipment racks Fast hook and loop



cable release • Easy change of equipment and cords •Available in different colors and lengths •Five pieces per package


	Dimensions			
Order #	(W) x (L)	Color	(1-2 pkgs.)	(3 pkgsup)
21-4748	1" x 2"	Black	\$14.79	\$11.96
21-4749	1" x 2"	Gray	14.79	11.61
21-4750	1" x 4"	Black	16.75	13.52
21-4751	1" x 4"	Gray	16.75	13.13

RIP_TIE. Lite™

• End the frustration of lost cable ties forever •Especially designed for places where industrial strength is not needed, perfect for where cables are rearranged less frequently •One piece design is based on the patented Rip-Tie® CableWrap and can be reused 300 times •Attaches to a single cable and stays in place

• Won't damage delicate cables • Available in different colors and lengths •Ten pieces per package Dimensions

	Dimensions			
Order #	(W) x (L)	Color	(1-2 pkgs.)	(3 pkgsup)
21-4752	½" x 5"	Black	\$7.94	\$6.54
21-4753	½" x 5"	Rainbow	7.94	6.54
21-4754	½" x 8"	Black	9.67	7.97
21-4755	½" x 8"	Rainbow	9.67	7.97
21-4756	½" x 12"	Black	13.45	11.07





F6's unique split, semi-rigid braided construction makes it the ideal solution for situations where ease of installation is of primary importance. The lateral split allows the tube to open up to accommodate a wide variety of bundling requirements, and the semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners (velcro, tape, etc.). Features: •Lightweight and flexible •Easy installation •Soft and quiet in high vibration uses •25% edge overlap •Cut and abrasion resistant •Can withstand temperatures of -103°F~257°F •Melting temperature: 446°F

Order #	Nominal Diameter	Length	(1-3)	(4-up)
21-8318	1/2"	75'	\$59.95	\$54.54
21-8320	3/"	50'	51.95	48.36
21-8322	1"	25'	64.95	56.60
21-8324	1½"	25'	64.95	56.60



HellermannTyton Grip-Ties

Constructed of Velcro® hook and loop material, grip-ties are a low profile, single piece fastening device that can be removed and re-used for repetitive access to cabling. Because they cannot be over cinched, they are safe for Category 5 and fiberoptic cable. Available in a variety of sizes, grip-ties can be used for most any wire bundling applications. Ten per package.

			Price	per pkg.
Order #	Width	Length	(1-9)	(10-up)
10 per pkg.				
21-4000	1/2"	6"	\$9.93	\$9.52
21-4020	1/2"	8"	10.24	10.02
21-4040	1/2"	11"	11.26	10.97
21-4060	3/"	11"	17.93	17.37
100 per pkg.				
21-4010	1/2"	6"	66.66	64.50
21-4030	1/2"	8"	73.73	70.74
21-4050	1/2"	11"	90.20	-
21-4080	1/2"	180" roll	12.41	-

HellermannTyton

Rite-On Wire Markers •Self-laminating wire and cable



markers •Ideal for marking multiple cable runs •Temperature range: -50°~200°F

Order #	(1-3)	(4-up)
21-1510	\$11.95	\$11.63





<u>o BRADy</u> Write-On

Self-Laminating Wire and Cable Markers

 Transparent part over-wraps to provide snug fitting, self-laminating shield that resists oil, water and solvents •For



applications above or below ground •Wire markers are in a convenient book format White vinyl material

Order # Mfr. #	Qty. per Book	Size of Write-on Area (W) x (H)	Size	(ea.)
28-4911 PWC-PK-1	120	.75" x .50"	.75" x 1.75"	\$19.95
28-4912 PWC-PK-3	60	1.00" x .75"	1.00" x 3.00"	19.95

O-BRADY.

Self-Laminating Wire Marking Labels

•Self-laminating labels used with the IDPro Plus and BMXC Plus label printers •Clear laminate

protects the wire marker from fading •Suffix -292 is a self-laminating vinyl cloth, maximum temperature 150°F, heat, and solvent resistant

100 1,11	cut, u	iiu sori	CHIC LODIC	ourro.		
Order #	Label Dime	nsions	Maximum Char. Across Max lines			
Mfr. #	Α	В	of print	Large	Small	(ea.)
10~16	gauge	wire, 2	50 labels (per roll		
28-4877			2	3	4	\$25.24
WML-20	5-292-	75				
28-4880	1.00	.75"	2	7	10	24.95
WML-21	1-292-	75				

Carlon **Resi–Guard**[®] **Flexible Raceway**

Ideal for providing a main chase from the main distribution panel to a secondary hub in the attic

or basement, Resi–Guard[®] nonmetallic flexible raceway is available in ¾" and 2" diameters. It is hand bendable, lightweight and easily cut-to-length to reduce scrap. Additionally, the 2" diameter size includes a factory–installed 900 lb. pull tape. Bright orange color clearly signifies a low-voltage installation.

			Р	rice per ro	II
Order #	Diameter	Length	(1–3)	(4–9)	(10-up)
28-17210	3/1"	100'	\$44.95	\$41.15	\$40.12
28-17215	2"	50'	73.75	68.25	66.00



This complete line of one-piece quick connect couplings, threaded adaptors and snap in terminator adaptors provides easy, professional installation of flexible raceway. All pieces are sold individually.

Fig	. Order #	Description	(1–3)	(4–9)	(10-up)
Α	28-17185	3/4" quick coupling	\$0.89	\$0.75	\$0.70
В	28-17190	3/4" threaded adaptor	1.75	1.49	1.40
С	28-17200	2" standard coupling	0.85	0.71	0.67
D	28-17205	2" threaded adaptor	1.19	1.02	0.92

Carlon

Resi-Guard® Raceway Clamps

Used to secure Carlon and similar flexible raceway. PVC clamps are

non-conductive and non-corrosive. Sizes available for use with ¾" and 2" raceway. Five per package.

Order #	Diameter	(1–3 pkgs.))(4–9 pkgs.)	(10 pkgsup)
28-17220	3/4"	\$1.49	\$1.35	\$1.29
28-17225	2"	3 79	3 39	3 18



ScotchCode[™] Wire Labeler

•These compact ScotchCode dispensers provide fast, convenient labeling of wire and cable •Resistant to flagging, dirt, oil and heat •Dispensers available with ten rolls of numbered tape (one each of 0~9), or ten rolls of different colored tape

	ton romo or anno		
Order #	Labeler Type	Per Roll	(ea.)
108-030	Number	60'	\$46.95
108-035	Colored	8'	46.95
Order #	Refill	Order #	Refill
108-040	"0"	108-065	"5"
108-045	"1"	108-070	"6"
108-050	"2"	108-075	"7"
108-055	"3"	108-080	"8"
108-060	"4"	108-085	"9"

\$2.99 (ea.)\$2.69 (2-up)

Write-On Wire Marker Dispenser

Light weight and durable dispensers with markers. Use to mark wire, motor

panels, or sub-assemblies. Each dispenser contains a black marker pen and 70 labels, except for #108-3223 which contains 250 labels.

Order #	Description	(ea.)
108-3222	Dispenser with 1" x 2.5" labels	\$37.95
108-3223	Dispenser with ¾" x 1¾" labels	36.95
108-3308	Refill for #108-3223	28.95

SPB Printed Wire Marker Books

SPB wire marker books contain printed vinyl cloth wire and terminal

letters, numbers and industry-standard legends. Books for alarm systems and load centers are also available. Each book contains a minimum of 450 marks, the contents of which are clearly listed on the cover. Also included with each book is a 3M Post-it note pad.

	1		
Order #	Contents Include	(1-2)	(3-up)
108-870	45 ea. 0-9; 15 ea. L1, L2, L3. T1. T2. T3	\$22.95	\$20.66
108-871	10 ea. A-Z, 0-15,+, -,/	22.95	20.66
108-872	10 ea. 1-43	22.95	20.66

	nd mobile e		viring •Black	k
Order #	(I.D.)	Length	(1-9 pkgs.)	(10 pkgsup)
28-1505	1/4"	50'	\$5.52	\$4.69
28-1510	1/4"	100'	9.99	8.49
28-1520	3⁄8"	100'	13.53	11.83
28-1110	1/2"	30'	5.29	4.64
28-1525	1/2"	50'	7.86	6.88
28-1530	1/2"	100'	14.57	12.75
28-1965	3/"	30'	7.24	6.34
28-1975	3/"	100'	22.31	19.54

Wire and Cable

e company

Section 1



wires •Paintable, stainable, repositionable • 100% customizable to any length without waste •Great for organizing home office, computer networks, and home theater systems •Can easily be removed from most surfaces •Simply measure and cut, fold and mount, peel tape and seal wires

Order #	Color	Description	(ea.)							
Retail pack										
21-8380	White	1/2" x 3/4" x 8'	\$10.49							
21-8382	White	½" x 1½" x 8'	11.25							
21-8384	Black	1/2" x 3/4" x 8'	10.49							
21-8386	Black	½" x 1½" x 8'	11.25							
Bulk pack										
21-8388	White	½" x ¾" x 50'	59.95							
21-8390	White	½" x 1½" x 50'	61.95							
21-8392	Black	½" x ¾" x 50'	59.95							
21-8394	Black	½" x 1½" x 50'	61.95							

Harness Wrap

•Reuseable harness wrap protects wire bundles •Leads can be brought out at any point to make custom wiring harness •Ideal for car stereo installation •25' length •Clear

Order #	Size	(ea.)
28-1155	1/16"~1/2"	\$6.55
28-0290	⁵ ∕16"~2"	17.99

MCM Heat Shrink Kit

•This kit features high-quality ICO-Rally heat shrink products •127 pieces of the most popular heat shrink sizes and colors •6" length **Kit contains:**



Size	Black	Clear	Red	White	Blue	Yellow	Green	Refill#
1/16"	6	4	4	3	3	2	2	95-780
3/32"	6	4	4	3	3	2	2	95-785
1/8"	6	4	4	3	3	2	2	95-790
3/16"	6	4	4	3	3	2	2	95-675
1/4"	6	4	2	2	2	2	2	95-680
3/8"	3	2	2	1	1	1	1	95-685
#102-025\$39.95 (kit)								





markers with

clearly printed