

Micro Commercial Components

Micro Commercial Components 20736 Marilla Street Chatsworth

CA 91311 Phone: (818) 701-4933

Fax: (818) 701-4939

BAT54T THRU BAT54ST

Features

- Ultra-Small Surface Mount Package
- Low Forward Voltage Drop
- Fast Switching
- PN Junction Guard Ring for Transient and ESD Protection
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0

- 6				
ĺ	MCC	Device		Pin
	Part Number	Marking	Type	Configuration
	BAT54T	L1	Single	Figure 1
	BAT54AT	L2	Dual	Figure 2
	BAT54CT	L3	Dual	Figure 3
	BAT54ST	L4	Dual	Figure 4

Maximum Ratings


DC Blocking Voltage	V_R	30V	
Average Rectified Output Current	Io	200mA	
Repetitive Peak Forward Current	I_{FRM}	300mA	
Non-Repetitive Peak Forward Current t<1s	I_{FSM}	600mA	
Total Power Dissipation @ T _A = 25°C	P_{D}	150mW	
Storage Temperature Range	T _{stg}	-65°C to 150°C	
Junction Temperature	Tj	-65°C to 150°C	


Electrical Characteristics @ 25°C Unless Otherwise Specified


Ratings	Symbol	Max.	Notes	
Forward Voltage	V_{F}	240mV 320mV 400mV 500mV 1000mV	$I_F = 0.1\text{mA}$ $I_F = 1\text{mA}$ $I_F = 10\text{mA}$ $I_F = 30\text{mA}$ $I_F = 100\text{mA}$	
Reverse Current	I_R	2μΑ	V _R = 25V	
Reverse Breakdown Voltage	$V_{(BR)}$	>30V	I _R =100uA	
Total Capacitance	Ст	10pF	Measured at 1.0MHz, V _R =1.0V	
Reverse Recovery Time	t _{rr}	5nS	IF = 10mA; IR = 10mA ~1.0mA, RL = 100 Ω	

150mWatt, 30Volt Schottky Barrier Diode











DIMENSIONS									
	INCHES MM								
DIM	MIN	MAX	MIN	MAX	NOTE				
Α	.059	.067	1.50	1.70					
В	.030	.033	0.75	0.85					
С	.057	.069	1.45	1.75					
D	.020 Nominal		0.50Nominal						
Е	.035	.043	0.90	1.10					
G	.000	.004	.000	.100					
Τ	.028	.031	.70	0.80					
J	.004	.008	.100	.200					
V	010	014	25	25					


BAT54T thru BAT54ST




Micro Commercial Components









 V_R , REVERSE VOLTAGE (V) Fig. 4 Typical Capacitance vs. Reverse Voltage

Pin Configuration - Top View











IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes.
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp* . are not intended for use in Medical,

Aerospace or Military Applications.