## Mini BNC Plug Straight





## **Specifications:**

Connector Type : BNC Coaxial
Body Style : Straight Plug
Coaxial Termination : Crimp

Impedance :  $75\Omega$ 

Coaxial Cable Types : RG-179B, RG-187A

**Contact Material** : Brass **Contact Plating** : Gold Frequency Max : 1GHz Connector Mounting : Cable **Body Plating** : Nickel Coaxial Connector Type : Mini BNC Contact Resistance : 12mΩ : 1,000MΩ Insulation Resistance : PTFE Insulator Material No. of Mating Cycles : 500


Operating Temperature : -40°C to +85°C


VSWR : 1.16 Voltage Rating : 400V AC Withstand Voltage : 1,000V





## Mini BNC Plug Straight











**Stripping Dimension** 

Dimensions: Millimetres (Inches)

Number	Description	Material	Finish
1	Shell	Brass	Nickel 100μ" Min.
2	Body		
3	Gasket	Silicone	Red
4	Washer	Brass	Nickel 100μ" Min.
5	Spring Washer	SK-5	
6	Washer	Brass	
7	Insulation	PTFE	None
8	Centre Contact	Brass	Gold
9	Crimp Ferrule		Nickel 100µ" Min.

## **Part Number Table**

Description	Part Number
Plug, Mini BNC, 75Ω, Straight	56-01N-TGN

Important Notice: This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com



15/01/13 V1.0