


Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output	
12 mm - Embeddable, <i>picofast</i>® Connection 	Bi 2-G12-AN6X-V1131	T4635583		2	3-Wire DC NPN	
	Bi 4-G12-AN6X-V1131		<i>Extended Range</i>	4		
	Bi 2-G12-AP6X-V1131	T4606597		2	3-Wire DC PNP	
	Bi 4-G12-AP6X-V1131	M1690703	<i>Extended Range</i>	4		
	12 mm - Nonembeddable, <i>picofast</i> Connection 	Ni 5-G12-AN6X-V1131	T4635721		5	3-Wire DC NPN
		Ni 5-G12-AP6X-V1131	T4635690		5	3-Wire DC PNP
12 mm - Embeddable, <i>eurofast</i>® Connection 	Bi 2-G12-AN6X-H1141	T4606693		2	3-Wire DC NPN	
	Bi 2-G12-AP6X-H1141	T4606595		2	3-Wire DC PNP	
	Bi 4-EG12-AP6X-H1141	T4607091	<i>Extended Range</i>	4		
12 mm - Nonembeddable, <i>eurofast</i> Connection 	Ni 5-G12-AN6X-H1141	T4635793		5	3-Wire DC NPN	
	Ni 5-G12-AN7X-H1141	T1714593		5		
	Ni 8-G12-AN6X-H1141	T4611383	<i>Extended Range</i>	8		
	Ni 5-G12-AP6X-H1141	T4635692		5	3-Wire DC PNP	
	Ni 5-G12-Y0-H1141	T1005594		5	2-Wire DC NAMUR	

For detailed sensor specifications see Section A.
 Normally Closed versions available upon request, consult factory.



Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Face	Power LED	Output LED	Mating Cordset	Wiring Diagram #	Wiring Diagrams
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	PKG 3Z-*	1	Diagram 1
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	PKG 3Z-*	1	
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	PKG 3Z-*	2	Diagram 2
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	PKG 3Z-*	2	
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	PKG 3Z-*	1	Diagram 3
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	PKG 3Z-*	2	Diagram 4
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	Diagram 5
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	4	Diagram 5
	2000	≤200	-25 to +70	IP 67	SS	PA 12	N/A	YE	RKV 4T-*	4	
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	Diagram 5
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	
	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	3	
10-30 VDC	2000	≤200	-25 to +70	IP 67	CPB	PA 12	N/A	YE	RK 4T-*	4	Diagram 5
5-30 VDC	2000	Remote	-25 to +70	IP 67	CPB	PA 12	N/A	N/A	RK 4,21T-*	5	Diagram 5

Barrels

* Length in meters.

For material descriptions see page A34.