

# Safety Data Sheet according to (EC) No 1907/2006

Page 1 of 8

sds no.: 351606 V003.3

Revision: 04.01.2012

printing date: 26.02.2013

Loctite Double Bubble Part A

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### **Product identifier:**

Loctite Double Bubble Part A

#### Relevant identified uses of the substance or mixture and uses advised against:

Intended use:

2-Component epoxy adhesive

## Details of the supplier of the safety data sheet:

Henkel Limited Technologies House Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (0)1442 278000 +44 (0)1442 278071 Fax-no.:

ua-productsafety.uk@uk.henkel.com

#### **Emergency Telephone Number:**

24 Hours Emergency Tel: +44 (0)1442 278497

## **SECTION 2: Hazards identification**

# Classification of the substance or mixture:

#### Classification (DPD):

Xi - Irritant

R36/38 Irritating to eyes and skin.

Sensitizing

R43 May cause sensitisation by skin contact.

N - Dangerous for the

environment

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

MSDS-No.: 351606 Loctite Double Bubble Part A Page 2 of 8

V003.3

### Label elements (DPD):

N - Dangerous for the environment

Xi - Irritant





#### Risk phrases:

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### Safety phrases:

S24 Avoid contact with skin.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of water and soap.

S37 Wear suitable gloves.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

### Additional labeling:

Contains epoxy constituents. See information supplied by the manufacturer.

For consumer use only: S2 Keep out of the reach of children

S46 If swallowed, seek medical advice immediately and show this container or label.

### Contains:

Bisphenol-A epichlorhydrin resin MW <= 700,

RP Bisphenol F-epichlorohydrin resin, MW<=700,

1,3-Propanediol, 2-(hydroxymethyl)-2-methyl-, polymer with 2-(chloromethyl)oxirane

### Other hazards:

None if used properly.

# **SECTION 3: Composition/information on ingredients**

# General chemical description:

Part A of two part adhesive

# Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components	EC Number	content	Classification
CAS-No.	REACH-Reg No.		
Bisphenol-A epichlorhydrin resin MW <=	500-033-5	< 25 %	Chronic hazards to the aquatic environment 2
700	01-2119456619-26		H411
25068-38-6			Serious eye irritation 2
			H319
			Skin irritation 2
			H315
			Skin sensitizer 1
			H317

Only dangerous ingredients for which a CLP classification is already available are displayed in this table. For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

MSDS-No.: 351606 Loctite Double Bubble Part A Page 3 of 8

V003.3

#### Declaration of ingredients according to DPD (EC) No 1999/45:

Hazardous components	EC Number	content	Classification	
CAS-No.	REACH-Reg No.			
Bisphenol-A epichlorhydrin resin MW	500-033-5	< 25 %	R43	
<= 700	01-2119456619-26		Xi - Irritant; R36/38	
25068-38-6			N - Dangerous for the environment; R51/53	

For full text of the R-Phrases indicated by codes see section 16 'Other Information'. Substances without classification may have community workplace exposure limits available.

### **SECTION 4: First aid measures**

#### Description of first aid measures:

#### Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

#### Skin contact:

Rinse with running water and soap.

Seek medical advice.

#### Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

#### Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.

Seek medical advice.

### Most important symptoms and effects, both acute and delayed:

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

#### Indication of any immediate medical attention and special treatment needed:

See section: Description of first aid measures

## **SECTION 5: Firefighting measures**

### **Extinguishing media:**

# Suitable extinguishing media:

Carbon dioxide, foam, powder

### Extinguishing media which must not be used for safety reasons:

None known

### Special hazards arising from the substance or mixture:

In the event of a fire, carbon monoxide (CO) and carbon dioxide (CO2) can be released.

In case of fire, keep containers cool with water spray.

#### Advice for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

# **SECTION 6: Accidental release measures**

### Personal precautions, protective equipment and emergency procedures:

Avoid skin and eye contact.

### **Environmental precautions:**

Do not let product enter drains.

MSDS-No.: 351606 Loctite Double Bubble Part A Page 4 of 8

V003.3

#### Methods and material for containment and cleaning up:

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

#### Reference to other sections:

See advice in chapter 8

#### **SECTION 7: Handling and storage**

#### Precautions for safe handling:

Use only in well-ventilated areas.

Avoid skin and eye contact.

Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

#### Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

#### Conditions for safe storage, including any incompatibilities:

Store in a cool, well-ventilated place.

#### Specific end use(s):

2-Component epoxy adhesive

# **SECTION 8: Exposure controls/personal protection**

### Control parameters:

Valid for

Great Britain

None

### **Exposure controls:**

#### Respiratory protection:

Use only in well-ventilated areas.

# Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

# Eye protection:

Wear protective glasses.

#### Skin protection:

Wear suitable protective clothing.

MSDS-No.: 351606 Loctite Double Bubble Part A Page 5 of 8

V003.3

### **SECTION 9: Physical and chemical properties**

### Information on basic physical and chemical properties:

Appearance liquid colourless
Odor mild

pH No data available / Not applicable Initial boiling point No data available / Not applicable

Flash point > 100,00 °C (> 212 °F) Decomposition temperature No data available / Not applicable Vapour pressure No data available / Not applicable

Density 1,2000 g/cm3

Bulk density No data available / Not applicable Viscosity No data available / Not applicable Viscosity (kinematic) No data available / Not applicable Explosive properties No data available / Not applicable Solubility (qualitative) No data available / Not applicable No data available / Not applicable Solidification temperature No data available / Not applicable Melting point No data available / Not applicable Flammability Auto-ignition temperature No data available / Not applicable Explosive limits No data available / Not applicable Partition coefficient: n-octanol/water No data available / Not applicable Evaporation rate No data available / Not applicable No data available / Not applicable Vapor density No data available / Not applicable Oxidising properties

#### Other information:

No data available / Not applicable

## **SECTION 10: Stability and reactivity**

#### Chemical stability:

Stable under recommended storage conditions.

#### Possibility of hazardous reactions:

See section reactivity

### **Conditions to avoid:**

Stable under normal conditions of storage and use.

#### **Incompatible materials:**

None if used properly.

### Hazardous decomposition products:

carbon oxides.

# **SECTION 11: Toxicological information**

### General toxicological information:

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### **Oral toxicity:**

May cause irritation to the digestive tract.

### Inhalative toxicity:

May cause irritation to respiratory system.

### Skin irritation:

Irritating to the skin.

MSDS-No.: 351606 Loctite Double Bubble Part A Page 6 of 8

V003.3

### Eye irritation:

Irritating to eyes.

#### **Sensitizing:**

May cause sensitization by skin contact.

#### Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Bisphenol-A epichlorhydrin resin MW <= 700 25068-38-6	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		

# **SECTION 12: Ecological information**

### General ecological information:

Do not empty into drains / surface water / ground water.

Toxic to aquatic organisms

May cause long-term adverse effects in the aquatic environment.

The preparation is classified based on the conventional method outlined in Article 6(1)(a) of Directive 1999/45/EC. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

#### **Ecotoxicity:**

No data available for the product.

## **SECTION 13: Disposal considerations**

### Waste treatment methods:

Product disposal:

Dispose of in accordance with local and national regulations.

Contribution of this product to waste is very insignificant in comparison to article in which it is used

#### Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

### Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

# **SECTION 14: Transport information**

### Road transport ADR:

Class: 9
Packaging group: III
Classification code: M6
Hazard ident. number: 90
UN no.: 3082
Label: 9

Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (Epoxy resin)

Tunnelcode: (E)

MSDS-No.: 351606 Loctite Double Bubble Part A Page 7 of 8

V003.3

### Railroad transport RID:

Class: 9
Packaging group: III
Classification code: M6
Hazard ident. number: 90
UN no.: 3082
Label: 9

Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (Epoxy resin)

Tunnelcode:

## Inland water transport ADN:

Class: 9
Packaging group: III
Classification code: M6

Hazard ident. number:

UN no.: 3082 Label: 9

Technical name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (Epoxy resin)

#### Marine transport IMDG:

Class: 9
Packaging group: III
UN no.: 3082
Label: 9
EmS: F-A ,S-F
Seawater pollutant: Marine pollutant

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (Epoxy resin)

### Air transport IATA:

Class: 9
Packaging group: III
Packaging instructions (passenger) 964
Packaging instructions (cargo) 964
UN no.: 3082
Label: 9

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin)

## **SECTION 15: Regulatory information**

### Safety, health and environmental regulations/legislation specific for the substance or mixture:

VOC content < 3,00 %

(1999/13/EC)

MSDS-No.: 351606 Loctite Double Bubble Part A Page 8 of 8

V003.3

## **SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

R36/38 Irritating to eyes and skin.

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

#### **Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and it's subsequent amendments, and Commission Directive 1999/45/EC.