

No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Epoxy Minute Adhesive Resin (GB)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Name of product Epoxy Minute Adhesive Resin (GB)

Code-Nr. 105501

Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

2-Component Epoxy Resin - Resin Component

Details of the supplier of the safety data sheet

Manufacturer/distributor WEICON GmbH & Co. KG

Königsberger Straße 255, DE-48157 Münster

Postbox 84 60, DE-48045 Münster

Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244

E-Mail: info@weicon.de Internet: www.weicon.de

Advice Abteilung Angebote, Verkauf, Export

Phone ++49(0)251 / 9322 - 0 E-mail (competent person):

info@weicon.de

Emergency telephone number

Emergency advice Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)

Phone ++49(0)228-19 240

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to 67/548/EEC or 1999/45/EC

Xi; R36/38 R43 N; R51/53 **R-phrases**

36/38 Irritating to eyes and skin.

43 May cause sensitisation by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Label elements

Labelling according to 67/548/EEC or 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives.

Xi Irritant

N Dangerous for the environment

R-phrases

36/38 Irritating to eyes and skin.

May cause sensitisation by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases

2 Keep out of the reach of children.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

36/37 Wear suitable protective clothing and gloves.



No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Epoxy Minute Adhesive Resin (GB)

If swallowed, seek medical advice immediately and show this container or label.
 Avoid release to the environment. Refer to special instructions/safety data sheets.

Hazardous ingredients for labeling

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. See information supplied by the manufacturer.

Other hazards

No information available.

SECTION 3: Composition/information on ingredients

Mixtures

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC	
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	resin (number average molecular		
CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]	
25068-38-6	500-033-5	500-033-5 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)		Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411	
REACH					
CAS No	Name			REACH registration number	
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)			01-2119456619-26-xxxx	

Description

Resin for a two-component epoxy adhesive

SECTION 4: First aid measures

Description of first aid measures

General information

Remove contaminated soaked clothing immediately and dispose it safely.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

Do not use solvents or thinners.

In case of contact with skin wash off with soap and water.

In case of eye contact

May cause superficial burns.

In case of contact with eyes rinse thoroughly with water.

Seek medical advice immediately.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

If swallowed give water to drink.



No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Epoxy Minute Adhesive Resin (GB)

Most important symptoms and effects, both acute and delayed

No information available.

Indication of any immediate medical attention and special treatment needed

Treatment (Advice to doctor)

In the event of pulmonary irritation treat initially with dexamethasone metered-dose aerosol.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

Extinguishing media which must not be used for safety reasons

Full water jet

Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.

Nitrogen oxides (NOx)

Carbon monoxide (CÓ)

Carbon dioxide (CO2)

Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

Methods and material for containment and cleaning up

Send in suitable containers for recovery or disposal.

Take up with absorbent material.

Reference to other sections

No information available.

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.

Advice on storage compatibility

Do not store together with animal feedstuffs.

Do not store together with food.



No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Epoxy Minute Adhesive Resin (GB)

Further information on storage conditions

Protect from direct solar radiation.
Store container at cool and aired place.
Store in a dry place.
Protect from heat/overheating.

Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

Control parameters

No information available.

Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Breathing apparatus in the event of aerosol or mist formation.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves. Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

tightly fitting goggles protective shield

Skin protection

Light protective clothing.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Form Colour Odour

liquid pale hardly noticeable

Important health, safety and environmental information

Value Temperature at Method Remark

Flash point > 100 °C

Density 1,16 g/cm3

Solubility in water insoluble

Other information

No information available.



No. 1907/2006 (REACH) Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Epoxy Minute Adhesive Resin (GB)

SECTION 10: Stability and reactivity

Reactivity

No information available.

Chemical stability

No information available.

Possibility of hazardous reactions

No information available.

Conditions to avoid

Keep away from heat.

Incompatible materials

Materials to avoid

Reactions with strong acids and alkalies. Reactions with strong oxidising agents.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 2000 mg/kg	rat		
Irritability skin	irritant	rabbit		
Irritability eye	irritant	rabbit eye		
Skin sensitization	sensitizing	Guinea pig		

Experiences made from practice

Sensitization through skin contact possible.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

SECTION 12: Ecological information

Toxicity

No information available.

Persistence and degradability

No information available.

Bioaccumulative potential

No information available.

Mobility in soil

No information available.

Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.



No. 1907/2006 (REACH)
Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

Epoxy Minute Adhesive Resin (GB)

SECTION 13: Disposal considerations

Waste treatment methods

Recommendations for the product

Cured material may be considered inert and disposed of as builders waste.

Remove in accordance with local official regulations.

Recommendations for packaging

Uncontaminated packaging may be treated as household waste.

Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land and inland navigation transport ADR/RID

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY HARZ), 9, III, (E), Classification code: M6

Marine transport IMDG

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN), 9, III

MARINE POLLUTANT: Yes
Air transport ICAO/IATA-DGR

UN 3082 Environmentally hazardous substance, liquid, n.o.s. (BISPHENOL A EPOXY RESIN), 9, III

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

Special precautions for user

No information available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

Remark

Daten separat anfragen / Request data separately.

Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.