

Extension Lead

10 Gang, Tower, 2m

pro-ELEC



Features:

- 10 gang tower surge protected 13A non-rewireable extension socket with surge protected neon
- Main switch with power neon with 2m cable

Standard:

- BS 1363/A, BS 5733

Specifications:

Connector Type A	: UK Mains Plug
Connector Type B	: Socket
Current Rating	: 13A
Cable Assembly Type	: Power Cord
Jacket Colour	: White
Cable Length	: 2m
Conductor Size	: 1.25mm ²
No. of Outputs	: 10
Voltage	: 220V to 240V
Maximum Operating Voltage	: 300Vrms
Mains Three Way Protection	: LN LE NE
Peak Current	: 4.5kA
Energy Max	: 3 × 125J
Clamping Voltage Max	: 775V
Response Time	: < 50ns

Conditions for Use:

An ambient temperature in the range -5°C to +40°C, the average value over 24 hours not exceeding 25°C.

A situation not subject to exposure to direct radiation from the sun or other source of heat like to raise temperature above the limits.

An altitude not exceeding 2,000m above sea level.

An atmosphere no subject to abnormal pollution by smoke, chemical fumes, rain, spray, prolonged periods of high humidity or other abnormal conditions.

Extension Lead

10 Gang, Tower, 2m

Construction:

Item	Description	Material
1	Socket cover, base, stand cover	ABS
2	Internal frame, stand	FRPP
3	Socket terminals (bus bar)	Brass
4	Cover screw	Mild steel nickel plated
5	Shutter	Nylon (PA)
6	Spring	Mild steel
7	Neon lamp with 220kΩ resistor	Green light
8	Neon lamp cover	Polycarbonate (PC)
9	Surge component	Metal oxide varistor + thermal fuse + neon indicator
10	Switch	Nylon (PA)+polycarbonate (PC)
11	Plug	13A BS 1363 plug
12	Cable	PVC, BS6500 3 × 1.25mm ²

Part Number Table

Description	Part Number
Extension Lead, 10 Gang, Tower, 2m	2710-2M

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-ELEC is the registered trademark of the Group. © Premier Farnell plc 2012.