



Features:

- High efficiency
- High transparent low-iron, tempered glass
- Unique techniques give the panel following features: aesthetic appearance, with stands high wind-pressure and snow load, and easy installation
- Outstanding low-light performance
- Nominal DC for standard output
- Unique technology ensure that problems of water freezing and warping do not occur
- Design to meet unique demand of customer


Specifications:

MONO or Poly	: Poly
Maximum Power	: 12Wp
Maximum Power Voltage	: 17V
Maximum Power Current	: 0.59A
Current at P Max	: 590mA
Length	: 327mm
Width	: 357mm
Height	: 18mm
Weight Min	: 1.68kg
Open Circuit Voltage	: 21.5V
Short Circuit Current	: 0.63A
Package	: 1pc/box
Maximum System Voltage	: 720V DC
Temperature Coefficients of I _{sc}	: 0.06%/K
Temperature Coefficients of V _o	: -0.36%/K
Temperature Coefficients of P _m	: -0.45%/K
Temperature Range	: -40°C to +85°C
Surface Maximum Load Capacity	: 60ms (200kg/sq.m)
Allowable Hail Load	: Steel ball fall down from 1m height
Length of Cables	: Terminals
Output Tolerance	: ±3%
Frame (Material, Corners, etc.)	: Aluminium (epx 0.8w)


Electrical Characteristics

I-V Curves

Current-voltage characteristics of photovoltaic Module SP12 at various cell temperatures




Current-voltage characteristics of photovoltaic Module SP12 at various irradiance levels



Physical Specifications

SP12



Dimensions : Millimetres

Part Number Table

Description	Part Number
Solar Panel, 12W, 17.5V, 357mm × 327mm × 18mm	MC-SP12-GCS

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.