

		+	-	
		++		
	+	++		H
				Ħ

Features:

- · High efficiency
- High transparent low-iron, tempered glass
- Unique techniques give the panel following features: aesthetic appearance, with stands high wind-pressure and snow load, and easy installation
- Outstanding low-light performance
- Nominal DC for standard output
- Unique technology ensure that problems of water freezing and warping do not occur
- · Design to meet unique demand of customer

Specifications:

MONO or Poly	: Poly		
Maximum Power	: 30Wp		
Maximum Power Voltage	: 17V		
Maximum Power Current	: 1.77A		
Length	: 426mm		
Width	: 668mm		
Height	: 35mm		
Weight Min	: 6.36kg		
Open Circuit Voltage	: 21.5V		
Short Circuit Current	: 1.93A		
Package	: 1pc/box		
Maximum System Voltage	: 720V DC		
Temperature Coefficients of Isc	: 0.06%/K		
Temperature Coefficients of Vo	: -0.36%/K		
Temperature Coefficients of Pm	: -0.45%/K		
Temperature Range	: -40°C to +85°C		
Surface Maximum Load Capacity	: 60ms (200kg/sq.m)		
Allowable Hail Load	: Steel ball fall down from 1m height		
Length of Cables	: Terminals		
Output Tolerance	: ±3%		
Frame (Material, Corners, etc.)	: Aluminium (epx 0.8w)		


www.element14.com www.farnell.com www.newark.com



Solar Panel




Electrical Characteristics




Current-voltage characteristics of photovoltaic Module SP30 at various irradiance levels


I-V Curves



Physical Specifications

SP30





Back View

Part Number Table

Description	Part Number	
Solar Panel, 30W, 17.5V, 668mm × 426mm × 35mm	MC-SP30-GCS	

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

www.element14.com www.farnell.com www.newark.com

Dimensions : Millimetres

