




Guide rail with coding, grey



Optional ESD clip for alignment pin



Part no.:
64560-089

Features:

- Guide rail, plastic, one-piece, red, for 2 mm groove width
- Assembly
 - Can be clipped into horizontal rails in Al extrusion
 - Can be clipped into 1.5 mm thick plate
- Storage temperature: from -40 °C ... 130 °C
- With keying/coding block
- The optional ESD clip ensures conductive contact between PCB and horizontal rail, on both the solder side and the component side.
- The optional ESD clip for IEEE alignment pins can be fitted into guide rails with keying/coding and into the keying/coding block. It ensures conductive contact between the alignment pin of the insertion/extraction handle (IEL or IET handle) and the horizontal rail
- Optional keying/coding pegs to prevent boards being inserted into the wrong slot position

Standard pack quantity 50




Technical information:

Board length	Groove width	Material	Finish	Qty	Description
160 (mm)	2 (mm)	PBT, UL 94 V-0	red	1 piece (SPQ 50)	For CompactPCI, VME64x with coding for 4 HP wide application

Dimensions
table

Board height		Dimensions			
L	A2	w	C	D	
mm	mm	mm	mm	mm	
160	149.39	135	120	150	

A2: length of rail
B: Pitch of snap-in fixing
C: Pitch of guide rail retention screws
D: Pitch of horizontal rail retention screws



Optional screw fixing

Product illustrations are exemplary illustrations and can deviate from supplied products.

Accessories:

Part no.	Description	
24560-141	Torx panhead screw 2.5 × 9.3, zinc-plated, Qty: 100 pieces	
20817-501	Coding peg PC, UL 94 V-0, RAL 7035, Qty: 100 pieces	
24560-255	ESD clip for guide rails Qty: 50 pieces	
24560-256	ESD clip for alignment pin of CPC/IVME64x handle Qty: 50 pieces	

Note:
Delivery is exclusively in standard pack quantity