



Produkt Informationen

Weller®

WR 3000M

Bestellnummer : **T0053368699**

Desoldering Station Set

Desoldering station with multi-digital 420 W, 230 V with soldering iron DSX 80 and internal pump

Technical data

This station is ESD safe.



Dimension L x B x H:	273 x 235 x 102 mm (10,75 x 9,2 x 4,02 inch)
Weight:	approx. 6,7 kg
Channels:	3
Net supply:	230 V
Power supply:	360 W
Protection class:	I
Fuse:	T500 mA (230V / 50/60 Hz)
Fuse overcurrent release:	2 A
Temperature control of channels:	Soldering and desoldering tool, continuously variable from 50°C - 550°C (150°F - 999°F)
	Temperature control range is tool independent
	Soldering iron WP 80 / WP 120: 50°C - 450°C (150°F - 850°F)
	Soldering iron WP 200 / WSP 150: 50°C - 550°C (150°F - 950°F)
	Soldering iron WMRT/WMRP: 100°C - 450°C (200°F - 850°F)
	Desoldering iron DSX 80 / DXV 80 / DSX 120: 50°C - 450°C (150°F - 850°F)
	Hot air iron HAP 1 /HAP200: 50°C - 550°C (150°F - 950°C)

Temperature accuracy:	± 9°C (± 17°F)
Temperature stability:	± 2°C (± 4°F)
Bleeder:	Soldering tip (Tip to ground) conforms IPC-J-001
Bleeder voltage:	Soldering tip (Tip to ground) conforms IPC-J-001
Pump:	(periodic duty 30/30s)
Max. vacuum:	0,7 bar
Max. delivery rate:	max. 18 l/min
Hot air:	max. 15 l/min
Display:	LCD
Temperature control:	Buttons
Equipotential bonding:	Via 3.5 mm pawl socket at the back of device (hard grounded normal state)
USB interface:	yes

Rework - Soldering, Desoldering and Hot air

- One station meets the requirements of a rework workplace
- Unique connecting compatibility of all tools
- 3 respectively 2 independent tool channels with automatic tool recognition guarantee the simultaneous operation of 2 to 3 soldering tools.
- Tools are permanently ready for use