


Surface Mount Switching Diode



Features

- Fast switching speed.
- Surface mount package ideally suited for automatic insertion.
- For general purpose switching applications.
- High conductance.

Applications

High speed switching application.

Maximum Rating @ T_A = 25°C unless otherwise specified



Characteristic	Symbol	BAS19	BAS20	Unit
Peak Repetitive Reverse Voltage	V _{RRM}	120	200	V
Working Peak Reverse Voltage DC Reverse Voltage	V _{RWM} V _R	100	150	V
RMS Reverse Voltage	V _{R(RMS)}	71	106	V
Forward Continuous Current (max.)	I _{FM}	400		mA
Average rectified output Current	I _O	200		mA
Non-Repetitive Peak Forward Surge Current @t=1.0µs @t=1.0s	I _{FSM}	2.5 0.5		A
Repetitive Peak Forward Surge Current	I _{FRM}	625		A
Power Dissipation	P _D	250		mW
Thermal Resistance Junction to Ambient Air	R _{θJA}	500		°C/W
Operating Junction Temperature Range	T _j	150		°C
Storage Temperature Range	T _{STG}	-65 to +150		°C

Surface Mount Switching Diode

Electrical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbol	Min	Max.	Unit	Test Condition
Reverse breakdown voltage BAS19 BAS20	$V_{(BR)R}$	100 150	-	V	$I_R = 100\mu\text{A}$
Forward Voltage	V_F	-	1 1.25	V	$I_F = 100\text{mA}$ $I_F = 200\text{mA}$
Reverse Leakage Current BAS19 BAS20	I_R	-	100	nA	$V_R = 100\text{V}$ $V_R = 105\text{V}$
Junction Capacitance	C_j	-	5	pF	$V_R = 0\text{V}$, $f = 1.0\text{MHz}$
Reverse Recovery Time	t_{rr}	-	50	ns	$I_F = I_R = 30\text{mA}$, $t_{rr} = 0.1 \times I_R$


Typical Characteristics @ $T_A = 25^\circ\text{C}$ unless otherwise specified



Surface Mount Switching Diode


Package Outline

Plastic surface mounted package



SOT-23		
Dim	Min	Max
A	2.85	2.95
B	1.25	1.35
C	1 Typical	
D	0.37	0.43
E	0.35	0.48
G	1.85	1.95
H	0.02	0.1
J	0.1 Typical	
K	2.35	2.45
All Dimensions in mm		

Soldering Footprint



Dimension : Millimetres

Package Information

Device	Package	Shipping
BAS19/20/21	SOT-23	3000/Tape&Reel

Part Number Table

Description	Part Number
Surface mount switching diode	BAS19-7-F
	BAS20W-7-F

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.