

U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>ÖLFLEX® HEAT 180 SiHF</b>	<b>12.09.2012</b>

Silicone cables with extended temperature range  
Flexibility simplifies installation where space is limited  
Possesses insulating properties after combustion due to remaining SiO<sub>2</sub> ash on the conductor



### Info

The classic for multi-functional use

### Application range

Areas with high ambient temperatures where insulating and sheath materials of conventional cables will embrittle after a short while

Typical fields of application - Steel, cement, ceramic and iron works - Bakery equipment and industrial furnaces - Electric motor industry - Sauna/solarium construction - Thermal and heating elements - Lighting technology - Ventilator engineering - Air-conditioning technology - Galvanisation technology

### Design

Fine-wire, tinned-copper conductor  
Silicone-based core insulation  
Cores twisted in layers  
Silicone-based outer sheath, colour red-brown

### Product features

Halogen-free and flame-retardant (IEC 60332-1-2)  
Resistant to a multitude of oils, alcohols, vegetable and animal fats, and chemical substances

### Remark

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100kg. Refer to Appendix T17 for the definition and calculation of copper-related surcharges.


Please find our standard lengths at: [www.lappkabel.de/en/cable-standardlengths](http://www.lappkabel.de/en/cable-standardlengths)

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

Product Management	Document: LAPP_PRO149EN.pdf	1 / 4
--------------------	-----------------------------	-------

U.I. Lapp GmbH	<b>PRODUCT INFORMATION</b>	
	<b>ÖLFLEX® HEAT 180 SiHF</b>	<b>12.09.2012</b>

### Technical Data

Core identification code:	Colours according to VDE 0293-308, refer to Appendix T9 From 6 cores: black with white numbers
Specific insulation resistance:	>200 GOhm x cm
Conductor stranding:	Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Minimum bending radius:	Occasional flexing: 15 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage:	U <sub>0</sub> /U: 300/500 V
Test voltage:	2000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	-50 °C to +180 °C (adequate ventilation required)

Product Management	Document: LAPP_PRO149EN.pdf	2 / 4
--------------------	-----------------------------	-------

## ÖLFLEX® HEAT 180 SiHF

12.09.2012

Part number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 180 SiHF				
0046001	2 X 0,75	6,4	14.4	59
0046002	3 G 0,75	6,8	21.6	70
00460033	4 G 0,75	7,6	28.8	89
00460043	5 G 0,75	8,5	36.0	112
0046005	6 G 0,75	9,2	43.2	131
0046006	7 G 0,75	9,2	50.4	136
0046007	2 X 1	6,6	19.2	66
0046008	3 G 1	7.0	29.0	79
00460093	4 G 1	7,9	38.4	101
00460103	5 G 1	8,8	48.0	127
0046012	7 G 1	9,5	67.0	156
0046013	2 X 1,5	7,6	29.0	90
0046014	3 G 1,5	8.0	43.0	109
00460153	4 G 1,5	8,8	58.0	134
00460163	5 G 1,5	9,6	72.0	163
0046018	7 G 1,5	10,4	101.0	202
0046039	12 G 1,5	14.0	173.0	361
0046040	16 G 1,5	16,2	230.4	478
0046041	20 G 1,5	17,5	288.0	574
0046042	24 G 1,5	19,8	345.6	720
0046019	2 X 2,5	8,8	48.0	128
0046020	3 G 2,5	9,7	72.0	167
00460213	4 G 2,5	10,6	96.0	206
00460223	5 G 2,5	11,6	120.0	251
0046024	7 G 2,5	12,6	168.0	313
0046025	2 X 4	10,8	76.8	196
0046026	3 G 4	11,5	115.0	241
00460273	4 G 4	12,6	154.0	300
00460283	5 G 4	14.0	192.0	374

Part number	Number of cores and mm <sup>2</sup> per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0046030	7 G 4	15,6	269.0	486
0046031	2 X 6	12,4	116.0	268
0046032	3 G 6	13,2	173.0	333
00460333	4 G 6	14,7	230.0	425
00460343	5 G 6	16,6	288.0	538
0046036	7 G 6	18,6	403.0	705
00460373	4 G 10	19,4	384.0	707
00460453	5 G 10	21,6	480.0	878
00460383	4 G 16	21,4	614.0	1004