

6 ft Mini DisplayPort™ to DVI Adapter Converter Cable – Mini DP to DVI 1920x1200 - Black

StarTech ID: MDP2DVIMM6B



The MDP2DVIMM6B Mini DisplayPort to DVI Adapter Cable lets you directly connect your Mini DP video source (Desktop PC, Laptop, UltrabookWednesday, July 24, 2013 3:03:47 PMrade;, etc.) to a DVI monitor or projector, eliminating the expense of having to upgrade to a Mini DisplayPort-capable monitor.

The adapter cable is 6 feet (1.8 m) in length, and features male-to-male connectors, allowing you to connect your Mini DisplayPort source directly to a DVI display with no additional cabling required.

Compatible with Intel® ThunderboltWednesday, July 24, 2013 3:03:47 PMrade;, when connected directly to a supporting DisplayPort over Thunderbolt I/O port, the adapter supports resolutions up to 1920x1200 (WUXGA).

MDP2DVIMM6B is a passive adapter that requires a dual-mode DisplayPort port (DisplayPort++), meaning that DVI and HDMI signals can also be passed through the port.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Connect your existing DVI display device (monitor, projector) to a Mini DisplayPort output device
- Ideal for using your DVI monitor as a secondary display

Features

- 1x Male Mini DisplayPort connector, 1x Male DVI connector
- Supports resolutions up to 1920x1200 (WUXGA) and HDTV resolutions up to 1080p
- Compatible with Intel® Thunderbolt[™] devices that are capable of outputting a DisplayPort signal

uk.startech.com 0800 169 0408



Hard-to-find made easy*

Technical Specifications

Warranty	2 Years
Audio	No
Chipset ID	NXP 3361
Converter Type	Passive
Output Signal	DVI-D (DVI Digital)
Connector A	1 - Mini-DisplayPort (20 pin) Male
Connector B	1 - DVI-D (25 pin) Male
Maximum Cable Length	1.8 m [6 ft]
Wide Screen Supported	Yes
Maximum Digital Resolutions	1920x1200 / 1080p
Color	Black
Product Height	15 mm [0.6 in]
Product Width	40 mm [1.6 in]
Product Length	1830 mm [72 in]
Product Weight	110 g [3.9 oz]
Humidity	40%-85%RH
Operating Temperature	0°C to 60°C (32°F to 140°F)
Storage Temperature	-10°C to 70°C (14°F to 158°F)
System and Cable Requirements	DP++ (DisplayPort++) port required from video card or video source for DVI and HDMI® signal pass-through
Included in Package	1 - Mini DisplayPort® to DVI Adapter
Shipping (Package) Weight	0.1 kg [0.3 lb]

Certifications, Reports and Compatibility

