

LRD10

TeSys D thermal overload relays - 4...6 A - class 10A



Main

| | |
|-------------------------------------|--|
| Commercial Status | Commercialised |
| Range of product | TeSys D thermal overload relays |
| Product or component type | Differential thermal overload relay |
| Device short name | LRD |
| Relay application | Motor protection |
| Product compatibility | LC1D09...LC1D38 |
| Network type | AC DC |
| Overload tripping class | Class 10A conforming to IEC 60947-4-1 |
| Thermal protection adjustment range | 4...6 A |
| [Ui] rated insulation voltage | 690 V power circuit conforming to IEC 60947-4-1 600 V power circuit conforming to UL 600 V power circuit conforming to CSA |

Complementary

| | |
|--|---|
| Network frequency | 0...400 Hz |
| Mounting support | Under contactor |
| Tripping threshold | 1.14 +/- 0.06 I _r conforming to IEC 60947-4-1 |
| [I _{th}] conventional free air thermal current | 5 A for signalling circuit |
| Permissible current | 0.22 A at 125 V DC-13 for signalling circuit 3 A at 120 V AC-15 for signalling circuit |
| [U _e] rated operational voltage | 690 V AC 0...400 Hz |
| [U _{imp}] rated impulse withstand voltage | 6 kV |
| Phase failure sensitivity | Tripping current 130 % of I _r on two phase, the last one at 0 |
| Temperature compensation | -30...60 °C |
| Connections - terminals | Power circuit: screw clamp terminals 1 cable(s) 1...6 mm ² - cable stiffness: solid - without cable end Power circuit: screw clamp terminals 1 cable(s) 1...4 mm ² - cable stiffness: flexible - with cable end Power circuit: screw clamp terminals 1 cable(s) 1.5...10 mm ² - cable stiffness: flexible - without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: solid - without cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: flexible - with cable end Control circuit: screw clamp terminals 2 cable(s) 1...2.5 mm ² - cable stiffness: flexible - without cable end |
| Tightening torque | Power circuit: 1.7 N.m - on screw clamp terminals Control circuit: 1.7 N.m - on screw clamp terminals |
| Width | 45 mm |
| Depth | 70 mm |
| Product weight | 0.124 kg |
| Quantity per set | Set of 10 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|---|
| Standards | EN 60947-4-1 EN 60947-5-1 IEC 60947-4-1 IEC 60947-5-1 UL 508 CSA C22.2 No 14 |
| Product certifications | ATEX INERIS BV CCC CSA DNV GL GOST RINA UL LROS |
| Protective treatment | TH conforming to IEC 60068 |
| IP degree of protection | IP2x conforming to VDE 0106 |
| Ambient air temperature for operation | -20...60 °C without derating conforming to IEC 60947-4-1 |
| Ambient air temperature for storage | -60...70 °C |
| Fire resistance | 850 °C conforming to IEC 60695-2-1 |
| Flame retardance | V1 conforming to UL 94 |
| Mechanical robustness | Shocks 15 Gn for 11 ms IEC 60068-2-7 Vibrations 6 Gn IEC 60068-2-6 |
| Dielectric strength | 6 kV at 50 Hz conforming to 60255-5 |

RoHS compliance

| | |
|--------------------------------|-----------|
| RoHS EUR status | Compliant |
| RoHS EUR conformity date(YYWW) | 0631 |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|