

# Terminal Block





**RoHS  
Compliant**



## Specifications:

Current Rating	: 16Amp. AC 300V
Insulation Withstands Volt	: AC2,000V min.
Insulation Resistance	: >2,000MΩ DC500V
Operation Temperature	: -40°C to +105°C
Wire Range	: 14AWG to 24AWG
Screw Torque	: 4.5lb-inch



Dimensions : Millimetres (Inches)

## Part Number Table

Description	Poles	A (mm)	A (Inch)	Part Number
Terminal Block	2	10.16	0.4	MC200-50802
	3	15.24	0.6	MC200-50803
	4	20.32	0.8	MC200-50804
	5	25.4	1	MC200-50805
	6	30.48	1.2	MC200-50806
	7	35.56	1.4	MC200-50807
	8	40.64	1.6	MC200-50808
	9	45.72	1.8	MC200-50809
	10	50.8	2	MC200-50810
	11	55.88	2.2	MC200-50811
	12	60.96	2.4	MC200-50812

No.	Material		Plating/Finish
1.	Insulating Body	Polyamide	-
2.	Contact	Phosphor Bronze	Tin Plated
3.	Cage clamp	Brass	Ni Plated
4.	Screw	Steel	Ni Plated

**Important Notice :** This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2012.

